



US008087593B2

(12) **United States Patent**
Leen

(10) **Patent No.:** **US 8,087,593 B2**
(45) **Date of Patent:** **Jan. 3, 2012**

(54) **HVAC CONTROLLER WITH QUICK SELECT FEATURE**

(75) Inventor: **Cary Leen**, Hammond, WI (US)

(73) Assignee: **Honeywell International Inc.**,
Morristown, NJ (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 439 days.

(21) Appl. No.: **12/323,226**

(22) Filed: **Nov. 25, 2008**

(65) **Prior Publication Data**

US 2009/0140056 A1 Jun. 4, 2009

Related U.S. Application Data

(60) Provisional application No. 60/991,626, filed on Nov. 30, 2007.

(51) **Int. Cl.**

B64D 13/00 (2006.01)

F24F 7/00 (2006.01)

G05B 11/01 (2006.01)

G05B 15/00 (2006.01)

(52) **U.S. Cl.** **236/91 D**; 236/49.3; 700/17; 700/83

(58) **Field of Classification Search** 236/49.3,
236/91 D, 46 R, 47, 94; 700/17, 83, 275,
700/276

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,079,366 A 3/1978 Wong
4,174,807 A 11/1979 Smith et al.
4,206,872 A 6/1980 Levine

4,224,615 A 9/1980 Penz
4,264,034 A 4/1981 Hyltin et al.
4,296,334 A 10/1981 Wong et al.
4,298,946 A 11/1981 Hartsell et al.
4,308,991 A 1/1982 Peinetti et al.
4,332,352 A 6/1982 Jaeger
4,337,822 A 7/1982 Hyltin et al.
4,337,893 A 7/1982 Flanders et al.
4,373,664 A 2/1983 Barker et al.
4,379,483 A 4/1983 Farley
4,382,544 A 5/1983 Stewart
4,386,649 A 6/1983 Hines et al.
4,388,692 A 6/1983 Jones et al.
4,431,134 A 2/1984 Hendricks et al.
4,442,972 A 4/1984 Sahay et al.
4,446,913 A 5/1984 Krockner
4,479,604 A 10/1984 Didner

(Continued)

FOREIGN PATENT DOCUMENTS

DE 3334117 4/1985

(Continued)

OTHER PUBLICATIONS

Lennox, "Network Control Panel (NCP)," User's Manual, 18 pages, Nov. 1999.

(Continued)


Primary Examiner — Chen Wen Jiang

(74) *Attorney, Agent, or Firm* — Seager, Tulte & Wickhem LLC

(57) **ABSTRACT**

An HVAC controller is described that is configured to be more intuitive and user friendly to program and operate than convention HVAC controllers. In some instances, the HVAC controller may include a touch screen interface that provides greater flexibility in displaying information to the user and/or soliciting information from the user.

27 Claims, 100 Drawing Sheets




U.S. PATENT DOCUMENTS					
4,503,471 A	3/1985	Hanajima et al.	6,318,639 B1	11/2001	Toth
4,506,827 A	3/1985	Jamieson et al.	6,330,806 B1	12/2001	Beaverson et al.
4,556,169 A	12/1985	Zervos	6,351,693 B1	2/2002	Monie et al.
4,606,401 A	8/1986	Levine et al.	6,344,861 B1	3/2002	Naughton et al.
4,621,336 A	11/1986	Brown	6,398,118 B1	6/2002	Rosen et al.
4,622,544 A	11/1986	Bially et al.	6,453,687 B2	9/2002	Sharood et al.
4,628,201 A	12/1986	Schmitt	6,466,132 B1	10/2002	Caronna et al.
4,646,964 A	3/1987	Parker et al.	6,478,233 B1	11/2002	Shah
4,717,333 A	1/1988	Carignan	6,502,758 B2	1/2003	Cottrell
4,725,001 A	2/1988	Carney et al.	6,518,953 B1	2/2003	Armstrong
4,837,731 A	6/1989	Levine et al.	6,518,957 B1	2/2003	Lehtinen et al.
4,881,686 A	11/1989	Mehta	6,546,419 B1	4/2003	Humpleman et al.
4,918,439 A	4/1990	Wozniak et al.	6,556,899 B1	4/2003	Harvey et al.
4,948,040 A	8/1990	Kobayashi et al.	6,578,770 B1	6/2003	Rosen
4,992,779 A	2/1991	Sugino et al.	6,580,950 B1	6/2003	Johnson et al.
4,997,029 A	3/1991	Otsuka et al.	6,581,846 B1	6/2003	Rosen
5,005,365 A	4/1991	Lynch	6,595,430 B1	7/2003	Shah
5,012,973 A	5/1991	Dick et al.	6,608,560 B2	8/2003	Abrams
5,038,851 A	8/1991	Mehta	6,619,555 B2	9/2003	Rosen
5,053,752 A	10/1991	Epstein et al.	6,621,507 B1	9/2003	Shah
5,065,813 A	11/1991	Berkeley et al.	6,726,112 B1	4/2004	Ho
5,086,385 A	2/1992	Launey et al.	6,786,421 B2	9/2004	Rosen
5,088,645 A	2/1992	Bell	6,789,739 B2	9/2004	Rosen
5,140,310 A	8/1992	DeLuca et al.	6,868,293 B1	3/2005	Schurr et al.
5,161,606 A	11/1992	Berkeley et al.	7,050,026 B1	5/2006	Rosen
5,170,935 A	12/1992	Federspiel et al.	7,055,759 B2	6/2006	Wacker et al.
5,172,565 A	12/1992	Wruck et al.	7,083,109 B2	8/2006	Pouchak
5,181,653 A	1/1993	Foster et al.	7,152,806 B1	12/2006	Rosen
5,187,797 A	2/1993	Nielsen et al.	7,156,318 B1	1/2007	Rosen
5,230,482 A	7/1993	Ratz et al.	7,225,054 B2	5/2007	Amundson et al.
5,238,184 A	8/1993	Adams	7,232,075 B1	6/2007	Rosen
5,251,813 A	10/1993	Kniepkamp	2001/0029585 A1	10/2001	Simon et al.
5,259,445 A	11/1993	Pratt et al.	2001/0042684 A1	11/2001	Essalik et al.
5,329,991 A	7/1994	Mehta et al.	2001/0052459 A1	12/2001	Essalik et al.
5,348,078 A	9/1994	Dushane et al.	2002/0005435 A1	1/2002	Cottrell
5,386,577 A	1/1995	Zenda	2002/0011923 A1	1/2002	Cunningham et al.
5,404,934 A	4/1995	Carlson et al.	2002/0022991 A1	2/2002	Sharood et al.
5,414,618 A	5/1995	Mock et al.	2002/0060701 A1	5/2002	Naughton et al.
5,482,209 A	1/1996	Cochran et al.	2002/0092779 A1	7/2002	Essalik et al.
5,526,422 A	6/1996	Keen	2002/0096572 A1	7/2002	Chene et al.
5,537,106 A	7/1996	Mitsubishi	2002/0138184 A1	9/2002	Kipersztok et al.
5,566,879 A	10/1996	Longtin	2002/0173929 A1	11/2002	Seigel
5,570,837 A	11/1996	Brown et al.	2003/0000692 A1	1/2003	Okano et al.
5,673,850 A	10/1997	Uptegraph	2003/0014179 A1	1/2003	Szukala et al.
5,682,206 A	10/1997	Wehmeyer et al.	2003/0033156 A1	2/2003	McCall
5,732,691 A	3/1998	Maiello et al.	2003/0033230 A1	2/2003	McCall
5,782,296 A	7/1998	Mehta	2003/0034897 A1	2/2003	Shamoon et al.
5,818,428 A	10/1998	Eisenbrandt et al.	2003/0034898 A1	2/2003	Shamoon et al.
5,873,519 A	2/1999	Beilfuss	2003/0074489 A1	4/2003	Steger et al.
5,886,697 A	3/1999	Naughton et al.	2003/0121652 A1	7/2003	Carey et al.
5,902,183 A	5/1999	D'Souza	2003/0123224 A1	7/2003	LaCroix et al.
5,915,473 A	6/1999	Ganesh et al.	2003/0136135 A1	7/2003	Kim et al.
5,937,942 A	8/1999	Bias et al.	2003/0142121 A1	7/2003	Rosen
5,947,372 A	9/1999	Tiernan	2003/0150926 A1	8/2003	Rosen
5,950,709 A	9/1999	Krueger et al.	2003/0150927 A1	8/2003	Rosen
6,009,355 A	12/1999	Obradovich et al.	2003/0177012 A1	9/2003	Drennan
6,020,881 A	2/2000	Naughton et al.	2004/0074978 A1	4/2004	Rosen
6,032,867 A	3/2000	Dushane et al.	2004/0193324 A1	9/2004	Hoog et al.
6,059,195 A	5/2000	Adams et al.	2004/0245352 A1	12/2004	Smith
6,081,197 A	6/2000	Garrick et al.	2004/0262410 A1	12/2004	Hull
6,101,824 A	8/2000	Meyer et al.	2007/0045429 A1 *	3/2007	Chapman et al. 236/46 C
6,104,963 A	8/2000	Cebasek et al.	FOREIGN PATENT DOCUMENTS		
6,119,125 A	9/2000	Gloudeman et al.	EP	0070414	1/1983
6,121,875 A	9/2000	Hamm et al.	EP	0434926	8/1995
6,140,987 A	10/2000	Stein et al.	EP	0678204	3/2000
6,141,595 A	10/2000	Gloudeman et al.	EP	0985994	3/2000
6,149,065 A	11/2000	White et al.	EP	1033641	9/2000
6,154,681 A	11/2000	Drees et al.	EP	1074009	7/2001
6,167,316 A	12/2000	Gloudeman et al.	FR	2711230	4/1995
6,192,282 B1	2/2001	Smith et al.	WO	WO 97/11448	3/1997
6,196,467 B1	3/2001	Dushane et al.	WO	WO 97/39392	10/1997
6,208,331 B1	3/2001	Singh et al.	WO	WO 00/43870	7/2000
6,216,956 B1	4/2001	Ehlers et al.	WO	WO 01/52515	7/2001
6,236,326 B1	5/2001	Murphy	WO	WO 01/79952	10/2001
6,259,074 B1	7/2001	Brunner et al.			
6,285,912 B1	9/2001	Ellison et al.			
6,290,140 B1	9/2001	Pesko et al.			
6,315,211 B1	11/2001	Sartain et al.			

OTHER PUBLICATIONS

- "CorAccess Systems/In Home," <http://web.archive.org/web/20011212084427/www.coraccess.com/home.html>, 1 page, copyright 2001, printed Aug. 19, 2004.
- "HAI Company Background," http://www.homeauto.com/AboutHAI/abouthai_main.htm, 2 pages, printed Aug. 19, 2004.
- "High-tech options take hold in new homes—200-08-28—Dallas Business Journal," <http://bizjournals.com/dallas/stories/2000/08/28/focus4>, 3 pages, dated Aug. 28, 2000, printed Aug. 19, 2004.
- "Home Toys Review—TouchLinc", <http://www.hometoys.com/htinews/aug99/reviews/touchlinc/touchlinc.htm>, 3 pages, dated Aug. 1999, printed Aug. 20, 2004.
- "HTI News Release," <http://www.hometoys.com/htinews/apr99/releases/ha101.htm>, 3 pages, Apr. 1999.
- "Mark of Excellence Award Finalist Announced," <http://64.233.167.104/search?Q=cache:ciOA2YtYaBIJ:www.hometoys.com/releases/mar...>, 6 pages, Leopard Touchscreen on p. 2, dated prior to Mar. 4, 2000, printed Aug. 20, 2004.
- "Product Review—Philips Pronto Remote Control," http://hometheaterhifi.com/volume_6_2/philipsprontoremotecontrol.html, 5 pages, dated May 1999, printed Aug. 20, 2004.
- "RC X10 Automation Forum: Control your Heating and Cooling System with Pronto(1/1)," <http://www.remotecentral.com/cgi-bin/mboard/rc-x10/thread.cgi?12>, 2 pages, dated Apr. 23, 1999, printed Aug. 20, 2004.
- "Spotlight on integrated systems," Custom Builder, V8, N2, p. 66(6), Mar.-Apr. 1993.
- "Vantage Expands Controls for Audio/Video, HVAC and Security," <http://www.hometoys.com/htinews/aug99/releases/vantage03.htm>, 2 pages, dated Aug. 3, 1999, printed Aug. 20, 2004.
- ADI, "Leopard User Manual," 93 pages, 2001.
- Adicon 2500, "The Automator," 4 pages, Oct.-Dec. 2000.
- ADT Security Services, "iCenter Advanced User Interface 8142ADT," Installation and Setup Guide, 4 pages, May 2001; First Sale Feb. 2001.
- Aprilaire Electronic Thermostats Models 8344, 8346, 8348, 8363, 8365, 8366 Operating Instructions, 8 pages, 2003.
- Aube Technologies, Electronic Thermostat for Heating System Model TH135-01, 5 pages, Aug. 14, 2001.
- Aube Technologies, TH140-28 Electronic Programmable Thermostat, Installation Instructions and User Guide, pp. 1-4, Jan. 22, 2004.
- AutomatedBuildings.com Article—"Thin Client" Solutions, "Pressure, Air Flow, Temperature, Humidity & Valves," Dwyer Instruments, Inc., 5 pages, printed Sep. 20, 2004.
- Blake et al., "Seng 310 Final Project Demo Program" Illustration, 3 pages, Apr. 6, 2001.
- Blake et al., "Seng 310 Final Project" Report, dated Apr. 6, 2001.
- Blister Pack Insert from a Ritetemp 8082 Touch Screen Thermostat Product, 2 pages, 2002.
- Braeburn Model 3000 Owner's Manual, pp. 1-13, 2001.
- Braeburn Model 5000 Owners Manual, pp. 1-17, 2001.
- BRK Electronics Maximum Protection Plus Ultimate Convenience Smoke Alarm, 24 pages, Sep. 2000.
- BRK First Alert, User's Manual, Smoke and Fire Alarms, pp. 1-7, Nov. 2002.
- Business Wire, "MicroTouch Specialty Products Group to Capitalize on Growing Market for Low-Cost Digital Matrix Touchscreens," p. 1174 (2 pages), Jan. 6, 1999.
- Cardio Manual, available at <http://www.secant.ca/En/Documentation/Cardio2e-Manual.pdf>, Cardio Home Automation Inc., 55 pages, printed Sep. 28, 2004.
- Cardio, by Secant; <http://www.hometoys.com/htinews/apr98/reviews/cardio.htm>, "HTI News Review," Feb. 1998, 5 pages, printed Sep. 14, 2004.
- Carrier Microelectronic Programmable Thermostat Owner's Manual, pp. 1-24, May 1994.
- Carrier TSTATCCRFO1 Programmable Digital Thermostat, pp. 1-21, prior to Apr. 21, 2005.
- Carrier, "Programmable Dual Fuel Thermostat," Installation, Start-Up & Operating Instructions, pp. 1-12, Oct. 1998.
- Carrier, "Programmable Thermostats," Installation, Start-Up & Operating Instructions, pp. 1-16, Sep. 1998.
- Carrier, "Standard Programmable Thermostat," Homeowner's Manual, pp. 1-8 pages, 1998.
- Carrier, "Thermostat Control," Installation, Start-Up, and Operating Instructions, pp. 1-12, Aug. 1999.
- CorAccess, "Companion 6," User Guide, pp. 1-20, Jun. 17, 2002.
- Danfoss RT51/51RF & RT52/52RF User Instructions, 2 pages, Jun. 2004.
- DeKoven et al., "Designing Collaboration in Consumer Products," 2 pages, 2001.
- DeKoven et al., "Measuring Task Models in Designing Intelligent Products," 2 pages, Jan. 13-16, 2002.
- Domotique Secant Home Automation—Web Page, available at <http://www.secant.ca/En/Company/Default.asp>, 1 page, printed Sep. 28, 2004.
- Firex Smoke Alarm, Ionization Models AD, ADC Photoelectric Model Pad, 4 pages, prior to Apr. 21, 2005.
- Freudenthal et al., "Communicating extensive smart home functionality to users of all ages: the design of a mixed-initiative multimodal thermostat-interface," pp. 34-39, Mar. 12-13, 2001.
- Gentex Corporation, HD135, 135° Fixed Temperature Heat Detector AC Powered, 120V, 60Hz With Battery Backup, Installation Instructions—Owner's Information, pp. 1-5, Jun. 1, 1998.
- Gentex Corporation, 9000 Series, Photoelectric Type Single Station/Multi-Station Smoke Alarms AC Powered With Battery Backup, Installation Instructions—Owner's Information, pp. 9-1 to 9-6, Jan. 1, 1993.
- Honeywell Bravis Deluxe Programmable Thermostat, pp. 1-20, 2002.
- Honeywell Bravis T8602C Chronotherm IV Deluxe Programmable Thermostats, Installation Instructions, pp. 1-12, 2002.
- Honeywell CT8602C Professional Fuel Saver Thermostat, pp. 1-6, 1995.
- Honeywell Electronic Programmable Thermostat, Owner's Guide, pp. 1-20, 2003.
- Honeywell Electronic Programmable Thermostats, Installation Instructions, pp. 1-8, 2003.
- Honeywell News Release, "Honeywell's New Sysnet Facilities Integration System for Boiler Plant and Combustion Safety Processes," 4 pages, Dec. 15, 1995.
- Honeywell T8002 Programmable Thermostat, Installation Instructions, pp. 1-8, 2002.
- Honeywell T8602A,B,C,D and TS8602A,C Chronotherm III Fuel Saver Thermostats, Installation Instructions, pp. 1-12, 1995.
- Honeywell T8602D Chronotherm IV Deluxe Programmable Thermostats, Installation Instructions, pp. 1-12, 2002.
- Honeywell TH8000 Series Programmable Thermostats, Owner's Guide, pp. 1-44, 2004.
- Honeywell, "Introduction of the 57350A Honeywell WebPAD Information Appliance," Home and Building Control Bulletin, 2 pages, Aug. 29, 2000; Picture of WebPad Device with touch screen, 1 Page; and screen shots of WebPad Device, 4 pages.
- Honeywell, "W7006A Home Controller Gateway User Guide," 31 pages, Jul. 2001.
- Honeywell, MagicStat® CT3200 Programmable Thermostat, Installation and Programming Instructions, pp. 1-24, 2001.
- http://www.cc.gatech.edu/computing/classes/cs6751_94_fall/groupe/climate-2/node1.html, "Contents," 53 pages, printed Sep. 20, 2004.
- http://www.ritetemp.info/rtMenu_13.html, Rite Temp 8082, 8 pages, printed Jun. 20, 2003.
- <http://www.thermostatsales.com>, Robertshaw, "9610 Digital Programmable Thermostat," 3 pages, printed Jun. 17, 2004.
- <http://www.thermostatsales.com>, Robertshaw, "9700 Deluxe Programmable Thermostat," 3 pages, printed Jun. 17, 2004.
- <http://www.thermostatsales.com>, Robertshaw, "9710 Deluxe Programmable Thermostat," 3 pages, printed Jun. 17, 2004.
- <http://www.thermostatsales.com>, Robertshaw, "9720 Deluxe Programmable Thermostat," 3 pages, printed Jun. 17, 2004.
- Hunter, "44200/44250," Owner's Manual, 32 pages, prior to Jul. 7, 2004.
- Hunter, "44300/44350," Owner's Manual, 35 pages, prior to Jul. 7, 2004.
- Hunter, "Auto Saver 550," Owner's Manual Model 44550, 44 pages, prior to Jul. 7, 2004.

- Install Guide for Ritetemp Thermostat 8082, 6 pages, 2002.
- Invensys™, “9700i 9701i 9715i 9720i Deluxe Programmable Thermostats,” User’s Manual, pp. 1-28, prior to Jul. 7, 2004.
- Lux ELV1 Programmable Line Voltage Thermostat, Installation Instructions, 3 pages, prior to Jul. 7, 2004.
- Lux TX500 Series Smart Temp Electronic Thermostat, 3 pages, prior to Jul. 7, 2004.
- Lux TX9000 Installation, 3 pages, prior to Apr. 21, 2005.
- Lux, “511 Series Smart Temp Electronic Thermostat,” Owner’s Manual, 3 pages, prior to Jul. 7, 2004.
- Lux, “600 Series Smart Temp Electronic Thermostat,” Owner’s Manual, 3 pages, prior to Jul. 7, 2004.
- Lux, “602 Series Multi-Stage Programmable Thermostat,” Owner’s Manual, 2 pages, prior to Jul. 7, 2004.
- Lux, “605/2110 Series Programmable Heat Pump Thermostat,” Owner’s Manual, 3 pages, prior to Jul. 7, 2004.
- Lux, “700/9000 Series Smart Temp Electronic Thermostat,” Owner’s Manual, 3 pages, prior to Jul. 7, 2004.
- Lux, “PSPH521 Series Programmable Heat Pump Thermostat,” Owner’s Manual, 3 pages, prior to Jul. 7, 2004.
- Lux, “TX1500 Series Smart Temp Electronic Thermostat,” Owner’s Manual, 6 pages, prior to Jul. 7, 2004.
- METASYS, “HVAC PRO for Windows User’s Manual,” 308 pages, 1998.
- Operation Manual for Ritetemp Touch Screen Thermostat 8082, 8 pages, 2002.
- Proliphix, “Web Enabled IP Thermostats, Intelligent HVAC Control,” Proliphix Inc., 2 pages, on or before Aug. 28, 2004.
- Proliphix, “Web Enabled IP Thermostats, Ultimate in Energy Efficiency!,” Proliphix Inc., 2 pages, on or before Aug. 28, 2004.
- Proliphix, Inc., “NT10e & NT20e,” 54 pages, on or before Aug. 30, 2005.
- Quick Start Guide for Ritetemp Thermostat 8082, 1 page, 2002.
- Remote Control Power Requirement for Ritetemp Thermostat 8082, 1 page, 2002.
- Ritetemp Operation 8029, 3 pages, Jun. 19, 2002.
- Ritetemp Operation 8050, 5 pages, Jun. 26, 2002.
- Ritetemp Operation 8085, pp. 1-6, prior to Apr. 21, 2005.
- Sealed Unit Parts Co., Inc., Supco & CTC Thermostats . . . loaded with features, designed for value!, 6 pages, prior to Apr. 21, 2005.
- Totaline Model P474-1035 Owner’s Manual Programmable 5-2 Day Digital Thermostat, pp. 1-21, Apr. 2003.
- Totaline Star CPE230RF, Commercial Programmable Thermostat Wireless Transmitter, Owner’s Manual, pp. 1-16, Oct. 1998.
- Totaline Star P/N P474-0130 Non-Programmable Digital Thermostat Owner’s Manual, pp. 1-22, prior to Apr. 21, 2005.
- Totaline, “1 For All programmable Digital Thermostat,” Owner’s Manual P/N P374-1100FM, 23 pages, Nov. 1998.
- Totaline, “1 For All Programmable Digital Thermostat,” Owner’s Manual P/N P474-1050, 21 pages, Nov. 1998.
- Totaline, “1 For All Programmable Digital Thermostat,” Owner’s Manual P/N P374-1100, 24 pages, Apr. 2001.
- Totaline, “Intellistat Combination Temperature and Humidity Control,” Owner’s Manual P/N P374-1600, 25 pages, Jun. 2001.
- Totaline, “Programmable Thermostat Configurable for Advanced Heat Pump or Dual Fuel Operation,” Owner’s Manual P/N P374-1500, 24 pages, Jun. 1999.
- Totaline, “Instructions P/N P474-1010,” Manual, 2 pages, Dec. 1998.
- Totaline, “Programmable Thermostat,” Homeowner’s Guide, 27 pages, Dec. 1998.
- Trouble Shooting Guide for Ritetemp Thermostat 8082, 1 page, 2002.
- Visor Handheld User Guide, 280 pages, Copyright 1999-2000.
- Warmly Yours, “Model TH111GFCI-P (120 VAC),” Manual, pp. 1-4, prior to Jul. 7, 2004.
- White-Rodgers 1F80-224 Programmable Electronic Digital Thermostat, Installation and Operation Instructions, 8 pages, prior to Apr. 21, 2005.
- White-Rodgers Comfort-Set III Thermostat, pp. 1-44, prior to Jul. 7, 2004.
- White-Rodgers Installation Instructions for Heating & Air Conditioning IF78 Non-Programmable Thermostat, 6 pages, prior to Apr. 21, 2005.
- White-Rodgers Installation Instructions for Heating & Air Conditioning IF78 5/2 Day Programmable Thermostat, 7 pages, prior to Jul. 7, 2004.
- White-Rodgers, “Installation Instructions for Heating & Air Conditioning IF72 5/2 Day Programmable Heat Pump Thermostat,” 8 pages, prior to Jul. 7, 2004.
- White-Rodgers, “Comfort-Set 90 Series Thermostat,” Manual, pp. 1-24, prior to Jul. 7, 2004.
- White-Rodgers, 1F80-240 “(for Heating Only systems) Programmable Electronic Digital Thermostat,” Installation and Operation Instructions, 8 pages, prior to Jul. 7, 2004.
- White-Rodgers, 1F80-241 “Programmable Electronic Digital Thermostat,” Installation and Operation Instructions, 6 pages, prior to Jul. 7, 2004.
- White-Rodgers, 1F80-261 “Programmable Electronic Digital Thermostat,” Installation and Operation Instructions, 8 pages, prior to Jul. 7, 2004.
- White-Rodgers, 1F81-261 “Programmable Electronic Digital Multi-Stage Thermostat,” Installation and Operation Instructions, 8 pages, prior to Jul. 7, 2004.
- White-Rodgers, 1F82-261 “Programmable Electronic Digital Heat Pump Thermostat,” Installation and Operation Instructions, 8 pages, prior to Jul. 7, 2004.
- White-Rodgers, Comfort-Set 90 Series Premium, 4 pages, prior to Apr. 21, 2005.
- www.icmcontrols.com, Simplecomfort, SC3000 Single Stage Heat/Single Stage Cool or Single Stage Heat Pump/Manual Changeover, 1 page, prior to Jul. 7, 2004.
- www.icmcontrols.com, Simplecomfort, SC3001 Single Stage Heat/Single Stage Cool or Single Stage Heat Pump/Manual Changeover, 1 page, prior to Jul. 7, 2004.
- www.icmcontrols.com, Simplecomfort, SC3006 Single Stage Heat/Single Stage Cool or Single Stage Heat Pump/Manual Changeover, 1 page, prior to Jul. 7, 2004.
- www.icmcontrols.com, Simplecomfort, SC3201 2 Stage Heat Pump Manual Changeover, 1 page, prior to Jul. 7, 2004.
- www.icmcontrols.com, Simplecomfort, SC3801 2 Stage Heat/2 Stage Cool 2 Stage Heat Pump/Audio Changeover, 1 page, prior to Jul. 7, 2004.
- AED Electronics, Inc., “Presenting Climatouch the Most Innovative Thermostat in the World!,” 2 pages, prior to Nov. 30, 2007.
- Climatouch, User Manual, Climatouch CT03TSB Thermostat, Climatouch CT03TSHB Thermostat with Humidity Control, Outdoor UHF Temperature Transmitter 217S31, 19 pages, printed Sep. 15, 2004.
- Carrier, “Edge Performance Programmable Owner’s Manual,” 64 pages, 2007.
- Lux, “9000RF Remote Instructions,” 2 pages, prior to Nov. 30, 2007.
- Operation Manual for Ritetemp Touch Screen Thermostat 8082, 8 pages, 2002.
- Totaline, “P/N P374-0431 Thermostat Remote Control and Receiver,” Owner’s Manual, 11 pages, prior to Nov. 30, 2007.
- Totaline, “Wireless Remote Sensor, Model P474-0401-1RF/REC,” 2 pages, prior to Nov. 30, 2007.
- Totaline, “P474-1100RF, P474-1100REC Wireless Thermostat,” 1 page, prior to Nov. 30, 2007.
- Totaline, “Wireless Programmable Digital Thermostat,” Owner’s Manual P474-1100RF, 21 pages, 2000.
- Honeywell, “Excel Building Supervisor-Integrated R7044 and FS90 Ver. 2.0,” Operator Manual, 70 pages, Apr. 1995.
- Trane, “System Programming, Tracer Summit Version 14, BMTW-SVP01D-EN,” 623 pages, 2002.

* cited by examiner

*Figure 1*




Figure 2




Figure 3




Figure 4




Figure 5




Figure 6




Figure 7




Figure 8




Figure 9




Figure 10




Figure 11






Figure 12

*Figure 13**Figure 14*




Figure 15





Figure 16

*Figure 17*




Figure 18




Figure 19




Figure 20




Figure 21




Figure 22




Figure 23

280

Please press a time period below to schedule.



Monday-Friday			
254	256	258	260
72° 78° 6:00A- 8:00A WAKE	62° 85° 8:00A- 6:00P LEAVE	70° 78° 6:00P- 10:00P RETURN	62° 82° 10:00P- 6:00A SLEEP
Done 282			

Figure 24

284

Please wait while the system
saves your changes.

Figure 25

*Figure 26**Figure 27*




Figure 28




Figure 29




Figure 30




Figure 31




Figure 32




Figure 33




Figure 34




Figure 35




Figure 36




Figure 37




Figure 38




Figure 39




Figure 40






Figure 41

*Figure 42**Figure 43*




Figure 44




Figure 45




Figure 46






Figure 47

*Figure 48**Figure 49*

494

496 → Please enter the date you will Return from your Vacation.

340

MONTH February

340

DAY 3

342

342

500

498

Back

Next

314

318

Figure 50

502

504 → Please set the time that you will Return on February 3.

RETURN 12:30 PM

340

342

506



Back

Next

314

318

Figure 51

*Figure 52**Figure 53*




Figure 54




Figure 55




Figure 56




Figure 57




Figure 58




Figure 59




Figure 60




Figure 61




Figure 62




Figure 63




Figure 64








Figure 65

*Figure 66**Figure 67*

*Figure 68**Figure 69*




Figure 70




Figure 71







Figure 72

*Figure 73*

*Figure 74**Figure 75*




Figure 76






Figure 77

*Figure 78**Figure 79*




Figure 80










Figure 81

*Figure 82**Figure 83*

*Figure 84**Figure 85*

*Figure 86**Figure 87*




Figure 88








Figure 89

*Figure 90**Figure 91*

*Figure 92**Figure 93*




Figure 94




Figure 95




Figure 96




Figure 97




Figure 98






Figure 99

*Figure 100**Figure 101*

966

968 → Please set the date that you will Return Home Late.

Month	^ 932	Day	^ 932
February 928	∇ 934	1 930	∇ 934

Cancel 936 Next 952

Figure 102

970

972 → Please set the time that you will Return Home Late.

Return	^ 932
12:30 PM 974	∇ 934

Back 960 Next 952

Figure 103




Figure 104




Figure 105




Figure 106




Figure 107




Figure 108












Figure 109

*Figure 110**Figure 111*

*Figure 112**Figure 113*

*Figure 114**Figure 115*

*Figure 116**Figure 117*




Figure 118




Figure 119




Figure 120




Figure 121




Figure 122








Figure 123

*Figure 124**Figure 125*

*Figure 126**Figure 127*




Figure 128




Figure 129




Figure 130




Figure 131




Figure 132








Figure 133

*Figure 134**Figure 135*

*Figure 136**Figure 137*




Figure 138




Figure 139




Figure 140




Figure 141




Figure 142




Figure 143




Figure 144




Figure 145




Figure 146






Figure 147

*Figure 148**Figure 149*




Figure 150




Figure 151




Figure 152






Figure 153

*Figure 154**Figure 155*




Figure 156




Figure 157




Figure 158




Figure 159




Figure 160




Figure 161




Figure 162






Figure 163

*Figure 164**Figure 165*




Figure 166








Figure 167

*Figure 168**Figure 169*

*Figure 170**Figure 171*




Figure 172






Figure 173

*Figure 174**Figure 175*




Figure 176






Figure 177

*Figure 178**Figure 179*




Figure 180




Figure 181




Figure 182




Figure 183




Figure 184




Figure 185




Figure 186




Figure 187




Figure 188






Figure 189

*Figure 190**Figure 191*




Figure 192




Figure 193




Figure 194




Figure 195

1

**HVAC CONTROLLER WITH QUICK SELECT
FEATURE****PRIORITY**

This application claims priority under 35 U.S.C. § 119 to U.S. Provisional Application having Ser. No. 60/991,626 entitled "HVAC CONTROLLER" filed Nov. 30, 2007, the entirety of which is incorporated herein by reference.

TECHNICAL FIELD

The disclosure pertains generally to HVAC controllers

BACKGROUND

Heating, ventilation, and/or air conditioning (HVAC) systems are often used to control the comfort level within a building or other structure. Many HVAC controllers include a controller that activates and deactivates one or more HVAC components of the HVAC system to affect and control one or more environmental conditions within the building. These environmental conditions can include, but are not limited to, temperature, humidity, and/or ventilation. In many cases, such HVAC controller may include, or have access to, one or more sensors, and may use parameters provided by the one or more sensors to control the one or more HVAC components to achieve desired programmed or set environmental conditions. Because of the increased complexity of such modern HVAC controllers, programming and/or operating such devices can be considered difficult and/or confusing, particularly for novice and/or non-technical users. Thus, there is a need for HVAC controllers that are more intuitive and user friendly to program and operate.

SUMMARY

This disclosure relates to HVAC controllers that are configured to be more intuitive and user friendly to program and operate. In some instances, the disclosure relates to HVAC controllers that include a touch screen interface that provides greater flexibility in displaying information to the user and/or soliciting information from the user, although this is not required.

The above summary is not intended to describe each and every disclosed embodiment or every implementation of the disclosure. The Description that follows more particularly exemplifies the various illustrative embodiments.

BRIEF DESCRIPTION OF THE FIGURES

The following description should be read with reference to the drawings, in which like elements in different drawings are numbered in like fashion. The drawings, which are not necessarily to scale, depict selected embodiments and are not intended to limit the scope of the disclosure. The disclosure may be more completely understood in consideration of the following detailed description of various embodiments in connection with the accompanying drawings, in which:

FIG. 1 is a schematic view of an illustrative but non-limiting HVAC controller;

FIG. 2 is a front view of an illustrative but non-limiting HVAC controller;

FIGS. 3 through 17 provide illustrative but non-limiting examples of home screens that may be displayed upon the HVAC controllers of FIGS. 1 and 2;

2

FIGS. 18 through 46 provide illustrative but non-limiting examples of screens pertaining to creating and/or editing a schedule using the HVAC controllers of FIGS. 1 and 2;

FIGS. 47 through 53 provide illustrative but non-limiting examples of screens pertaining to creating and/or editing a vacation schedule using the HVAC controllers of FIGS. 1 and 2;

FIGS. 54 through 60 provide illustrative but non-limiting examples of screens pertaining to changing and/or viewing humidification and dehumidification settings using the HVAC controllers of FIGS. 1 and 2;

FIGS. 61 through 66 provide illustrative but non-limiting examples of screens pertaining to changing and/or viewing ventilation settings using the HVAC controllers of FIGS. 1 and 2;

FIGS. 67 through 69 provide illustrative but non-limiting examples of screens pertaining to setting system information using the HVAC controllers of FIGS. 1 and 2;

FIGS. 70 through 72 provide illustrative but non-limiting examples of screens pertaining to changing and/or viewing date and time settings using the HVAC controllers of FIGS. 1 and 2;

FIGS. 73 through 95 provide illustrative but non-limiting examples of screens pertaining to changing and/or viewing preferences information using the HVAC controllers of FIGS. 1 and 2;

FIGS. 96 through 112 provide illustrative but non-limiting examples of screens pertaining to temporary schedule changes using the HVAC controllers of FIGS. 1 and 2;

FIGS. 113 through 114 provide illustrative but non-limiting examples of screens pertaining to fan scheduling using the HVAC controllers of FIGS. 1 and 2;

FIG. 115 provides an illustrative but non-limiting example of a screen pertaining to locating a remote control using the HVAC controllers of FIGS. 1 and 2;

FIGS. 116 through 117 provide illustrative but non-limiting examples of screens pertaining to screen cleaning using the HVAC controllers of FIGS. 1 and 2;

FIGS. 118 through 123 provide illustrative but non-limiting examples of screens pertaining to changing and/or viewing security settings using the HVAC controllers of FIGS. 1 and 2; and

FIGS. 124 through 195 provide illustrative but non-limiting examples of screens pertaining to installer setup of the HVAC controllers of FIGS. 1 and 2.

While the invention is amenable to various modifications and alternative forms, specifics thereof have been shown by way of example in the drawings and will be described in detail. It should be understood, however, that the intention is not to limit the invention to the particular embodiments described. On the contrary, the intention is to cover all modifications, equivalents, and alternatives falling within the spirit and scope of the invention.

DESCRIPTION

Generally, the disclosure pertains to simplified interfaces for controllers having programming capabilities. These controllers can be used in a variety of systems such as, for example, HVAC systems, water heater systems, water softener systems, sprinkler systems, security systems, lighting systems, and the like. The Figures depict HVAC controllers. While the present invention is not so limited, an appreciation of various aspects of the invention will be gained through a discussion of the examples provided below.

FIG. 1 is a schematic view of an illustrative HVAC controller 10. In some cases, HVAC controller 10 may be con-

3

sidered to be a thermostat, but this is not required. HVAC controller **10** includes a processor or controller **12** and a user interface **14**. Controller **12** may be adapted to operate in accordance with an algorithm that controls or at least partially controls one or more components of an HVAC system. In some instances, the algorithm may include a number of operating parameters. Examples of components that may be controlled by controller **12** include one or more of a furnace, a boiler for hot water heat or steam heat, a heat pump, an air conditioning unit, a humidifier, a dehumidifier, an air exchanger, an air cleaner, and the like. Controller **12** may, for example, operate in accordance with an algorithm that provides temperature set points, starting and/or ending times, and the like.

User interface **14** may be any suitable interface that permits controller **12** to display and/or solicit information as well as permitting a user to enter data such as temperature set points, humidity set points, starting times, ending times, and the like. In some cases, user interface **14** may include a display and a distinct keypad. A display may be any suitable alphanumeric display. In some instances, a display may include or may be a liquid crystal display (LCD). If desired, user interface **14** may be a touch screen LCD panel that functions as both display and keypad. In some instances, a touch screen LCD panel may be adapted to solicit values for a number of operating parameters and/or to receive said values.

HVAC controller **10** may include a memory block **16** that may be considered as being electrically connected to controller **12**. Memory block **16** may be used to store any desired information, such as the aforementioned control algorithm, set points, and the like. Controller **12** may store information within memory block **16** and may subsequently retrieve the stored information. Memory block **16** may be any suitable type of storage device, such as RAM, ROM, EPROM, a flash drive, a hard drive, and the like.

In some cases, as illustrated, HVAC controller **10** may include a data port **18**. Data port **18** may be configured to communicate with controller **12** and may, if desired, be used to either upload information to controller **12** or to download information from controller **12**. Information that can be uploaded or downloaded may include values of operating parameters. In some instances, data port **18** may be used to upload a previously-created thermostat configuration into HVAC controller **10**, thereby hastening the programming process. In some cases, data port **18** may be used to download a thermostat configuration that has been created using HVAC controller **10**, so that the thermostat configuration may be used in other thermostats. In some cases, data port **18** may be used to upload and/or download information pertaining to an HVAC dealer or contractor.

Data port **18** may be a wireless port such as a Bluetooth™ port or any other wireless protocol. In some cases, data port **18** may be a wired port such as a serial port, a parallel port, a CAT5 port, a USB (universal serial bus) port, or the like. In some instances, data port **18** may be a USB port and may be used to download and/or upload information from a USB flash drive. Other storage devices may also be employed, as desired.

FIG. 2 is a front view of an illustrative HVAC controller **20**. In some cases, HVAC controller **20** may represent a manifestation of HVAC controller **10** (FIG. 1), but this is not required. HVAC controller **20** includes a display **22** that is disposed within a housing **24**. In some cases, display **22** may be a touch screen LCD display. If desired, display **22** may be a dot matrix touch screen LCD display. A dot matrix touch screen LCD display is a touch screen LCD that permits images such as letters, numbers, graphics, and the like to be displayed any-

4

where on the LCD, rather than being confined to predetermined locations such as is the case with a fixed segment LCD. Housing **24** may be formed of any suitable material, such as a polymeric material.

In some cases, HVAC controller **20** may be configured to provide substantial display and/or programming functionality. FIGS. 3 through 15 provide examples of home screens that may be displayed by HVAC controller **20**. In some cases, home screens may include screens that can be accessed by a top level navigational menu. In some cases, a home screen may be a screen that is displayed by HVAC controller **20** as a default display, or when no other data entry is underway. A home screen may, if desired, display one or more parameters relating to environmental conditions such as indoor and/or outdoor temperature and/or humidity, expected weather conditions, and/or the status of any equipment that is at least partially controlled by HVAC controller **20**.

In FIG. 3, HVAC controller **20** is displaying on display **22** a home screen **24** that includes a navigational bar **26** that may be considered as providing top level navigation. In some cases, if desired, navigation bar **26** may include one or more of a HOME button **28**, a FAN button **30**, a HEAT/COOL button **32** and/or a MENU button **34**. The function of each button within navigational bar **26** will be demonstrated, in turn. FIG. 3 is an example of a screen that may be displayed after a user has pushed HOME button **28**.

In some cases, home screen **24** may be considered as having two or more regions. For example, home screen **24** may include a first region **36** and a second region **38**. In some instances, first region **36** may be considered as displaying or otherwise providing primary information while second region **38** may be considered as displaying or otherwise providing secondary information. In some cases, primary information may be information that is considered to be more important, more interesting and/or more useful than secondary information. To illustrate, first region **36** may display one or more of a current temperature reading, a current indoor humidity, a schedule status, and the like. Second region **38** may display one or more of a date and time, an outdoor temperature reading, an outdoor humidity reading, an equipment status, and the like.

Home screen **24** may also include a third region **40** that may be used for displaying and/or adjusting a parameter value such as a parameter that is displayed within first region **36** of home screen **24**. In some cases, for example, third region **40** may include a parameter **42**, an up arrow **44** and a down arrow **46**. The value of parameter **42** may be increased or decreased using, as necessary, up arrow **44** and/or down arrow **46**.

As illustrated, second region **38** may refer to a left-hand section of home screen **24**, third region **40** may refer to a right-hand section of home screen **24** and first region **36** may refer to a center section of home screen **24** that is between second region **38** and third region **40**. In some instances, however, one or more of first region **36**, second region **38** and/or third region **40** may instead be aligned vertically above or below the other regions within home screen **24**, as desired.

In FIG. 4, HVAC controller **20** is displaying on display **22** a home screen **48** that is similar in many ways to home screen **24** (FIG. 3). Home screen **48**, however, includes a third region **50** that may be used to display and/or adjust two different parameter values. For example, third region **50** may, as illustrated, display both a heating temperature set point and a cooling temperature set point, but this is not required. Third region **50** may include a first parameter **52**, a first up arrow **54** and a first down arrow **56**. Third region **50** may include a second parameter **58**, a second up arrow **60** and a second down arrow **62**. First parameter **52** may be adjusted up or

5

down using first up arrow 54 and/or first down arrow 56, as appropriate. Second parameter 58 may be adjusted up or down using second up arrow 60 and/or second down arrow 62, as desired.

In some instances, pressing up arrow 44 and/or down arrow 46 (FIG. 3) may cause HVAC controller 20 to display on display 22 a home screen 64 as shown in FIG. 5. Home screen 64 may, as illustrated, include a hold bar 66 that is displayed along a portion of display 22. Hold bar 66 may include one or more of an adjustable time button 68, a resume schedule button 70, a permanent hold button 72 and a done button 74. The adjustable time button 68 may include an up arrow 76 and a down arrow 78. A user may adjust an ending time for a temperature hold by pressing up arrow 76 and/or down arrow 78, as appropriate. If a user changes their mind, and wishes to instead return to the programmed schedule, they may do so simply by pressing resume schedule button 70. Once they have adjusted the ending time as desired, they may press done button 74.

FIG. 6 is similar to FIG. 5, but includes third region 50 as originally discussed with respect to FIG. 4. FIG. 6 shows a home screen 80 that might be displayed by HVAC controller if a user has pressed or one or more of first up arrow 54, first down arrow 56, second up arrow 60 and/or second down arrow 62 to adjust a temperature set point.

Returning briefly to FIG. 5, if a user presses done button 74, HVAC controller 20 may display on display 22 a home screen 82, as shown in FIG. 7. Home screen 82 may include first region 36, second region 38 and third region 40 as discussed with respect to FIG. 3. However, first region 36 may include a hold status button 84 that displays an ending time for the temporary temperature schedule as well as providing the user with a way to adjust the temporary temperature schedule. If the user had instead pressed permanent hold button 72 (FIG. 5), HVAC controller 22 may instead display a permanent hold status button 86 in place of hold status button 84. In some cases, HVAC controller 20 may permit a user to set a temporary temperature schedule that lasts longer than 24 hours and thus HVAC controller 20 may instead display a hold status button 88 in place of hold status button 84 or permanent hold status button 86.

FIG. 8 is similar to FIG. 7, but includes third region 50 as originally discussed with respect to FIG. 4. FIG. 8 shows a home screen 90 that might be displayed by HVAC controller if a user has pressed or one or more of first up arrow 54, first down arrow 56, second up arrow 60 and/or second down arrow 62 to adjust a temperature set point.

FIG. 9 shows an illustrative home screen 91 that in some ways is similar to home screen 82 (FIG. 7), but accounts for HVAC controller 20 cooperating with a remote control. One such remote control is described in U.S. Provisional Patent Application No. 60/991,674 filed Nov. 30, 2007, entitled "REMOTE CONTROL UNIT FOR HVAC SYSTEM", which application is hereby incorporated by reference herein. In some cases, a remote control may be used to control one or more of a variety of different functions of HVAC controller 20. In some instances, for example, HVAC controller 20 may be configured to either sense ambient temperature at HVAC controller 20 using an internal thermal sensor and/or to use a temperature reading from a thermal sensor that may be present within the remote control.

Home screen 91 as illustrated shows that HVAC controller 20 is using a temperature reading from the remote control, as indicated by the text "Sensing from remote" displayed within first region 36 of display 22. An individual may instead wish to instruct HVAC controller 20 to use the internal thermal sensor (or a remote sensor located near HVAC controller 20

6

and communicating wirelessly therewith). A Sense from Here button 93 provides the individual with the opportunity to instruct HVAC controller 20 to use its internal thermal sensor. In some cases, if HVAC controller 20 is using its own thermal sensor, home screen 91 may include a "Sense from Remote" button (not illustrated) and/or the remote control may include a button that permits the homeowner to instead sense the temperature from the remote. A Vacation button 95, as will be discussed further with respect to subsequent Figures, permits a homeowner to view and/or modify temporary vacation-related scheduling.

In some instances, HVAC controller 20 may display a first image within first region 36 of display 22 and a second image within second region 38. The first image may include a first set of information while the second image may include a second set of information. A third image that may include information pertaining to one or more HVAC system status conditions may temporarily replace the second image otherwise displayed within second region 38. In some instances, the first image, the second image and the third image may all be displayed on a home screen. In some cases, displaying the third image in place of the second image may not impact the display of the first image.

In some cases, the first set of information displayed within first region 36 may include current indoor temperature, a temperature set point, an indoor humidity reading and schedule information. The second information displayed within second region 38 may, for example, include one or more of date, a time, an equipment status and an outdoor weather parameter. HVAC controller 20 may, for example, replace the second image with the first image when HVAC controller 30 detects the occurrence of one or more system status events or conditions.

In some instances, HVAC controller 20 may provide messages such as informational messages, equipment status messages, and the like upon at least part of display 22, particularly if home button 28 has been pressed or otherwise chosen or is automatically displayed after, for example, no user interaction is sensed for a period of time (e.g. thirty seconds). FIG. 10 provides an illustrative home screen 92 that includes an information button 94. As illustrated, information button 94 may be displayed within second region 38 and as such does not interfere or otherwise eliminate any information displayed within first region 36.

Home screen 92 includes third region 40 as discussed with respect to FIGS. 3, 5 and 7.

FIG. 11 provides a home screen 96 that includes information button 94 displayed within second region 38, but includes third region 50 as discussed previously with respect to FIGS. 4, 6 and 8. In either case, pressing information button 94 may cause HVAC controller 20 to display further information pertaining to the shorter message displayed within information button 94.

Information button 94 may provide a variety of equipment status messages. An example includes "Your air filter needs to be replaced." Other examples may pertain to humidifier pad replacement, UV light replacement, and other furnace and/or A/C service schedules as appropriate, depending on installed equipment options. FIGS. 10 and 11 show information button 94 displaying the aforementioned message regarding air filter replacement. In some cases, pressing information button 94 (either in FIG. 10 or FIG. 11) will cause HVAC controller 20 to display a screen 100, as shown in FIG. 12.

In FIG. 12, screen 100 includes further information pertaining to the equipment status message included on information button 94. Screen 100 includes text 102 that provides the homeowner with information regarding what needs to be

done and/or how to do it. As illustrated, text **102** says “Your system’s (equipment name) (e.g. air filter) needs to be replaced. When you have replaced it, please press Reset.” HVAC controller **20** may fill in the appropriate equipment name, and sometimes provide the appropriate model number and/or appropriate information. The appropriate equipment name, model number and/or other information may reference a current value of a variable that is embedded within the information message, if desired.

Screen **100** includes a Reset button **104**, which may be pressed once the appropriate equipment has in fact been replaced. In some cases, home screen **100** may include a Reminder button **106** that provides the homeowner with a period of time sufficient to address the particular issue. For example, Reminder button **106** may temporarily satisfy HVAC controller **20** for a period of time long enough for the homeowner to go to the store and buy the appropriate replacement item such as a new air filter, a new humidifier pad, or the like.

In some cases, home screen **100** may also include a Dealer button **108**. When HVAC controller **20** is initially installed, the installer may, if desired and as will be discussed with respect to subsequent Figures, enter information identifying the HVAC contractor. By pressing Dealer button **108**, the homeowner may, for example, be provided with a telephone number or email address for the HVAC contractor and thus the homeowner may simply call the HVAC contractor either to order the appropriate replacement item and/or to request that the contractor resolve the issue by obtaining and installing the appropriate replacement item.

In some cases, a “Service Request” button may be provided that sends a message to the identified contractor and requests the contractor to address the issue. HVAC controller **20** may contact the contractor by email message, text message, or the like. The message may, for example, include appropriate part numbers or other diagnostic information so that the contractor can bring the appropriate parts and/or equipment. Of course, HVAC controller **20** would have to be provided with telephone or other Internet access in order to provide this functionality.

In some cases, HVAC controller **20** may have more than one message to display. In these instances, information button **94** may instead display a message such as “There are multiple messages.” or something to that effect. In some cases, screen **100** may include a scroll bar **110** or the like that provides information pertaining to how many messages are waiting as well as providing scroll buttons **112** and **114** so that the homeowner or HVAC contractor may scroll through the messages. If there is only one message to display, scroll bar **110** may not be displayed.

In some instances, and as illustrated with respect to subsequent Figures, HVAC controller **20** may display a help button that, if pressed, may cause HVAC controller **20** to display one or more context sensitive help screens that may provide the user with information that is pertinent to one or more displayed operating parameters. In some cases, the help screen may temporarily replace whatever information was being displayed. The help screens, if displayed, may include information pertaining to, for example, operating parameters such as circulating fan operation, system operation, scheduling, humidification and/or dehumidification settings, ventilation settings, maintenance reminders, equipment settings, and the like. In some cases, the help screen may include current values of one or more variables embedded within the help screen message, if desired. The information that is displayed

may be context sensitive or dependent upon the operating and/or programming steps that are currently being undertaken by the user.

FIG. **13** provides an illustrative home screen **116** that may be displayed if Fan button **30** is pressed. In some cases, a Help button **118** may be displayed within second region **38**. By pressing Help button **118**, a homeowner or other individual may obtain additional information regarding the choices they are being asked to make. First region **36** may include one or more fan buttons that can be pressed to instruct HVAC controller **20** how to operate the fan present within the HVAC equipment. The fan buttons may include, for example, one or more of a Run Continuously button **120**, an Automatic button **122**, an Intermittent button **124** and/or a Run Fan with Schedule button **126**. As there may be more fan buttons than can be displayed at one time within first region **36**, third region **40** may include an up scroll button **128** and a down scroll button **130** in order to scroll through the available fan buttons.

FIG. **14** provides an illustrative help screen **132** that may be provided by HVAC controller **20** if a homeowner or other individual presses Help button **118** within home screen **116** (FIG. **13**). Second region **38** may include a Back button **133** that permits an individual to return to the previous screen (e.g. FIG. **13**) once they have read and understood the information provided within help screen **132**. First region **36** includes textual information providing the individual with information pertaining to the fan choices presented within home screen **116**. Third region **40** includes up scroll button **128** and down scroll button **130** in order to scroll up and down through the text provided within first region **36**, if necessary.

FIG. **15** provides an illustrative home screen **134** that may be displayed if Heat/Cool button **32** is pressed. In some cases, a Help button **136** may be displayed within second region **38**. By pressing Help button **136**, a homeowner or other individual may obtain additional information regarding the choices they are being asked to make. First region **36** may include one or more selection buttons that can be pressed to instruct HVAC controller **20** how to operate the HVAC equipment. The selection buttons may include, for example, one or more of a Heating button **138**, a Cooling button **140**, an Automatic button **142**, an Off button **144** and/or an Emergency Heat button **146**. As there may be more selection buttons than can be displayed at one time within second region **38**, third region **40** may include an up scroll button **128** and a down scroll button **130** in order to scroll through the available selection buttons.

FIG. **16** provides an illustrative help screen **148** that may be provided by HVAC controller **20** if a homeowner or other individual presses Help button **136** within home screen **134** (FIG. **15**). Second region **38** may include a Back button **133** that permits an individual to return to the previous screen (e.g. FIG. **15**) once they have read and understood the information provided within help screen **132**. First region **36** includes textual information providing the individual with information pertaining to the selection choices presented within home screen **116**. Third region **40** includes up scroll button **128** and down scroll button **130** in order to scroll up and down through the displayed text.

FIG. **17** provides an illustrative home screen **150** that may be displayed if Menu button **34** is pressed. HVAC controller **20** may display a variety of menu items within first region **36** and/or within second region **38**. Third region **40** may include up scroll button **128** and down scroll button **130** to scroll up and down the displayed menu items, if necessary. These menu items may permit a homeowner or other individual to set a variety of parameters of HVAC controller **20**.

In some cases, home screen **150** may include, for example, one or more of a Create/Edit Schedule button **152**, a Vacation Mode button **154**, an Humidification button **156**, a Dehumidification button **158**, a Ventilation button **160**, a System Information button **162**, a Date/Time button **164**, a Preferences button **166**, a Temporary Schedule Changes button **168**, a Schedule Fan button **170**, a Southern Dehumidification Mode button **172**, a Find Remote button **174**, a Clean Screen button **176**, a Security Settings button **178** and/or an Installer Set Up button **180**. Subsequent Figures will provide illustrative screens that may be displayed by HVAC controller **20** in response to a homeowner or other individual selecting one or more of these menu items.

FIGS. **18** through **46** provide illustrative but non-limiting examples of screens that may be displayed by HVAC controller **20** pertaining to creating, editing and/or viewing a schedule within HVAC controller **20**. In particular, FIG. **18** provides an illustrative screen **182** that may be displayed by HVAC controller **20** in response to someone pressing or otherwise selecting Create/Edit Schedule button **152** (FIG. **16**). In some instances, screen **182** provides a user with one or more options as to how they wish to create, edit and/or view a schedule. Screen **182** may include one or more of a View/Edit Current Schedule button **184**, a Guide Me Through The Scheduling button **186** and/or an I'll Do It Myself button **188**. The functionality of each will be described, in turn. Screen **182** may include a Back button **190** that permits a user to return to a previous screen and/or a Help button **192** that may provide the user with pertinent assistance.

In some cases, pressing View/Edit Current Schedule button **184** may cause HVAC controller **20** to display a screen **194**, as shown in FIG. **19**. Screen **194** may display time and/or temperature set point information for one or more time periods of one or more days. As illustrated, screen **194** provides heating and cooling temperature set points for the Wake period, the Leave period, the Return period and the Sleep period for weekdays Monday through Friday. In some cases, screen **194** may be considered as including a Wake button **196**, a Leave button **198**, a Return button **200** and a Sleep button **202**. As will be discussed, the heating and/or cooling temperature set points for a particular time period, as well as the starting and/or ending times for a particular time period, may be changed by pressing the appropriate button such as Wake button **196**, Leave button **198**, Return button **200** and/or Sleep button **202**.

In some cases, screen **194** may include a View Individual Day button **204** that permits an individual to view only one day at a time, rather than a group of days. If View Individual Day button **204** is pressed, HVAC controller **20** may display heating and cooling temperature set points for one or more time periods for a single day, and may also display a button (not illustrated) that permits the user to scroll ahead to the next day.

In some instances, as illustrated, screen **194** may include a Next Group of Days button **206**. If, for example, the displayed group of days is Monday-Friday, pressing Next Group of Days button **206** may cause HVAC controller **20** to display heating and cooling temperature set points for one or more periods of time for Saturday and/or Sunday. A Done button **208** permits a user to tell HVAC controller **20** that they are done viewing and/or editing the schedule, and HVAC controller **20** may return to a previous screen, if desired. Screen **194** may be considered a schedule review screen because the displayed schedule cannot be changed without touching one of buttons **196-202**. Once one of buttons **196-202** are touched, HVAC controller **20** may be considered to be in an edit mode.

This may, for example, help the user to know whether changes are being made to the schedule.

FIG. **20** provides an illustrative screen **210** that may be displayed by HVAC controller **20** if, with reference to screen **194** (FIG. **19**), one were to press Wake button **196**. Screen **210** may permit a user to change one or more of a start time for the Wake time period, the cooling temperature set point and/or the heating temperature set point for Wake time period. Screen **210** includes a Cancel This Period button **212** that, if pressed, permits the user to return to the previous screen and select a different time period, if desired.

Screen **210** includes a time setting block **214** that may include up and down buttons or other indicia that permit a user to alter the start time displayed within time setting block **214**. Screen **210** may include a cooling temperature set point block **216** and/or a heating temperature set point block **218**. Each of cooling temperature set point block **216** and heating temperature set point block **218** may include up and down button or other indicia that permit a user to alter the cooling temperature set point and/or the heating temperature set point.

In some instances, screen **210** may include a Help button **220** that may, if pressed, cause HVAC controller **20** to display appropriate information pertaining to instructions, available options, and the like. A Cancel button **222** may permit a user to cancel out of whatever changes they have entered, if any, without saving any changes. A Done button **224** may be pressed to inform HVAC controller **20** that the changes, if any, have been entered and should be saved. In some cases, when Done button **224** is pressed, a message such as "Saving Changes" may be displayed, notifying the user that the changes are being saved.

Returning briefly to FIG. **18**, another option for creating, editing and/or viewing a schedule is to press I'll Do It Myself button **188**. Pressing this button may cause HVAC controller **20** to display an illustrative screen **226**, shown in FIG. **21**. Screen **226** includes a Monday button **228**, a Tuesday button **230**, a Wednesday button **232**, a Thursday button **234**, a Friday button **236**, a Saturday button **238** and a Sunday button **240**. One way to select which day or days to view/edit is to press the button or buttons corresponding to the desired days. As illustrated, it can be seen that Monday button **228**, Tuesday button **230**, Wednesday button **232**, Thursday button **234** and Friday button **236** have been pressed.

It will be appreciated that in some instances, there may be a desire to be able to quickly make multiple selections. HVAC controller **20** may, for example, display a first menu that includes one or more quick select touch buttons that may be used to quickly select two or more of a plurality of displayed selection options. In some cases, each of the selection options may have an associated algorithm parameter, and HVAC controller **20** may be configured to permit the user to simultaneously change the associated algorithm parameters for each of the two or more of the plurality of selection options that are selected by pressing one of the one or more quick select touch buttons. In some instances, HVAC controller **20** may display a second menu that permits the user to simultaneously change the associated algorithm parameters for each of the two or more of the plurality of selection options that are selected by pressing one of the one or more quick select touch buttons.

In an illustrative example, HVAC controller **20** may display a first menu that includes a schedule menu, and in this situation each of the plurality of selection options of the schedule menu may correspond to a corresponding day of a week. In some cases, one of the quick select touch buttons may be a WEEKDAY button that, when pressed, selects Monday, Tuesday, Wednesday, Thursday and Friday for scheduling. Another example is a WEEKEND button that, when pressed,

11

selects Saturday and Sunday for scheduling. Another example is an ALL button that, when pressed, selects all days of the week for scheduling.

In some instances, HVAC controller 20 may display a schedule menu, and each of the plurality of selection options of the schedule menu may correspond to a PERIOD of a day of a week. In another example, one of the quick select touch buttons comprises a wake button that, when pressed, selects the wake period for all or selected days of the week. In another example, one of the quick select touch buttons comprises a leave button that, when pressed, selects the leave period for all or selected days of the week. In another example, one of the quick select touch buttons comprises a return button that, when pressed, selects the return period for all or selected days of the week. In another example, one of the quick select touch buttons comprises a sleep button that, when pressed, selects the sleep period for all or selected days of the week.

Returning to the Figures, in some instances, several days may easily be selected using a quick select button such as a Weekdays button 242, a Weekends button 244 and/or an All button 246. Pressing Weekdays button 242 will cause all five week day buttons to be selected. As noted, Monday through Friday are indicated as having been selected. This may be achieved either by pressing each of the five day buttons or by simply pressing Weekdays button 242. Pressing Weekends button 244 may cause Saturday button 238 and Sunday button 240 to be indicated as having been selected. Pressing All button 246 will cause all seven day buttons to be indicated as having been selected. Selected buttons may be indicated, for example, by graphically making each selected button to appear that it has been depressed. In some instances, selected buttons may be indicated in other ways, such as using bolded text, different colors and the like.

In some cases, HVAC controller 20 may include text that helps the user to understand what is expected of them. For example, screen 226 can be seen to include the text "Select the days of the week to schedule". Messages such as this may help the user navigate through the screens that may be displayed by HVAC controller 20. Screen 226 may include a Cancel button 248 and a Next button 250. Cancel button 248 may be pressed to cancel any changes that have been entered and cause HVAC controller 20 to revert to a previous screen. Next button 250 may be pressed, for example, to move to the next screen.

In some cases, pressing Next button 250 (FIG. 21) causes HVAC controller 20 to display an illustrative screen 252, as shown in FIG. 22. Once the day or days have been selected (as discussed with respect to FIG. 21), the user is given the opportunity to select a time period to edit. Screen 252 includes a Wake button 254, a Leave button 256, a Return button 258 and a Sleep button 260. A Back button 262 permits a user to return to a previous screen such as screen 226 (FIG. 21) to, for example, alter the day or days selected. Again, HVAC controller 20 may display text such as "Please press a time period below to schedule" to assist the user in navigation.

Screen 252 permits the user to edit one or more of the distinct time periods. For example, pressing Wake button 254 may cause HVAC controller 20 to display an illustrative screen 264, as shown in FIG. 23. Screen 264 may permit a user to change one or more of a start time for the Wake time period, the cooling temperature set point and/or the heating temperature set point for Wake time period. Screen 264 includes a Cancel This Period button 266 that, if pressed, permits the user to return to the previous screen and select a

12

different time period, if desired. It can be seen that screen 264 may include helpful text such as "Set your wake time and temperature".

Screen 264 includes a time setting block 268 that may include up and down buttons or other indicia that permit a user to alter the start time displayed within time setting block 268. Screen 264 may include a cooling temperature set point block 270 and/or a heating temperature set point block 272. Each of cooling temperature set point block 270 and heating temperature set point block 272 may include up and down button or other indicia that permit a user to alter the cooling temperature set point and/or the heating temperature set point.

In some instances, screen 264 may include a Help button 274 that may, if pressed, cause HVAC controller 20 to display appropriate information pertaining to instructions, available options, and the like. A Cancel button 276 may permit a user to cancel out of whatever changes they have entered, if any, without saving any changes and/or return to a previous screen. A Next button 278 may be pressed to indicate to HVAC controller 20 that the displayed time period has been edited as desired. If Next button 278 is pressed, HVAC controller 20 may display an illustrative screen 280, as shown in FIG. 24.

Screen 280 is similar to screen 252 (FIG. 23), but includes the changes made to the Wake period made in FIG. 23, and permits a user to select another time period to edit, if desired. However, screen 280 also includes a Done button 282. If the user wishes to edit another time period, they may, one at a time, press one or more of Wake button 254, Leave button 256, Return button 258 and/or Sleep button 260, and may edit the selected time period(s) as discussed with respect to FIG. 23. However, once the user has finished editing the time periods they wish to edit, they may inform HVAC controller 20 that they have finished by pressing Done button 282.

Once the user has pressed Done button 282, HVAC controller 20 may display an illustrative screen 284, which is shown in FIG. 25. In screen 284, HVAC controller 20 may display a message informing the user that HVAC controller 20 is saving the changes that the user has made. HVAC controller may then display an illustrative screen 286 as shown in FIG. 26.

In FIG. 26, screen 286 may include text asking the user if they wish to schedule other days. A Yes button 288 and a No button 290 permits the user to provide their answer. If the user presses No button 290, HVAC controller 20 may revert to screen 182 as seen in FIG. 18. If the user presses Yes button 288, HVAC controller 20 may revert to screen 226 as seen in FIG. 21. In some cases, the days already modified may be indicated by displaying "modified" within the individual day buttons, but this is not required.

Returning briefly to FIG. 18, another option for creating, editing and/or viewing a schedule is to press Guide Me Through Scheduling button 186. Pressing this button may cause HVAC controller 20 to display an illustrative screen 292, shown in FIG. 27. Screen 292 may be considered as an informational screen, as screen 292 provides a text message that informs the user that they will be asked a series of questions regarding their preferred comfort settings. A Back button 294 permits a user to return to a previous screen, if desired, while a Next button 296 permits a user to advance to the next screen.

In some instances, once the user has pressed Next button 296, HVAC controller 20 will provide an illustrative screen 298, as shown in FIG. 28. Screen 298 permits the user to select one or more days that will have the same schedule. Screen 298 may include a text message to this effect. In some cases, for example, a user may decide to have the same sched-

13

ule for Monday through Friday and a different schedule for Saturday and Sunday. Screen 298 includes a Monday button 300, a Tuesday button 302, a Wednesday button 304, a Thursday button 306, a Friday button 308, a Saturday button 310 and a Sunday button 312.

Screen 298 may include a Back button 314 that permits a user to return to a previous screen such as screen 292 (FIG. 27), if desired, while a Cancel button 316 provides the user with an opportunity to revert to a previous screen or exit scheduling entirely. A Next button 318 permits the user to advance to a subsequent screen. In some cases, pressing Next button 318 may cause HVAC controller 20 to display an illustrative screen 320, as seen in FIG. 29.

Screen 320 may be the result of having selected Monday, Tuesday, Wednesday, Thursday and Friday via screen 298 (FIG. 28), as screen 320 includes a text message 322 that reminds the user which day or days have been selected. As shown, text message 322 simply says "Monday-Friday". In some cases, it is considered that text message 322 may list each individual day by full name, by abbreviated name, and the like.

Screen 320 may include an interview question 324, asking if someone is home during the day on the day or days being scheduled. The user may give an answer using either a Yes button 326 or a Not button 328. If someone is home during the day, in some cases HVAC controller 20 may operate in accordance with a Wake time period and a Sleep time period, with the Leave and Return periods rolled into the Wake period or otherwise inactivated, for example. However, if no one is home during the day, HVAC controller 20 will in subsequent screens request scheduling and temperature information for all of the time periods.

For this example, assume the user pressed No button 328. Screen 334 may include an interview question 336, asking what time the first person wakes up. HVAC controller 20 may, in some cases, use this time as the starting point for the Wake time period. Screen 334 includes a time setting block 338 that displays the time period as well as a time at which the first person wakes up. Time setting block 338 includes an Up arrow 340 and a Down arrow 342 that may be used to adjust the time as desired.

Pressing Next button 318 may cause HVAC controller 20 to display an illustrative screen 344, as seen in FIG. 31. Screen 344 may include an interview question 346, asking what time the last person leaves in the morning. HVAC controller 20 may, in some cases, use this time as the starting point for the Leave time period. Screen 344 includes a time setting block 348 that displays the time period as well as a time at which the last person leaves. Time setting block 348 includes an Up arrow 340 and a Down arrow 342 that may be used to adjust the time as desired.

Pressing Next button 318 may cause HVAC controller 20 to display an illustrative screen 350, as seen in FIG. 32. Screen 350 may include an interview question 352, asking what time the first person returns home. HVAC controller 20 may, in some cases, use this time as the starting point for the Return time period. Screen 350 includes a time setting block 354 that displays the time period as well as a time at which the last person leaves. Time setting block 354 includes an Up arrow 340 and a Down arrow 342 that may be used to adjust the time as desired.

Pressing Next button 318 may cause HVAC controller 20 to display an illustrative screen 356, as seen in FIG. 33. Screen 356 may include an interview question 358, asking what time the last person goes to sleep. HVAC controller 20 may, in some cases, use this time as the starting point for the Sleep time period. Screen 356 includes a time setting block 360 that

14

displays the time period as well as a time at which the last person goes to sleep. Time setting block 360 includes an Up arrow 340 and a Down arrow 342 that may be used to adjust the time as desired.

Pressing Next button 318 may cause HVAC controller 20 to display an illustrative screen 362, as seen in FIG. 34. Screen 362 may include an interview question 364, asking what heating temperature is preferred when the user wakes up in the morning. HVAC controller 20 may, in some cases, use this temperature as the heating temperature set point for the Wake period. Screen 362 includes a temperature setting block 366 that displays the time period, a heating temperature set point and an indication of which temperature set point is being set. Temperature setting block 366 includes an Up arrow 340 and a Down arrow 342 that may be used to adjust the temperature as desired.

Pressing Next button 318 may cause HVAC controller 20 to display an illustrative screen 368, as seen in FIG. 35. Screen 368 may include an interview question 370, asking what cooling temperature is preferred when the user wakes up in the morning. HVAC controller 20 may, in some cases, use this temperature as the cooling temperature set point for the Wake period. Screen 368 includes a temperature setting block 372 that displays the time period, a cooling temperature set point and an indication of which temperature set point is being set. Temperature setting block 372 includes an Up arrow 340 and a Down arrow 342 that may be used to adjust the temperature as desired.

Pressing Next button 318 may cause HVAC controller 20 to display an illustrative screen 374, as seen in FIG. 36. Screen 374 may include an interview question 376, asking what heating temperature is preferred when the user is away from the house. HVAC controller 20 may, in some cases, use this temperature as the heating temperature set point for the Leave period. Screen 374 includes a temperature setting block 378 that displays the time period, a heating temperature set point and an indication of which temperature set point is being set. Temperature setting block 378 includes an Up arrow 340 and a Down arrow 342 that may be used to adjust the temperature as desired. In some cases, screen 374 may include a message 380 providing a suggested heating temperature set point.

Pressing Next button 318 may cause HVAC controller 20 to display an illustrative screen 382, as seen in FIG. 37. Screen 382 may include an interview question 384, asking what cooling temperature is preferred when the user is away from the house. HVAC controller 20 may, in some cases, use this temperature as the cooling temperature set point for the Leave period. Screen 382 includes a temperature setting block 386 that displays the time period, a cooling temperature set point and an indication of which temperature set point is being set. Temperature setting block 386 includes an Up arrow 340 and a Down arrow 342 that may be used to adjust the temperature as desired. In some cases, screen 382 may include a message 388 providing a suggested cooling temperature set point.

Pressing Next button 318 may cause HVAC controller 20 to display an illustrative screen 390, as seen in FIG. 38. Screen 390 may include an interview question 392, asking what heating temperature is preferred when the user returns home. HVAC controller 20 may, in some cases, use this temperature as the heating temperature set point for the Return period. Screen 390 includes a temperature setting block 394 that displays the time period, a heating temperature set point and an indication of which temperature set point is being set. Temperature setting block 394 includes an Up arrow 340 and a Down arrow 342 that may be used to adjust the temperature as desired.

15

Pressing Next button 318 may cause HVAC controller 20 to display an illustrative screen 396, as seen in FIG. 39. Screen 396 may include an interview question 398, asking what cooling temperature is preferred when the user returns home. HVAC controller 20 may, in some cases, use this temperature as the cooling temperature set point for the Return period. Screen 396 includes a temperature setting block 400 that displays the time period, a cooling temperature set point and an indication of which temperature set point is being set. Temperature setting block 400 includes an Up arrow 340 and a Down arrow 342 that may be used to adjust the temperature as desired.

Pressing Next button 318 may cause HVAC controller 20 to display an illustrative screen 402, as seen in FIG. 40. Screen 402 may include an interview question 404, asking what heating temperature is preferred when the user is sleeping. HVAC controller 20 may, in some cases, use this temperature as the heating temperature set point for the Sleep period. Screen 402 includes a temperature setting block 406 that displays the time period, a heating temperature set point and an indication of which temperature set point is being set. Temperature setting block 406 includes an Up arrow 340 and a Down arrow 342 that may be used to adjust the temperature as desired.

Pressing Next button 318 may cause HVAC controller 20 to display an illustrative screen 408, as seen in FIG. 41. Screen 408 may include an interview question 410, asking what cooling temperature is preferred when the user is sleeping. HVAC controller 20 may, in some cases, use this temperature as the cooling temperature set point for the Sleep period. Screen 408 includes a temperature setting block 412 that displays the time period, a cooling temperature set point and an indication of which temperature set point is being set. Temperature setting block 412 includes an Up arrow 340 and a Down arrow 342 that may be used to adjust the temperature as desired.

Pressing Next button 318 may cause HVAC controller 20 to display an illustrative screen 414, as seen in FIG. 42. Screen 414 may include a question 416, asking the user if they wish to schedule other days. A Yes button 418 and a No button 420 permit the user to provide an appropriate answer. If the user presses Yes button 418, HVAC controller 20 may revert to screen 298 (FIG. 28) so that the user may select additional days to schedule. In some cases, although this is not required, the day buttons representing the days that have already been scheduled may be labeled as "modified".

Returning briefly to FIG. 42, if the user presses No button 420, HVAC controller 20 may display an illustrative screen 422, as seen in FIG. 43. Screen 422 may include a question 424, inquiring as to whether or not the user wishes to review their schedule. A Yes button 426 and a No button 428 permit the user to provide an appropriate answer. If the user presses No button 428, HVAC controller 20 may revert to screen 182 (FIG. 18). If the user presses Yes button 426, HVAC controller 20 may display an illustrative screen 430, as shown in FIG. 44.

Screen 430 may include a message 432 instructing the user that they may, if desired, further edit their schedule by pressing one of the time periods. Screen 430 may include a Wake button 434, a Leave button 436, a Return button 438 and a Sleep button 440. Screen 430 may include a View Individual Days button 442 that may, if pressed, instruct HVAC controller 20 to display only a single day at a time. Screen 430 may then include a Next Day button (not illustrated). A Next Group of Days button 444 may, if pressed, instruct HVAC controller 20 to display another group of days. For example,

16

HVAC controller 20 may display Saturday and Sunday. A Done button 446 may, if pressed, inform HVAC controller 20 that the user is finished.

Each of Wake button 434, Leave button 436, Return button 438 and Sleep button 440 may include or otherwise display one or more of period starting time, period heating temperature set point and/or period cooling temperature set point. If the user wishes to edit one of the time periods, they may do so by pressing the desired time period button. For example, pressing Wake button 434 may cause HVAC controller 20 to display an illustrative screen 448, as shown in FIG. 45.

Screen 448 may include one or more of a time block 450, a cooling temperature block 452 and/or a heating temperature block 454. Time block 450 may display a starting time for the Wake period, and may include Up arrow 340 and Down arrow 342 so that the user may adjust the starting time, if desired. Cooling temperature block 452 may display a cooling temperature for the Wake period, and may include Up arrow 340 and Down arrow 342 so that the user may adjust the cooling temperature, if desired. Heating temperature block 454 may display a heating temperature for the Wake period, and may include Up arrow 340 and Down arrow 342 so that the user may adjust the heating temperature, if desired. It will be appreciated that HVAC controller 20 may display a similar screen in response to the user pressing (with respect to FIG. 44), any of Wake button 434, Leave button 436, Return button 438 and Sleep button 440.

In some instances, screen 448 may include text 456 informing the user that they have the opportunity to set the wake time and temperatures (or whichever time period is being displayed as a result of having pressed a particular time period button with respect to screen 430, shown in FIG. 44). The user may have the opportunity to simply delete the displayed time period by pressing a Delete Period button 458. A Help button 460 may be pressed to obtain additional information, selection options, and the like.

FIG. 46 provides an illustrative screen 462 that may be provided by HVAC controller 20 if, with respect to previous Figures, the user presses Cancel button 316 during some of the scheduling screens. Screen 462 includes text 464 that informs the user that their changes will not be saved if they cancel. An inquiry 466 asks the user to confirm if they wish to cancel, knowing that their changes will not be saved. A Yes button 468 and a No button 470 permit a user to enter their preference.

FIGS. 47 through 53 provide illustrative but non-limiting examples of screens that may be displayed by HVAC controller 20 pertaining to creating, editing and/or viewing a vacation schedule within HVAC controller 20. In particular, FIG. 47 provides an illustrative screen 472 that may be displayed by HVAC controller 20 in response to someone pressing or otherwise selecting Vacation Mode button 154 (FIG. 17).

Screen 472 may include text 474 that instructs the user to enter the date that they will be leaving on vacation. A Month block 476 displays a month, and Up arrow 340 and/or Down arrow 342 may be used to scroll up and/or down to the desired month. A Date block 478 displays a day of the month that can be adjusted up or down using Up arrow 340 and/or Down arrow 342 as desired. As illustrated, the date is displayed using numbers 1 through 31. In some cases, the corresponding day of the week (Monday, Tuesday, Wednesday, Thursday, Friday, Saturday and Sunday) may also be displayed, but this is not required. Cancel button 316 may, if pressed, cause HVAC controller 20 to revert to screen 150 (FIG. 17).

Pressing Next button 318 may cause HVAC controller 20 to display an illustrative screen 480, as shown in FIG. 48. Screen 40 may include text 482 that instructs the user to set the time

17

that they will be leaving on vacation. In some cases, as illustrated, text **482** may reference the date previously set with respect to screen **472** (FIG. 47) but this is not required. A time block **484** displays a departure time that can be adjusted using Up arrow **340** and/or Down arrow **342**, as appropriate. Back button **314** permits the user to return to the previous screen, if, for example the date was set incorrectly.

Pressing Next button **318** may cause HVAC controller **20** to display an illustrative screen **486**, shown in FIG. 49. In some cases, screen **486** may include text **488** instructing the user to enter a temperature that they want to maintain while they are on vacation. In some instances, as illustrated, screen **486** may include a cooling temperature block **490** displaying a cooling temperature set point and a heating temperature block **492** displaying a heating temperature set point. Cooling temperature block **490** and/or heating temperature block **492** may each independently include UP arrow **340** and Down arrow **342** for adjusting temperature settings as desired. In some cases, screen **486** may instead include only a single temperature block (not illustrated), particularly if the user does not take advantages of the programmability of HVAC controller **20** and instead simply uses HVAC controller **20** to hold a particular constant temperature, or if only a heating system or only a cooling system is included as part of the HVAC system. Back button **314** permits the user to return to the previous screen, if desired.

Pressing Next button **318** may cause HVAC controller **20** to display an illustrative screen **494**, as shown in FIG. 50. Screen **494** may include text **496** that instructs the user to enter the date that they will be returning from vacation. A Month block **498** displays a month, and Up arrow **340** and/or Down arrow **342** may be used to scroll up and/or down to the desired month. A Date block **500** displays a day of the month that can be adjusted up or down using Up arrow **340** and/or Down arrow **342** as desired.

Pressing Next button **318** may cause HVAC controller **20** to display an illustrative screen **502**, as shown in FIG. 51. Screen **502** may include text **504** that instructs the user to set the time that they will be returning from vacation. In some cases, as illustrated, text **504** may reference the date previously set with respect to screen **486** (FIG. 49) but this is not required. A time block **506** displays a return time that can be adjusted using Up arrow **340** and/or Down arrow **342**, as appropriate. Back button **314** permits the user to return to the previous screen, if, for example the date was set incorrectly.

Pressing Next button **318** may cause HVAC controller **20** to display an illustrative screen **508**, shown in FIG. 52. In some cases, screen **508** may include text **510** instructing the user to enter a temperature that they want when they return from vacation. In some instances, as illustrated, screen **508** may include a cooling temperature block **512** displaying a cooling temperature set point and a heating temperature block **513** displaying a heating temperature set point. Cooling temperature block **512** and/or heating temperature block **513** may each independently include UP arrow **340** and Down arrow **342** for adjusting temperature settings as desired. In some cases, screen **508** may instead include only a single temperature block (not illustrated), particularly if the user does not take advantages of the programmability of HVAC controller **20** and instead simply uses HVAC controller **20** to hold a particular constant temperature, or if only a heating system or only a cooling system are included as part of the HVAC system. Back button **314** permits the user to return to the previous screen, if desired.

Pressing Next button **318** may cause HVAC controller **20** to display an illustrative screen **514**, as shown in FIG. 53. Screen **514** may include text **516** that asks the user to confirm their

18

vacation settings. If there is an error, or the user wishes to make any changes, they may do so by pressing Back button **314** and HVAC controller **20** will provide the appropriate screens to make any necessary changes. If the user agrees with the vacation settings, they may inform HVAC controller **20** thereof by pressing Yes button **520**.

FIGS. 54 through 60 provide illustrative but non-limiting examples of screens that may be displayed by HVAC controller **20** pertaining to changing and/or viewing humidification and dehumidification settings within HVAC controller **20**. In particular, FIGS. 54-57 provide illustrative screens that may be displayed by HVAC controller **20** in response to someone pressing or otherwise selecting Humidification button **156** (FIG. 17), FIGS. 58-59 provide illustrative screen that may be displayed by HVAC controller **20** in response to someone pressing or otherwise selecting Dehumidification button **158** (FIG. 17) and FIG. 60 provides an illustrative screen that may be displayed by HVAC controller **20** in response to someone pressing or otherwise selecting Southern Dehumidification Mode button **172** (FIG. 17).

FIG. 54 provides an illustrative screen **522** that may include text **524** instructing the user to select or set their humidification setting. HVAC controller **20** may, for example, use the humidification setting in controlling a humidifier such as a whole-house humidifier. HVAC controller **20** may, for example, display a parameter adjustment element for use in adjusting an operating parameter such as humidification, the parameter adjustment element may include an indicator that provides a qualitative indication for at least the current setting of the operating parameter.

To illustrate, screen **522** includes a slider bar **526** that has a scale **528**, a display **530**, a Left arrow **532** and a Right arrow **534**. Scale **528** can be seen as including text describing the humidification setting in relative or qualitative terms such as "Dry", "Comfort Zone" and "Wet". These particular terms are merely representative, as other terms may also be used. More generally, scale **528** may provide a qualitative context to a particular humidity value (e.g. 42%) so that a user unfamiliar with humidity values can still choose an appropriate humidity setting.

Display **530** may, as illustrated, provide a reminder that it is the indoor humidity setting that is being displayed as well as a current indoor humidity setting or current indoor humidity reading. FIG. 55 provides an illustrative screen **536** having a display **538** that provides a display of the current indoor humidity setting or reading as well as an indication that frost protection has been activated, as will be discussed with respect to subsequent Figures.

Returning to FIG. 54, slider bar **526** may be seen as including an indicator button **540** that may be moved left and/or right using left arrow **532** and/or right arrow **534**, as desired. Indicator button **540** may, with respect to scale **528**, provide a visual indication of the relative or qualitative humidity setting and may, if desired, include a pointer that interacts with scale **528**. Scale **528** may provide upper and/or lower numerical limits for the displayed parameter. In some instances, indicator button **540** may include a numerical representation of the indoor humidity setting.

In some cases, indicator button **540** may move a prescribed distance either left or right in response to the user pressing either left arrow **532** or right arrow **534**. In some cases, the distance that indicator button **540** moves may be at least partially a function of how many times left arrow **532** and/or right arrow **534** are pressed. In some instances, the distance that indicator button **540** moves may be at least partially a function of how long left arrow **532** and/or right arrow **534** are held down by the user. In some cases, indicator button **540**

may be a touch-sensitive button, and may be moved left or right simply by the user touching indicator button 540 and dragging their finger left or right.

Screen 522 may include a Disable Humidification button 542. In some cases, a user may not wish to provide HVAC controller 20 with humidification settings. For example, in warm climates, the user may not want or need to operate a humidifier such as a whole-house humidifier that is controlled by HVAC controller 20. In some cases, a user's HVAC equipment may not include any humidification equipment. In situations such as these, the user may deactivate this functionality by pressing Disable Humidification button 542. FIG. 56 provides an illustrative screen 552 that is similar to screen 522 (FIG. 54), but shows that HVAC controller 20 has grayed out slider bar 526 as a result of the user having pressed Disable Humidification button 542. It can be seen that text 524 also states that humidification has been disabled. In some cases, screen 552 may include an Enable Humidification button 554.

Returning to FIG. 54, screen 522 may include a Window Frost Protection Setting button 544, as will be discussed with respect to FIGS. 57 and 58. A Help button 546 may, if pressed, provide further information explaining humidification, providing clarification regarding options, and the like. A Cancel button 548, if pressed, may cause HVAC controller 20 to revert to screen 150 (FIG. 17) without saving any changes that may have been made. A Done button 550, if pressed, informs HVAC controller 20 that the humidification setting has been completed, and as a result, may revert to screen 150 (FIG. 17).

Pressing Window Frost Protection Setting button 544 (FIG. 54) may cause HVAC controller 20 to display an illustrative screen 556, as shown in FIG. 57. In some ways, selecting an indoor humidification setting is similar to selecting a window frost protection setting, as the risk of window condensation, particularly in cold weather, is at least partially a function of the indoor air humidity. However, window condensation is also at least partially a function of the efficiency of the windows within the house or other building.

An old, inefficient window such as a single-pane window may present a relatively cold glass surface to the heated atmosphere within the building. Condensation is more likely in this situation. In contrast, a newer, more efficient window such as a double-pane window or even a triple-pane window will present a relatively warmer glass surface to the heated atmosphere within the building. Thus, an efficient window may tolerate a relatively higher indoor humidity without excessive window condensation. It will be recognized, of course, that outdoor temperature may also play a part. In some cases, HVAC controller 20 may be in communication with an exterior temperature sensor and may be programmed to adjust humidity settings and/or window frost protection settings accordingly.

Screen 556 may include text 558 that informs the user that they are to select a setting for window frost protection. Screen 556 includes a slider bar 560 that has a scale 562, a display 564, a left arrow 532 and a right arrow 534. Scale 562 may include text describing the window frost protection setting in relative or qualitative terms such as "Less Efficient" and "More Efficient". It will be recognized that this refers to the relative efficiency of the windows within the building. Display 564 may, as illustrated, provide a reminder that it is the window energy efficiency setting that is being displayed.

Slider bar 560 may be seen as including an indicator button 563 that may be moved left and/or right using left arrow 532 and/or right arrow 534, as desired. Indicator button 563 may, with respect to scale 562, provide a visual indication of the relative or qualitative humidity setting and may, if desired, include a pointer that interacts with scale 562. In some

instances, indicator button 563 may include a numerical representation of the window frost protection setting.

Indicator button 563 may be moved using either left arrow 532 or right arrow 534. In some cases, the distance that indicator button 563 moves may be at least partially a function of how many times or for how long left arrow 532 and/or right arrow 534 are pressed. In some cases, indicator button 563 may be a touch-sensitive button, and may be moved left or right simply by the user touching indicator button 563 and dragging their finger left or right. A Humidification Setting button 565 may be pressed if the user wishes to return to screen 522 (FIG. 54) to alter the humidification setting. Cancel button 548, if pressed, may cause HVAC controller 20 to revert to screen 150 (FIG. 17) without saving any changes that may have been made. Done button 550, if pressed, informs HVAC controller 20 that the window frost protection setting has been completed, and as a result, may revert to screen 150 (FIG. 17).

FIG. 58 shows an illustrative screen 566 that may include text 568 instructing the user to select or set their dehumidification setting. HVAC controller 20 may, for example, use the dehumidification setting to control operation of a dehumidifier or an air exchanger. Screen 566 includes a slider bar 570 that has a scale 572, a display 574, a Left arrow 532 and a Right arrow 534. Scale 572 can be seen as including text describing the dehumidification setting in relative or qualitative terms such as "Dry", "Comfort Zone" and "Wet". These particular terms are merely representative, as other terms may also be used. More generally, scale 572 may provide a qualitative context to a particular humidity value (e.g. 42%) so that a user unfamiliar with humidity values can still choose an appropriate dehumidification setting.

Display 574 may, as illustrated, provide the current indoor humidity setting or current indoor humidity reading. Slider bar 570 may be seen as including an indicator button 576 that may be moved left and/or right using left arrow 532 and/or right arrow 534, as desired. Indicator button 576 may, with respect to scale 572, provide a visual indication of the dehumidification setting and may, if desired, include a pointer that interacts with scale 574. In some instances, indicator button 576 may include a numerical representation of the indoor humidity setting.

Indicator button 576 may be moved using either left arrow 532 or right arrow 534. In some cases, the distance that indicator button 576 moves may be at least partially a function of how many times or for how long left arrow 532 and/or right arrow 534 are pressed. In some cases, indicator button 576 may be a touch-sensitive button, and may be moved left or right simply by the user touching indicator button 576 and dragging their finger left or right.

Screen 566 may, as illustrated, include a Disable Dehumidification button 578. Pressing Disable Dehumidification button 578 may cause HVAC controller 20 to display an illustrative screen 580 as shown in FIG. 59. It can be seen that in screen 580, slider bar 570 has been grayed out. Text 568 may also include a message reminding the user that dehumidification has been disabled. The user may wish to disable dehumidification if, for example, their HVAC equipment does not include a dehumidifier or an air exchanger. In some cases, screen 580 may include an Enable Dehumidification button 582.

Returning to FIG. 58, cancel button 548, if pressed, may cause HVAC controller 20 to revert to screen 150 (FIG. 17) without saving any changes that may have been made. Done button 550, if pressed, informs HVAC controller 20 that the dehumidification setting has been completed, and as a result, may revert to screen 150 (FIG. 17).

21

FIG. 60 shows an illustrative screen 584 that may, for example, be reached by pressing Southern Dehumidification Mode button 172 (FIG. 17). Screen 584 provides the user with settings information pertaining to a southern dehumidification mode. Help button 546 may provide educational or information messages pertaining to the southern dehumidification mode, and/or may discuss possible options. Cancel button 548, if pressed, may cause HVAC controller 20 to revert to screen 150 (FIG. 17).

FIGS. 61 through 66 provide illustrative but non-limiting examples of screens that may be displayed by HVAC controller 20 pertaining to changing and/or viewing ventilation settings within HVAC controller 20. HVAC controller 20 may use these settings, for example, to control operation of an air exchanger or the like. In particular, FIG. 61 provides an illustrative screen 586 that may be displayed by HVAC controller 20 in response to someone pressing or otherwise selecting Ventilation button 160 (FIG. 16).

Screen 586 may include a menu bar 588 that includes navigational information so that the user may better remember and/or understand where they are within the menu and how they got there. Screen 586 may include one or more of an Automatic button 590, an On button 592 and an Off button 594. If the user presses Automatic button 590, HVAC controller 20 may operate the air exchanger only when, for example, other HVAC equipment such as a forced air furnace or an air conditioner is operating, or perhaps operate the air exchanger in accordance with dehumidification settings. Pressing On button 592 may cause HVAC controller 20 to operate the air exchanger at all times while pressing corresponding Off button 594 may cause HVAC controller 20 to not operate the air exchanger at all.

In some cases, screen 586 may include a Temporary Override button 596. In some cases, a user may want the air exchanger to run constantly for a relatively short period of time. Examples of when this may occur, for example, include a desire to eliminate strong cooking odors or perhaps steam from a hot shower. If the user presses Temporary Override button 596, HVAC controller 20 may display an illustrative screen 598, as shown in FIG. 62.

Screen 598 includes a time block 600 that may be used to enter or edit a length of time for which the air exchanger will operate. Time block 600 may include a numerical display 602 representing a length of time in any appropriate units such as minutes. Up arrow 604 and down arrow 606 may be used, as desired, to increase or decrease the length of time for operating the air exchanger. A Cancel button 608 may, if pressed, cause HVAC controller 20 to revert to a previous screen such as screen 150 (FIG. 17). A Done button 610, if pressed, tells HVAC controller 20 that a desired length of time has been entered, and thus HVAC controller 20 operates the air exchanger continuously for the specified length of time. In some cases, pressing Done button 610 also causes HVAC controller 20 to revert to screen 150 (FIG. 17).

Returning to FIG. 61, it is noted that screen 586 includes Cancel button 608 and Done button 610, as discussed with respect to FIG. 62. In FIG. 61, Temporary Override button 596 was pressed to bring up screen 598 (FIG. 62), with screen 598 including time block 600. In some cases, as seen in illustrative screen 612 (FIG. 63), time block 600 may instead be displayed on the same screen as Automatic button 590, On button 592 and Off button 594, for example.

In some cases, a user may wish to set ventilation settings based at least partially on time, or perhaps on particular time periods such as one or more of the Wake, Leave, Return and/or Sleep periods. FIG. 64 provides an illustrative screen 614 that includes a Vent in All Periods button 616 and a Do

22

Not Vent While Sleeping button 618. If the user presses Vent in All Periods button 616, they may be provided an opportunity to set ventilation settings for one or more of the aforementioned time periods. If they press Do Not Vent While Sleeping button 618, they may be given the opportunity to set ventilation settings for one or more of the aforementioned time periods absent the Sleep period. In some cases, other options such as a Do Not Vent while Gone button. A Help button 620 may, if pressed, provide the user with more information pertaining to their options.

In the illustrative embodiment, pressing one of Vent in All Periods button 616 or Do Not Vent While Sleeping button 618 may cause HVAC controller 20 to display an illustrative screen 622, as shown in FIG. 65. Screen 622 may include text 624 instructing the user to set ventilator settings for each time period shown. Screen 622 may include one or more of a Wake button 626, a Leave button 628, a Return button 630 and a Sleep button 632, each of which may display a current ventilator setting. A Back button 634 permits the user, if desired, to return to a previous screen.

The user may alter the ventilator setting for a particular time period by pressing the corresponding time period button. For example, if the user presses Wake button 626, HVAC controller 20 may display an illustrative screen 636, as shown in FIG. 66. Text 624 may include a message instructing the user to set the ventilation setting for the Wake period. Screen 636 may include an Automatic button 638 and an Off button 640. In some cases, screen 636 may also include an On button (not illustrated). By pressing one of Automatic button 638 and Off button 640, the user may select their desired ventilation setting for the Wake period. The other time periods may be set in a similar manner.

FIGS. 67 through 69 provide illustrative but non-limiting examples of screens that may be displayed by HVAC controller 20 pertaining to viewing system information within HVAC controller 20. In particular, FIG. 67 provides an illustrative screen 642 that may be displayed by HVAC controller 20 in response to someone pressing or otherwise selecting System Information button 162 (FIG. 17) in order to obtain system information such as equipment status, dealer information and the like.

Screen 642 may include a navigational bar 644 that assists the user in navigating through the menus provided by HVAC controller 20. Screen 642 may include one or more of a View Equipment Status button 646 that may be used by the user to view a summary of their equipment status and a View Dealer Information button 648 that may be used by the user to obtain dealer information. The user may want to obtain dealer information, for example, if there is a problem with the HVAC equipment, or perhaps if routine maintenance, filter replacement, and the like is needed. A Previous Menu button 650 may permit the user to return to a previous screen.

Pressing View Equipment Status button 646 may cause HVAC controller 20 to display an illustrative screen 652, as shown in FIG. 68. Navigational bar 644 may, as illustrated, reflect the current relative position within the menu structure. Screen 652 provides information pertaining to one or more of heating status, cooling status, fan mode, humidifier status, dehumidifier status, air filter replacement status, UV lamp replacement status, equipment timers, wireless devices, and such. In some cases, there may be more information to display than fits within screen 652. In some instances, screen 652 may include an Up arrow 654 and a Down arrow 656 so that the user may scroll through the displayed information. A Done button 658 informs HVAC controller 20 that the user is finished, and may cause HVAC controller 20 to revert to a previous screen such as screen 642 (FIG. 67).

Pressing View Dealer Information button **648** may cause HVAC controller **20** to display an illustrative screen **660**, as shown in FIG. **69**. Navigational bar **644** may, as illustrated, reflect the current relative position within the menu structure. Screen **660** provides contact information such as name, address, telephone number and/or email address for an HVAC contractor that installed and/or services the system, for example. As noted above, the user may wish to contact the dealer if there is a problem or if, for example, they want to order replacement parts such as air filters, humidifier pads, UV lamps and the like.

In some cases, a "Service Request" button may be provided that sends a message to the identified contractor and requests the contractor to address the issue. HVAC controller **20** may contact the contractor by email message, text message, or the like. The message may, for example, include appropriate part numbers or other diagnostic information so that the contractor can bring the appropriate parts and/or equipment. Of course, HVAC controller **20** would have to be provided with telephone or other Internet access in order to provide this functionality.

FIGS. **70** through **72** provide illustrative but non-limiting examples of screens that may be displayed by HVAC controller **20** pertaining to viewing and/or changing date and time information within HVAC controller **20**. In particular, FIG. **70** provides an illustrative screen **662** that may be displayed by HVAC controller **20** in response to someone pressing or otherwise selecting Date/Time button **164** (FIG. **17**) in order to view and/or change date and time information.

Screen **662** may include a navigational bar **664** that informs the user of their current relative position within the menu structure. Screen **662** may include one or more of a Set Time button **666**, a Set Date button **668** and a Previous Menu button **670**. The user may press Set Time button **666** in order to view or change time settings, or may press Set Date button **668** to view or change date settings. Previous Menu button **670** may cause HVAC controller **20** to revert to a previous screen.

Pressing Set Time button **666** may cause HVAC controller **20** to display an illustrative screen **672**, as shown in FIG. **71**. Screen **672** may include one or more of a hour block **674**, a minute block **676** and an AM/PM block **678**. Hour block **674** may display a current hour time setting and may include an Up arrow **680** and a Down arrow **682** that may be used to increase or decrease the current hour time setting, as desired. Minute block **676** may display a current minute time setting that can be increased or decreased using Up arrow **680** and/or Down arrow **682**, as appropriate. AM/PM block **678** may display an indication of whether the current time is AM or PM. Up arrow **680** and/or Down arrow **682** may be used to adjust whether the current time is before noon or after noon. A Cancel button **684**, if pressed, may cause HVAC controller **20** to revert to a previous screen without saving any changes. A Done button **686** may cause HVAC controller **20** to save any time changes made, and to subsequently revert to screen **662** (FIG. **70**).

Pressing Set Date button **668** may cause HVAC controller **20** to display an illustrative screen **688**, as shown in FIG. **72**. Screen **688** may include one or more of a Month block **690**, a Day block **692** and a Year block **694**. Month block **690** may display a current month setting that can be adjusted, if desired, using Up arrow **680** and/or Down arrow **682**. Day block **692** may display a current day setting that can be adjusted up or down via Up arrow **680** and/or Down arrow **682**. Year block **694** may display a current year setting that can be adjusted, if necessary, using Up arrow **680** and Down arrow **682**. Cancel button **684**, if pressed, may cause HVAC controller **20** to revert to a previous screen without saving any

changes. Done button **686** may cause HVAC controller **20** to save any time changes made, and to subsequently revert to screen **662** (FIG. **70**).

FIGS. **73** through **95** provide illustrative but non-limiting examples of screens that may be displayed by HVAC controller **20** pertaining to viewing and/or changing preferences within HVAC controller **20**. In particular, FIG. **73** provides an illustrative screen **700** that may be displayed by HVAC controller **20** in response to someone pressing or otherwise selecting Preferences button **166** (FIG. **17**) in order to view and/or change preferences information.

Screen **700** includes a navigational bar **702** that may provide the user with information pertaining to where they are within the menu structure. A Previous Menu button **704** permits the user to, if desired, return to a previous menu. In some cases, pressing Previous Menu button **704** may cause HVAC controller **20** to revert to screen **150** (FIG. **17**). Screen **700** may include a number of menu items for which preferences may be selected. In some cases, there may be more menu items than can be displayed at one time on screen **700**. Thus, in some cases screen **700** may include an Up arrow button **730** and a Down arrow button **732** so that the user may scroll up and/or down through the menu items. In FIG. **73**, various menu items are shown including some that are shown outside of screen **700**. It should be understood that this is only illustrative, and that Up arrow button **730** and/or Down arrow button **732** may be used to scroll through these various menu items on screen **700**.

In some instances, screen **700** may display one or more of a Reminders button **706**, a Fahrenheit/Celsius button **708**, a 12 h/24 h Clock button **710**, a Display Options button **712**, a Language Options button **714**, a Schedule Options button **716**, an Adaptive Intelligent Recovery button **718**, a Restore Energy Star Settings button **720**, an Unoccupied Settings button **722**, a Ventilation Settings button **724**, a Wireless Device Manager button **726** and a Daylight Savings Time button **728**.

Pressing Reminders button **706** may cause HVAC controller **20** to display an illustrative screen **734**, as shown in FIG. **74**. Navigational bar **702** may, for example, display information informing the user that they have selected Reminders under Preferences, which is itself a menu item. Screen **734** may include, for example, one or more of a Humidifier Pad button **736**, an Air Filter button **738**, a UV lamp button **740**, and a Ventilator Filter button **742**. A Help button **744**, if pressed, may provide the user with information describing and/or explaining the options.

FIG. **75** provides an illustrative screen **746** that may be reached by pressing one of Humidifier Pad button **736**, Air Filter button **738**, UV lamp button **740**, or Ventilator Filter button **742**. As shown, screen **746** provides a generic illustration, but it will be recognized that HVAC controller **20** may correctly and properly reference a specific piece of equipment, depending on which menu button was pressed with respect to screen **734** (FIG. **74**). For example, if the user pressed Humidifier Pad button **736** one week before the expiration of the time period ascribed to the humidifier pad, screen **746** may state "Your system's humidifier pad has seven days remaining in its current cycle. It is set to be changed every year. When you have replaced your humidifier pad, please press Reset." Similar messages may be displayed pertaining to the air filter, ventilator filter, UV lamp and the like.

Once the user replaces the appropriate piece of equipment, they may reset the timer for that piece of equipment by pressing a Reset Timer button **748**. Help button **744** may provide the user with additional information while a Done button **752** may cause HVAC controller **20** to revert to a previous screen

25

such as screen 734 (FIG. 74). In some cases, the user may wish to alter the predetermined time period for a particular piece of equipment. For example, the user may determine that the humidifier pad becomes too dirty and mineral-encrusted when used for an entire year. A Change Life Cycle button 750, if pressed, may permit the user to alter the time period.

FIG. 76 provides an illustrative screen 754 that may be displayed by HVAC controller 20 when Change Life Cycle button 750 (FIG. 75) is pressed. Again, screen 754 illustrates a generic message that may be customized in accordance with which of Humidifier Pad button 736, Air Filter button 738, UV lamp button 740, or Ventilator Filter button 742 was pressed with respect to screen 734 (FIG. 74). In this particular case, it can be seen via navigational bar 702 that the user is being given a chance to alter the life cycle of the humidifier pad.

Screen 754 may include a timer block 756 that displays a current life cycle as well as whether the life cycle is being displayed in days, weeks, or the like. An Up button 758 may be used to increase the life cycle and a Down button 760 may be used to decrease the life cycle. A Cancel button 762 permits the user to exit screen 754 without making any changes, if desired, while Done button 752 may cause HVAC controller 20 to revert to a previous screen such as screen 734 (FIG. 74).

Returning briefly to FIG. 73, pressing Fahrenheit/Celsius button 708 may cause HVAC controller 20 to display an illustrative screen 764, as shown in FIG. 77. Navigational bar 702 provides the user with an indication of where they are within the hierarchical menu structure. Screen 764 includes a Fahrenheit button 766 and a Celsius button 768. If the user wants HVAC controller 20 to display temperatures and temperature set points in degrees Fahrenheit, they may instruct HVAC controller 20 to do so by pressing Fahrenheit button 766. Similarly, if the user wants HVAC controller 20 to display in degrees Celsius, they may instruct HVAC controller 20 to do so by pressing Celsius button 768. The user may cancel out, if desired, using Cancel button 762. Pressing Done button 752 may cause HVAC controller 20 to save any changes made and/or revert to a previous screen.

FIG. 78 provides an illustrative screen 770 that may be displayed by HVAC controller 20 as a result of the user pressing 12 h/24 h Clock button 710 (FIG. 73). Navigational bar 702 provides the user with an indication of where they are within the hierarchical menu structure. Screen 770 includes a 12 Hour Clock button 772 and a 24 Hour Clock button 774. If the user wants HVAC controller 20 to display time using numbers 0 through 12, and AM/PM, they may instruct HVAC controller 20 to do so by pressing 12 Hour Clock button 772. If the user wants HVAC controller 20 to display time using numbers 0 through 24, without using AM or PM, they may instruct HVAC controller 20 to do so by pressing 24 Hour Clock button 774. The user may cancel out, if desired, using Cancel button 762. Pressing Done button 752 may cause HVAC controller 20 to save any changes made and/or revert to a previous screen.

Returning briefly to FIG. 73, if the user presses Display Options button 712, HVAC controller 20 may display an illustrative screen 776, as shown in FIG. 79. Navigational bar 702 provides the user with an indication of where they are within the hierarchical menu structure. Previous Menu button 704 permits the user to revert to a previous screen. Screen 776 may include, for example, one or more a Backlight button 778, a Contrast button 780 and a Screensaver button 782. These are display options that can be customized or otherwise modified by the user.

26

Pressing Backlight button 778 may cause HVAC controller 20 to display an illustrative screen 786, as shown in FIG. 80. Screen 786 may include text 788 that instructs the user to set their inactive backlight level. A slider bar 788 includes a scale 790, a display 792, a Left arrow 794 and a Right arrow 796. Scale 790 may provide relative or qualitative terms such as dim and bright. Display 792 may, as illustrated, provide a reminder that it is the backlight level that is being set. Slider bar 788 includes an indicator 798 that may be moved left and/or right using left arrow 794 and/or right arrow 796, as desired. Indicator button 798 may, with respect to scale 790, provide a visual indication of the relative or qualitative backlight level and may, if desired, include a pointer that interacts with scale 790. In some instances, indicator button 798 may include a numerical representation of the backlight level setting. In some cases, the numerical representation may range from 0 to 10, or perhaps 1 to 10.

In some cases, the distance that indicator button 798 moves may be at least partially a function of how many times or for how long left arrow 794 and/or right arrow 796 are pressed. In some cases, indicator button 798 may be a touch-sensitive button, and may be moved left or right simply by the user touching indicator button 798 and dragging their finger left or right. Help button 744 may provide the user with further information. The user may cancel out, if desired, using Cancel button 762. Pressing Done button 752 may cause HVAC controller 20 to save any changes made and/or revert to a previous screen.

Returning briefly to FIG. 79, pressing Contrast button 780 may cause HVAC controller 20 to display an illustrative screen 800, as shown in FIG. 81. Screen 800 may include text 802 that instructs the user to set their contrast level. A slider bar 803 includes a scale 804, a display 806, a Left arrow 808 and a Right arrow 810. Scale 804 may provide relative or qualitative terms such as less contrast and more contrast. Display 806 may, as illustrated, provide a reminder that it is the contrast level that is being set. Slider bar 803 includes an indicator 812 that may be moved left and/or right using left arrow 808 and/or right arrow 810, as desired. Indicator button 812 may, with respect to scale 804, provide a visual indication of the relative or qualitative backlight level and may, if desired, include a pointer that interacts with scale 804. In some instances, indicator button 812 may include a numerical representation of the contrast level setting.

In some cases, the distance that indicator button 812 moves may be at least partially a function of how many times or for how long left arrow 808 and/or right arrow 810 are pressed. In some cases, indicator button 812 may be a touch-sensitive button, and may be moved left or right simply by the user touching indicator button 812 and dragging their finger left or right. Help button 744 may provide the user with further information. The user may cancel out, if desired, using Cancel button 762. Pressing Done button 752 may cause HVAC controller 20 to save any changes made and/or revert to a previous screen.

Returning briefly to FIG. 79, pressing Screensaver button 782 may cause HVAC controller 20 to display an illustrative screen 814, as shown in FIG. 82. Screen 814 may include text 816 that instructs the user to set the screensaver timeout time. A timer block 818 may display the current timeout time that may be increased using an Up button 820 and/or may be decreased using a Down button 822. Help button 744 may provide the user with further information. The user may cancel out, if desired, using Cancel button 762. Pressing Done button 752 may cause HVAC controller 20 to save any changes made and/or revert to a previous screen.

In some cases, a Screensaver Select button may be provided, which may allow a user to select a particular screensaver from a list of screen savers for use by HVAC controller 20. In some cases, at least some screen savers may be uploaded into HVAC controller 20 by the user for later selection. In some instances, screen savers may be uploaded using data port 18 (FIG. 1).

Returning briefly to FIG. 73, pressing Language Options button 714 may cause HVAC controller 20 to display an illustrative screen 824, as shown in FIG. 83. Navigational bar 702 provides the user with an indication of where they are within the hierarchical menu structure. In some instances, HVAC controller 20 may be configured to display text in one or more of several languages. Screen 824 may include one or more of an English button 826, a French button 828 and a Spanish button 830. These buttons are shown for illustrative purposes only as it will be recognized that other languages may be represented either in place of these or in addition to these.

If the user wants HVAC controller 20 to display text using English, they may instruct HVAC controller 20 to do so by pressing English button 826. If the user wants HVAC controller 20 to display text using French, they may instruct HVAC controller 20 to do so by pressing French button 828. HVAC controller 20 may be instructed to display text in Spanish if the user presses Spanish button 830. The user may cancel out, if desired, using Cancel button 762. Pressing Done button 752 may cause HVAC controller 20 to save any changes made and/or revert to a previous screen.

Returning briefly to FIG. 73, pressing Schedule Options button 716 may cause HVAC controller 20 to display an illustrative screen 832, as shown in FIG. 84. Navigational bar 702 provides the user with an indication of where they are within the hierarchical menu structure. In some cases, HVAC controller 20 may be a programmable HVAC controller that may operate in accordance with a predetermined or user-entered or modified schedule. In some instances, HVAC controller 20 may not be a programmable HVAC controller. Screen 832 includes a Programmable button 834 and a Non-Programmable button 836. The user may specify whether HVAC controller 20 is programmable or non-programmable by pressing the appropriate button. The user may cancel out, if desired, using Cancel button 762. Pressing Done button 752 may cause HVAC controller 20 to save any changes made and/or revert to a previous screen.

With respect to FIG. 73, pressing Adaptive Intelligent Recovery button 718 may cause HVAC controller 20 to display an illustrative screen 838, as shown in FIG. 85. Navigational bar 702 provides the user with an indication of where they are within the hierarchical menu structure. Screen 838 may include an On button 840 and an Off button 842. Adaptive Intelligent Recovery may be turned on by pressing On button 840 and/or may be turned off by pressing Off button 842. Adaptive Recovery may implement a control algorithm that initiates the HVAC equipment at an appropriate time before a step change in temperature set points (e.g. at a transition between programmable time periods) such that the temperature in the building reaches the new set point at or about the time that the temperature change is set to take place. Help button 744 may provide the user with further information. The user may cancel out, if desired, using Cancel button 762. Pressing Done button 752 may cause HVAC controller 20 to save any changes made and/or revert to a previous screen.

Returning briefly to FIG. 73, pressing Restore Energy Star Settings button 720 may cause HVAC controller 20 to display an illustrative screen 844, as shown in FIG. 86. Navigational

bar 702 provides the user with an indication of where they are within the hierarchical menu structure. Screen 844 may, as illustrated, include text giving the user an explanation of what an Energy Star schedule is and what it involves. Screen 844 may include a Select Energy Star Schedule button 846 that, if pressed, may cause HVAC controller 20 to operate in accordance with a predetermined and/or pre-programmed schedule that is designed for energy savings. The Energy Star program may be entered into HVAC controller 20 at the time of its manufacture, for example.

Returning briefly to FIG. 73, pressing Unoccupied Settings button 722 may cause HVAC controller 20 to display an illustrative screen 848, shown in FIG. 87. In some cases, HVAC controller 20 may be programmed or otherwise configured to permit operation of the HVAC equipment in accordance with an unoccupied setting, i.e., anytime the house is temporarily unoccupied. In some cases, this may correspond to the Leave period, or when HVAC controller 20 has been instructed that the house will be temporarily vacant as a result of vacation and the like. In some instances, it is contemplated that HVAC controller 20 may instead include or be in communication with one or more sensors that register whether someone is in the house, and thus may operate in accordance with an unoccupied setting when the house is sensed to be empty.

Navigational bar 702 provides the user with an indication of where they are within the hierarchical menu structure. Screen 848 may include text 850 that informs the user that they are viewing and/or changing the unoccupied heating and cooling temperature set points. Screen 848 may include a heating block 852 and a cooling block 854. Heating block 852 may include a display of the present unoccupied heating temperature set point and may include up arrow 758 and down arrow 760 that can be used to raise or lower the heating temperature set point, as desired. Cooling block 854 may include a display of the present unoccupied cooling temperature set point, which can be raised or lowered using up arrow 758 and/or down arrow 760, as desired.

Returning briefly to FIG. 73, pressing Ventilation Settings button 724 may cause HVAC controller to display screen 614, which is shown in FIG. 64 as previously discussed with respect to Ventilation button 160 (FIG. 17). Pressing Wireless Device Manager button 726 (FIG. 73) may cause HVAC controller 20 to display an illustrative screen 856, as shown in FIG. 88. Navigational bar 702 provides the user with an indication of where they are within the hierarchical menu structure. Previous Menu button 704 provides the user with an opportunity to reach a previous screen while Help button 744 may provide the user with additional information and/or guidance. Screen 856 may include, for example, one or more of an Add Device button 858, a View Connected Devices button 860, a Remove Device button 862 and/or a Rename Thermostat button 864. Wireless devices that may communicate with HVAC controller 20 include, for example, exterior temperature sensors, exterior humidity sensors, exterior wind sensors, interior humidity sensors, HVAC equipment, computers, computer networks, and the like.

Pressing Add Device button 858 may cause HVAC controller 20 to display an illustrative screen 866, as shown in FIG. 89. Navigational bar 702 provides the user with an indication of where they are within the hierarchical menu structure. In some cases, adding a wireless device entails pressing a particular button on the remote device in order to establish wireless communication between HVAC controller 20 and the remote device. Screen 866 may include text 868 that instructs the user to press the designated button on the remote device. Text 870 may inform the user that they have a limited amount

29

of time to locate the remote device and press the designated button. Cancel button **762**, if pressed, may cause HVAC controller **20** to revert to a previous screen such as screen **856** (FIG. **88**).

If wireless communication between HVAC controller **20** and the remote device is not successfully established, HVAC controller **20** may display an illustrative screen **872**, as shown in FIG. **90**. Navigational bar **702** provides the user with an indication of where they are within the hierarchical menu structure. Screen **872** may include text **874** informing the user that the remote device was not found. Pressing Cancel button **762** may cause HVAC controller **20** to revert to a previous screen such as screen **856** (FIG. **88**). A Try Again button **876** permits the user to try once again to establish wireless communication between HVAC controller **20** and the wireless device. Pressing Try Again button **876** may cause HVAC controller **20** to revert to screen **866** (FIG. **89**).

If wireless communication between HVAC controller **20** and the remote device was successfully established, HVAC controller **20** may display an illustrative screen **878**, as shown in FIG. **91**. Navigational bar **702** provides the user with an indication of where they are within the hierarchical menu structure. Screen **878** may include text **880** informing the user that the remote device has been successfully added. In the illustrated example, the remote device was an Outdoor Sensor. Pressing Done button **752** may cause HVAC controller **20** to revert to screen **856** (FIG. **88**).

Returning briefly to FIG. **88**, pressing View Connected Devices button **860** may cause HVAC controller **20** to display an illustrative screen **882**, as shown in FIG. **92**. Navigational bar **702** provides the user with an indication of where they are within the hierarchical menu structure. Screen **882** may include a text box **884** that lists the devices that are wirelessly connected to HVAC controller **20**. In the illustrated example, HVAC controller **20** is connected wirelessly to an Outdoor Sensor, a Remote Control Unit and IAQ (Indoor Air Quality) equipment. Pressing Done button **752** may cause HVAC controller **20** to revert to screen **856** (Screen **88**).

Returning briefly to FIG. **88**, pressing Remove Device button **862** may cause HVAC controller **20** to display an illustrative screen **886**, as shown in FIG. **93**. Previous Menu button **704** may permit the user to return to a previous screen without removing any devices. Navigational bar **702** provides the user with an indication of where they are within the hierarchical menu structure. Screen **886** may include one or more of an Outdoor Sensor button **888**, a Remote Control button **890** and an IAQ equipment button **892**. The user may remove one of the connected devices by pressing the appropriate button.

For example, if the user presses Outdoor sensor button **888**, HVAC controller **20** may display an illustrative screen **894**, as shown in FIG. **94**. Navigational bar **702** provides the user with an indication of where they are within the hierarchical menu structure. Screen **894** may include an inquiry **896**, asking the user if they want to remove the Outdoor Sensor. A No button **898**, if pressed, will cause HVAC controller **20** to revert to screen **886** (FIG. **93**) without removing any devices. A Yes button **900**, if pressed, will cause HVAC controller **20** to remove, i.e., no longer communicate with, the Outdoor Sensor, and then to revert to screen **856** (FIG. **88**).

Returning briefly to FIG. **88**, pressing Rename Thermostat button **864** may cause HVAC controller **20** to display an illustrative screen **902**, as shown in FIG. **95**. Screen **902** provides a touch-sensitive QWERTY keyboard that the user may use to enter a new name for HVAC controller **20**. Cancel button **762**, if pressed, may cause HVAC controller **20** to revert to a previous screen without changing the name of

30

HVAC controller **20**. Once the new name has been typed, pressing Done button **752** may cause HVAC controller **20** to save the new name as well as to revert to screen **856** (FIG. **88**).

FIGS. **96** through **112** provide illustrative but non-limiting examples of screens that may be displayed by HVAC controller **20** pertaining to viewing and/or changing temporary schedule changes within HVAC controller **20**. In particular, FIG. **96** provides an illustrative screen **904** that may be displayed by HVAC controller **20** in response to someone pressing or otherwise selecting Temporary Schedule Changes button **168** (FIG. **17**) in order to view and/or create temporary schedule changes.

Screen **904** may include Navigational bar **702**, which provides the user with an indication of where they are within the hierarchical menu structure. Previous Menu button **704** may permit the user to return to a previous screen while Help button **744** may provide the user with additional information or guidance. Screen **904** may include several schedule adjustment buttons that can be used for temporary schedule changes such as vacations, days off, sick days, sleeping in, staying up late, and the like.

In some instances, screen **904** may include one or more of a Vacation Mode button **906**, a Stay Home From Work button **908**, a Return Home Early button **910**, a Return Home Late button **912**, a Wake Up Early button **914**, a Stay Up Late button **916** and a View Schedule Adjustments button **918**. These are merely illustrative, as additional buttons such as a Sleep In button, a Go To Bed Early button, and the like may also be included even though they are not expressly illustrated herein. In some cases, as illustrated, there may be more schedule adjustment buttons than can be displayed at one time on screen **904**. An Up arrow **920** and a Down arrow **922** may be used as desired to scroll up and/or down through the displayed schedule adjustment buttons.

Vacation Mode button **906** may be used to provide HVAC controller **20** with information pertaining to the user's vacation schedule, including vacation start date, return home date, heating and cooling temperature set points during the vacation, and the like. In some cases, pressing Vacation Mode button **906** may bring the user to screen **472** (FIG. **47**), much the same as pressing Vacation Mode button **154** (FIG. **17**).

Returning briefly to FIG. **96**, pressing Stay Home From Work button **908** may cause HVAC controller **20** to display an illustrative screen **924**, as shown in FIG. **97**. Screen **924** may include text **926**, informing the user that they are to set the date that they plan to stay home from work. Screen **924** includes a month block **928** and a day block **930**. Month block **928** may display a month and may include an up arrow **932** and a down arrow **934** that can be used to change the month, if necessary. Day block **930** may display a date or a day of the week, which may be adjusted using up arrow **932** and down arrow **934**, as appropriate.

A Cancel button **936**, if pressed, may permit the user to exit screen **924** without setting a date for staying home from work. In some cases, HVAC controller **20** may revert to a previous screen such as screen **904** (FIG. **96**). A Done button **938** may be used by the user to inform HVAC controller **20** that they have entered the date on which they will be staying home from work. In some instances, pressing Done button **938** may cause HVAC controller **20** to display an illustrative screen **940**, as shown in FIG. **98**.

Screen **940** may include an inquiry **942**, asking the user to confirm that they wish to adjust their schedule for the aforementioned date. Screen **940** includes a No button **944** and a Yes button **946** so that the user may provide their answer. If the user presses No button **944**, HVAC controller **20** will not save any information pertaining to a schedule adjustment. If

31

the user presses Yes button 946, HVAC controller 20 saves the appropriate information. In either case, HVAC controller 20 may revert to a previous screen such as screen 904 (FIG. 96).

Returning briefly to FIG. 96, pressing Return Home Early button 910 may cause HVAC controller 20 to display an illustrative screen 948, as shown in FIG. 99. Screen 948 may include text 950, instructing the user to set the date that they will be home early. Screen 948 includes month block 928 and day block 930. Month block 928 may display a month that can be adjusted using up arrow 932 and down arrow 934, if necessary. Day block 930 may display a date or a day of the week, which may be adjusted using up arrow 932 and down arrow 934, as appropriate.

Cancel button 936, if pressed, may permit the user to exit screen 948 without setting a date for returning home early. In some cases, HVAC controller 20 may revert to a previous screen such as screen 904 (FIG. 96). A Next button 952, if pressed, informs HVAC controller 20 that the date has been set, and thus HVAC controller 20 may then display an illustrative screen 954, as shown in FIG. 100. Screen 954 may include text 956 instructing the user that they are to enter the time that they will be returning home early. Screen 954 may include a time block 958 that may display a time that may be adjusted up and/or down using up arrow 932 and/or down arrow 934 as desired. A Back button 960 may be used, for example, if the user wants to return to a previous screen such as screen 948 (FIG. 99).

Once the time has been set appropriately, pressing Next button 952 may cause HVAC controller 20 to display an illustrative screen 962, as shown in FIG. 101. Screen 962 may include an inquiry 964, asking the user to confirm their schedule change. In some cases, screen 962 may be displayed when a user presses Next button 952 after setting a date and time for returning home early, waking up early, staying up late, and the like. If the user presses No button 944, HVAC controller 20 will not save any information pertaining to a schedule adjustment. If the user presses Yes button 946, HVAC controller 20 saves the appropriate information. In either case, HVAC controller 20 may revert to a previous screen such as screen 904 (FIG. 96).

Returning briefly to FIG. 96, pressing Return Home Late button 912 may cause HVAC controller 20 to display an illustrative screen 966, as shown in FIG. 102. Screen 966 may include text 968, instructing the user that they are to set the date that they will be returning home late. Screen 966 includes month block 928 and day block 930. Month block 928 may display a month that can be changed using up arrow 932 and down arrow 934, if necessary. Day block 930 may display a date or a day of the week, which may be adjusted using up arrow 932 and down arrow 934, as appropriate.

Cancel button 936, if pressed, may permit the user to exit screen 966 without setting a date for returning home late. In some cases, HVAC controller 20 may revert to a previous screen such as screen 904 (FIG. 96). Next button 952, if pressed, informs HVAC controller 20 that the date has been set, and thus HVAC controller 20 may then display an illustrative screen 970, as shown in FIG. 103.

Screen 970 may include text 972 instructing the user that they are to enter the time that they will be returning home late. Screen 970 may include a time block 974 that may display a time that may be adjusted up and/or down using up arrow 932 and/or down arrow 934 as desired. Back button 960 may be used, for example, if the user wants to return to a previous screen such as screen 966 (FIG. 102). Once the time has been set appropriately, pressing Next button 952 may cause HVAC controller 20 to display illustrative screen 962, as shown in FIG. 101 and as previously discussed.

32

Returning briefly to FIG. 96, pressing Wake Up Early button 914 may cause HVAC controller 20 to display an illustrative screen 976, as shown in FIG. 104. Screen 976 may include text 978, instructing the user that they are to set the date that they will be waking up early. Screen 976 includes month block 928 and day block 930. Month block 928 may display a month that may be adjusted using up arrow 932 and/or down arrow 934, if necessary. Day block 930 may display a date or a day of the week, which may be adjusted using up arrow 932 and down arrow 934, as appropriate.

Cancel button 936, if pressed, may permit the user to exit screen 976 without setting a date for waking up early. In some cases, HVAC controller 20 may revert to a previous screen such as screen 904 (FIG. 96). Next button 952, if pressed, informs HVAC controller 20 that the date has been set, and thus HVAC controller 20 may then display an illustrative screen 980, as shown in FIG. 105.

Screen 980 may include text 982 instructing the user that they are to enter the time that they will be waking up early. Screen 980 may include a time block 984 that may display a time that may be adjusted up and/or down using up arrow 932 and/or down arrow 934 as desired. Back button 960 may be used, for example, if the user wants to return to a previous screen such as screen 976 (FIG. 104). Once the time has been set appropriately, pressing Next button 952 may cause HVAC controller 20 to display illustrative screen 962, as shown in FIG. 101 and as previously discussed.

Returning briefly to FIG. 96, pressing Stay Up Late button 916 may cause HVAC controller 20 to display an illustrative screen 984, as shown in FIG. 106. Screen 984 may include text 986, instructing the user that they are to set the date that they will be staying up late. Screen 984 includes month block 928 and day block 930. Month block 928 may display a month that may be adjusted using up arrow 932 and/or down arrow 934, if necessary. Day block 930 may display a date or a day of the week, which may be adjusted using up arrow 932 and down arrow 934, as appropriate.

Cancel button 936, if pressed, may permit the user to exit screen 984 without setting a date for staying up late. In some cases, HVAC controller 20 may revert to a previous screen such as screen 904 (FIG. 96). Next button 952, if pressed, informs HVAC controller 20 that the date has been set, and thus HVAC controller 20 may then display an illustrative screen 988, as shown in FIG. 107.

Screen 988 may include text 990 instructing the user that they are to enter the time that they will be staying up late. Screen 988 may include a time block 992 that may display a time that may be adjusted up and/or down using up arrow 932 and/or down arrow 934 as desired. Back button 960 may be used, for example, if the user wants to return to a previous screen such as screen 984 (FIG. 106). Once the time has been set appropriately, pressing Next button 952 may cause HVAC controller 20 to display illustrative screen 962, as shown in FIG. 101 and as previously discussed.

Returning briefly to FIG. 96, pressing View Schedule Adjustments button 918 may cause HVAC controller 20 to display an illustrative screen 994, shown in FIG. 108. Navigational bar 702 provides the user with an indication of where they are within the hierarchical menu structure. Screen 994 may include buttons representing each temporary schedule change that has been saved. In some cases, there may be more such buttons than can be displayed at one time. An Up arrow 996 and a Down arrow 998 may be used to scroll up and/or down through the buttons representing the temporary schedule changes, if necessary.

In the illustrated example, screen 994 includes a first button 1000 and a second button 1002. First button 1000 represents

33

a temporary schedule change in which the user has specified that they will be staying home from work. Second button **1002** represents a temporary schedule change in which the user has specified that they will be coming home from work early. Screen **994** permits the user to not only view their temporary schedule changes, but also to edit and/or delete them, as they wish. Screen **994** includes an Edit button **1004**, a Help button **1006**, a Cancel button **1008** and a Done button **1010**. By pressing one of first button **1000** or second button **1002**, the user may be able to either edit or cancel the temporary schedule change represented by the pressed button. Help button **1006**, if pressed, may cause HVAC controller **20** to display information providing further assistance and/or guidance. Pressing Done button **1010** may cause HVAC controller **20** to revert to a previous screen such as screen **904** (FIG. **96**). It is contemplated that an Add button may also be provided, which when selected, provides a screen similar to that shown in FIG. **96**.

For illustrative purposes, assume that second button **1002** has been selected. If the user presses Edit button **1004**, HVAC controller **20** may display an illustrative screen **1012**, as shown in FIG. **109**. Screen **1012** may include text **1014**, instructing the user that they are to set the date that they will be returning home early. Screen **1012** may include month block **928** and day block **930**. Month block **928** may display a month that can be adjusted using up arrow **932** and down arrow **934**, if necessary. Day block **930** may display a date or a day of the week, which may be adjusted using up arrow **932** and down arrow **934**, as appropriate. Back button **960** may cause HVAC controller **20** to revert to a previous screen such as screen **994** (FIG. **108**).

Pressing Next button **952** may cause HVAC controller **20** to display an illustrative screen **1016**, as shown in FIG. **110**. Screen **1016** may include text **1018**, instructing the user that they are to set the time that they will be returning home early. Screen **1012** may include a time block **1020** that displays a time that can be adjusted up or down using up arrow **932** and/or down arrow **934**, as desired. Back button **960** may cause HVAC controller **20** to revert to a previous screen such as screen **1012** (FIG. **109**).

Pressing Done button **952** may cause HVAC controller **20** to display an illustrative screen **1022**, as shown in FIG. **111**. Screen **1022** may include an inquiry **1024**, asking the user to confirm if they wish to save the schedule change or changes they have just made. Pressing Back button **960** may cause HVAC controller **20** to revert to a previous screen such as screen **1012** (FIG. **109**) or screen **1016** (FIG. **110**) so that the user may have another opportunity to edit the temporary schedule change. A Yes button **1026**, if pressed, instructs HVAC controller **20** to save the changes made and to revert to a previous screen such as screen **994** (FIG. **108**).

Returning briefly to FIG. **108**, pressing Cancel button **1008** may cause HVAC controller **20** to display an illustrative screen **1028**, as shown in FIG. **112**. Screen **1028** may include an inquiry **1030**, asking the user to confirm that they wish to cancel the selected temporary schedule change. A No button **1032** and a Yes button **1034** permit the user to provide their answer. Pressing No button **1032** may cause HVAC controller **20** to retain the temporary schedule change while pressing Yes button may cause HVAC controller **20** delete the temporary schedule change. In either case, HVAC controller **20** may revert to screen **994** (**108**).

FIGS. **113** through **114** provide illustrative but non-limiting examples of screens that may be displayed by HVAC controller **20** pertaining to viewing and/or changing a fan schedule within HVAC controller **20**. In particular, FIG. **113** provides an illustrative screen **1036** that may be displayed by

34

HVAC controller **20** in response to someone pressing or otherwise selecting Schedule Fan button **170** (FIG. **17**) in order to view and/or create a fan schedule. Screen **904** may include a Navigational bar **1038**, which provides the user with an indication of where they are within the hierarchical menu structure. Text **1040** may instruct the user to set the fan operation schedule for each of the time periods shown.

Screen **1036** may include, for example, one or more of a Wake button **1042**, a Leave button **1044**, a Return button **1046** and a Sleep button **1048**. Each of Wake button **1042**, Leave button **1044**, Return button **1046** and Sleep button **1048** may display a fan setting for that particular time period. For example, as currently set, screen **1036** shows a Run Continuously setting for the Wake period, an Intermittent setting for the Leave period, an Automatic setting for the Return period and a Run Continuously setting for the Sleep period. A Back button **1050**, if pressed, may cause HVAC controller **20** to return to a previous screen without saving any changes to the fan schedule. A Done button **1052**, if pressed, may cause HVAC controller **20** to return to a previous screen and to save any changes that were made to the fan schedule. In some cases, HVAC controller **20** may revert to a previous screen such as screen **150** (FIG. **17**).

If the user wants to change the fan setting for one of the time periods, they may do so by pressing the appropriate button. For example, pressing Wake button **1042** may cause HVAC controller **20** to display an illustrative screen **1054**, as shown in FIG. **114**. Screen **1054** may include Navigational bar **1038**, which provides the user with an indication of where they are within the hierarchical menu structure. Screen **1054** includes text **1056**, instructing the user to set the fan setting for the Wake time period. Screen **1054** includes a Run Continuously button **1058**, an Automatic button **1060**, and an Intermittent button **1062**. Although not illustrated, it is contemplated that screen **1054** may also include a fan setting button that instructs HVAC controller **20** to operate the fan any time the ventilation system (air exchanger) is operating and/or at some other designated time.

By pressing the appropriate fan operation button, the user may instruct HVAC controller **20** how to operate the fan in any particular time period. Pressing Back button **1050** may cause HVAC controller **20** to return to screen **1036** (FIG. **113**) without saving any changes while pressing Done button **1052** may cause HVAC controller **20** to save the changes made as well as to revert to a previous screen such as screen **150** (FIG. **17**).

FIG. **115** provides an illustrative but non-limiting example of a screen that may be displayed by HVAC controller **20** pertaining to locating a remote control. In particular, FIG. **115** provides an illustrative screen **1064** that may be displayed by HVAC controller **20** in response to someone pressing or otherwise selecting Find Remote button **174** (FIG. **17**). Screen **1064** may include a Navigational bar **1038**, which provides the user with an indication of where they are within the hierarchical menu structure. Text **1066** may instruct the user to wait while the remote is being located. A timer **1068** provides a countdown for finding the remote. In some cases, the remote control may beep in response to the user pressing Find Remote button **172**.

FIGS. **116** through **117** provide illustrative but non-limiting examples of screens that may be displayed by HVAC controller **20** pertaining to screen cleaning. In particular, FIG. **116** provides an illustrative screen **1070** that may be displayed by HVAC controller **20** in response to someone pressing or otherwise selecting Clean Screen button **176** (FIG. **17**). Screen **1070** may include Navigational bar **1038**, which provides the user with an indication of where they are within the

35

hierarchical menu structure. An inquiry 1072 may ask the user if they want to deactivate the touch screen so that it can be cleaned. If the user presses a Back button 1074, HVAC controller 20 may revert to a previous screen such as screen 150 (FIG. 17).

If the user presses a Yes button 1076, HVAC controller 20 may display an illustrative screen 1078, as shown in FIG. 117. Screen 1078 may include text 1080 instructing the user to proceed with cleaning the screen. In some cases, text 1080 may also provide the user with instructions as to how to clean the screen, what type or kind of cloth and/or cleaner or solvent to use, and the like. A counter 1082 may count backwards from a predetermined time such as 30 seconds so that the user knows when they need to finish cleaning the screen.

FIGS. 118 through 123 provide illustrative but non-limiting examples of screens that may be displayed by HVAC controller 20 pertaining to viewing and/or changing security settings within HVAC controller 20. In particular, FIG. 118 provides an illustrative screen 1084 that may be displayed by HVAC controller 20 in response to someone pressing or otherwise selecting Security Settings button 178 (FIG. 17) in order to view and/or alter security settings. Screen 1084 may include a Navigational bar 1086, which provides the user with an indication of where they are within the hierarchical menu structure. Text 1088 may instruct the user to enter their password.

It should be noted that HVAC controller 20 may display screen 1084 upon the user pressing Security Settings button 178 (FIG. 17) if the user has already created a password. In some cases, if no password has been created, pressing Security Settings button 178 may cause HVAC controller 20 to display a preferences screen as will be discussed with respect to FIG. 120. In some instances, if the user has not already set a password, HVAC controller 20 may default to an initial password such as "9999" which can be entered via screen 1084 so that the user may subsequently set their own password.

Screen 1084 includes a password block 1090 that may be used to enter a password. As illustrated, password block 1090 is configured to accommodate a four digit numerical password. It will be recognized that password block 1090 may easily be configured to accommodate smaller or even larger numerical password, or to include one or more letters of the alphabet. Password block 1090 may be configured to represent a four digit lock tumbler including a first digit location 1092, a second digit location 1094, a third digit location 1096 and a fourth digit location 1098. Each digit location may display a number and may include an up arrow 1100 and a down arrow 1102 that may be used to adjust the displayed number.

A Cancel button 1104, if pressed, may permit the user to return to a previous screen. A Done button 1106, if pressed, informs HVAC controller 20 that the password has been entered. If the password is not correct, HVAC controller 20 may display an illustrative screen 1108, as shown in FIG. 119. Navigational bar 1086 provides the user with an indication of where they are within the hierarchical menu structure. Screen 1108 may include text 1110, which informs the user that the password was not entered correctly and that they should try again. Pressing a Back button 1112 may cause HVAC controller 20 to revert to a previous screen such as screen 1084 (FIG. 118).

Referring briefly to FIG. 118, if the password was entered correctly, pressing Done button 1106 may cause HVAC controller 20 to display an illustrative screen 1114, as shown in FIG. 120. Navigational bar 1086 provides the user with an indication of where they are within the hierarchical menu

36

structure. A Previous Menu button 1116, if pressed, may cause HVAC controller 20 to revert to a previous screen such as screen 150 (FIG. 17). Screen 1114 may include, for example, one or more of a Change Lock Mode button 1118, a Create Password button 1120, a Change Password button 1122, and a Remove Password button 1124. Screen 1114 may not display all of these buttons at one time. For example, if no password has yet been created, screen 1114 will likely not include Change Password button 1122 or Remove Password button 1124. If a password has already been created, Create Password button 1120 may not be displayed.

Returning briefly to FIG. 120, pressing Change Lock Mode button 1118 may cause HVAC controller 20 to display an illustrative screen 1126, as shown in FIG. 121. Navigational bar 1086 provides the user with an indication of where they are within the hierarchical menu structure. A Help button 1128 may provide the user with additional guidance or information pertaining to their options. Screen 1126 may include one or more of an Unlocked button 1130, a Partial Lockout button 1132 and a Full Lockout button 1134.

The user may select their desired lock mode by pressing one of Unlocked button 1130, Partial Lockout button 1132 and Full Lockout button 1134. Pressing Cancel button 1104 may cause HVAC controller 20 to discard any selection that may have been made, while pressing Done button 1106 may cause HVAC controller 20 to remember any selection that may have been made. In either case, HVAC controller 20 may revert to a previous screen such as screen 1114 (FIG. 120).

In one illustrative embodiment, Full Lockout may require that the user enter a password to make any (or most) changes to the HVAC controller settings. Partial Lockout may require a password to change certain settings, such as system settings. Unlock may not require a password to make any changes.

Returning briefly to FIG. 120, pressing Create Password button 1120 may cause HVAC controller 20 to display an illustrative screen 1136, as shown in FIG. 122. As can be seen within Navigational bar 1086, screen 1136 pertains to creating a password. If a password has already been created or if a default password is built into HVAC controller 20, a screen similar to screen 1136 may be reached, for example, by pressing Change Password button (FIG. 120).

Screen 1136 may include Password block 1090, which as discussed above may be configured to represent a four digit lock tumbler including first digit location 1092, second digit location 1094, third digit location 1096 and fourth digit location 1098. Each digit location may display a number and may include up arrow 1100 and down arrow 1102 that may be used to adjust the displayed number. A Cancel button 1104, if pressed, may permit the user to return to a previous screen. A Done button 1106, if pressed, informs HVAC controller 20 that the password has been entered.

Returning briefly to FIG. 120, if a password has previously been created and thus Remove Password button 1124 is displayed, pressing Remove Password button 1124 may cause HVAC controller 20 to display an illustrative screen 1138, as shown in FIG. 123. Navigational bar 1086 provides the user with an indication of where they are within the hierarchical menu structure. Screen 1138 may include an inquiry 1140, asking the user if they want to remove password protection. A No button 1142 and a Yes button 1144 permit the user to enter their choice. If the user presses No button 1142, the password is retained while if the User presses Yes button 1144, the password is removed. In either case, HVAC controller 20 may revert to a previous screen such as screen 1114 (FIG. 120).

FIGS. 124 through 195 provide illustrative but non-limiting examples of screens that may be displayed by HVAC controller 20 pertaining to installer setup of HVAC controller

20. In particular, FIG. 124 provides an illustrative screen 1200 that may be displayed by HVAC controller 20 in response to someone pressing or otherwise selecting Installer Setup button 180 (FIG. 17) in order to access the installer setup menu. While it is contemplated that a homeowner may access the installer setup, the installer setup menu will likely be accessed by an installer or other HVAC contractor.

Screen 1200 may include a Navigational bar 1202, which provides the user with an indication of where they are within the hierarchical menu structure. Screen 1200 may include text 1204 instructing the installer that they are entering installer setup. An inquiry 1206 may ask the installer to confirm that they want to continue. If the installer does not want to continue into installer setup, they can return to a previous screen such as screen 150 (FIG. 17) by pressing a Cancel button 1208. However, if they wish to advance into installer setup, they may do so by pressing a Next button 1210, which may cause HVAC controller 20 to display an illustrative screen 1212, as shown in FIG. 125.

Screen 1212 provides an installer, HVAC contractor or other professional the opportunity to create a setup, view or edit a current setup, test the HVAC equipment and/or reach advanced installer setup options. Screen 1212 may include one or more of View/Edit Current Installer Setup button 1214, a Create Setup button 1216, an Installer Test button 1218 and an Advanced Options button 1220. A Back button 1222, if pressed, may cause HVAC controller 20 to revert to a previous screen such as screen 150 (FIG. 17). A Help button 1224 may provide the installer with additional information or guidance pertaining to their options. In some cases, the installer setup may be password protected.

Pressing Create Setup button 1216 may cause HVAC controller 20 to begin an installer setup process. In some case, HVAC controller 20 may display one or more screens (not illustrated) asking the installer to set parameters such as a language in which they want HVAC controller 20 to present questions and in which HVAC controller 20 receives answers. The following screens provide examples of screens that may be displayed by HVAC controller 20 during the installer setup process but they should not be construed as being limiting in any manner. Depending on the particular HVAC equipment that will be controlled by HVAC controller 20, more or fewer screens may be displayed, depending on the circumstances.

As illustrated, pressing Create Setup button 1216 may cause HVAC controller 20 to display an illustrative screen 1226, as shown in FIG. 126. Screen 1226 may include a banner 1228 that provides the installer with an indication of where they are within the menu structure as well as providing a numerical key. The numerical key may, for example, correspond to known thermostat programming numbers with which an installer may be familiar, although this is not required.

Text 1230 instructs the installer that they are to edit a device name. A Thermostat button 1232 may be pressed to edit the name of the thermostat. In some cases, additional buttons (not illustrated) may be provided, so that the user may edit the names, if desired, of multiple devices. Back button 1222 permits the user to revert to a previous screen while Help button 1224 may provide the installer with additional information or guidance pertaining to their options. A Done button 1234, if pressed, may cause HVAC controller 20 to exit the installer setup process and revert to a previous screen such as screen 1212 (FIG. 125) while Next button 1236 may cause HVAC controller 20 to progress to a subsequent screen within the Create Setup menu.

Pressing Thermostat button 1232 may cause HVAC controller 20 to display an illustrative screen 1238, as shown in

FIG. 127. Screen 1238 may include text 1240, reminding the installer that they are to enter a name for the device in question. Screen 1238 may provide a touch-sensitive QWERTY keyboard that the installer may use to enter the new name. Done button 1234 may, in this case, instruct HVAC controller 20 to save the newly entered name as well as to proceed to the next screen in the installer setup process. In some instances, pressing Done button 1234 may cause HVAC controller 20 to display an illustrative screen 1242, as shown in FIG. 128.

Screen 1242 may include banner 1228, which as noted above provides the installer with an indication of menu location as well as a reminder that they are to set the date. Screen 1242 may include one or more of a Month block 1244, a Day block 1246 and a Year block 1248. Month block 1244 may display a month and may include an up arrow 1250 and a down arrow 1252 that can be used to change the month, if necessary. Day block 1246 may display a day or a date that can be adjusted using up arrow 1250 and/or down arrow 1252, as desired. Year block 1248 may display a year that can be adjusted using up arrow 1250 and/or down arrow 1252, as appropriate.

Back button 1222 permits the installer to revert to a previous screen while Help button 1224 may provide the installer with additional information or guidance pertaining to their options. Done button 1234, if pressed, may cause HVAC controller 20 to exit the installer setup process and revert to a previous screen such as screen 1212 (FIG. 125), while Next button 1236 may cause HVAC controller 20 to progress to a subsequent screen within the Create Setup menu. In some cases, pressing Next button 1236 may cause HVAC controller 20 to display an illustrative screen 1254, as shown in FIG. 129.

Screen 1254 may include banner 1228, which as noted provides the installer with an indication of menu location as well as a reminder that they are to set the time. Screen 1254 may include one or more of a Hour block 1256, a Minute block 1258 and an AM/PM block 1260. Hour block 1256 may display a current hour time setting that may be adjusted using up arrow 1250 and/or down arrow 1252, as desired. Minute block 1258 may display a current minute time setting that can be increased or decreased using up arrow 1250 and/or down arrow 1252, as appropriate. AM/PM block 1260 may display an indication of whether the current time is AM or PM. Up arrow 1250 and/or down arrow 1252 may be used to adjust whether the current time is before noon or after noon.

Back button 1222 permits the installer to revert to a previous screen while Help button 1224 may provide the installer with additional information or guidance pertaining to their options. Done button 1234, if pressed, may cause HVAC controller 20 to exit the installer setup process and revert to a previous screen such as screen 1212 (FIG. 125), while Next button 1236 may cause HVAC controller 20 to progress to a subsequent screen within the Create Setup menu.

In some cases, pressing Next button 1236 may cause HVAC controller 20 to display an illustrative screen 1262, as shown in FIG. 130. Screen 1262 may include banner 1228, which provides the installer with an indication of menu location. Screen 1262 may permit the installer to specify equipment type. In some cases, screen 1262 may include one or more of a Conventional button 1264, a Heat Pump button 1266 and a Heat Only, No Fan button 1268. The installer may instruct HVAC controller 20 which type of equipment is or will be controlled by HVAC controller 20 by pressing the appropriate equipment button. While only three equipment buttons are shown, it will be appreciated that in some instances there may be more equipment buttons than can be displayed at one time. Screen 1262 may, therefore, include an

Up button **1270** and a Down button **1272** that can be used to scroll up and/or down through the displayed equipment buttons.

Back button **1222** permits the installer to revert to a previous screen, while Help button **1224** may provide the installer with additional information or guidance pertaining to their options. Done button **1234**, if pressed, may cause HVAC controller **20** to exit the installer setup process and revert to a previous screen such as screen **1212** (FIG. **125**) while Next button **1236** may cause HVAC controller **20** to progress to a subsequent screen within the Create Setup menu.

In some cases, pressing Next button **1236** may cause HVAC controller **20** to display an illustrative screen **1274**, as shown in FIG. **131**. Screen **1274** may include banner **1228**, which provides the installer with an indication of menu location and in this case informs the installer that they are to provide data pertaining to the number of heating stages and the number of cooling stages. Screen **1274** may include one or both of a Heat Stages block **1276** and a Cool Stages block **1278**. Heat Stages block **1276** may display a number of heating stages that can be increased or decreased using up arrow **1250** and/or down arrow **1252**, as desired. Cool Stages block **1278** may display a number of cooling stages that can be increased or decreased using up arrow **1250** and/or down arrow **1252**, as desired. HVAC controller **20** may be intelligent enough so that only options relevant to the equipment that is installed are provided in the menu. For example, if a single stage heat source is to be used, the Heat Stages block **1276** may not be provided or may be grayed out.

In some instances, HVAC controller **20** may be considered as displaying a first setup parameter in conjunction with a first descriptive text and a second, possibly related, setup parameter in conjunction with a second descriptive text. For example, and with respect to screen **1274**, a first setup parameter may be the number of heating stages, and the first descriptive text may be the text "Heat Stages" displayed immediately above Heat Stages block **1276**. A second setup parameter may be the number of cooling stages, and the second descriptive text may be the text "Cooling Stages" displayed immediately above Cool Stages block **1278**.

These related parameters may be organized into a common setup category and displayed on the same screen **1274**. The number of heating stages and the number of cooling stages, while applicable to different HVAC equipment, are related to a common setup category as to they both specify the number of stages. Grouping and displaying such related parameters into common setup category clusters on the display is believed to make the setup process more intuitive and efficient for the installer. Example common setup categories can include, for example, number of stages of an HVAC system, indoor air quality equipment parameters, heat pump lockout temperatures, humidity control parameters, ventilation parameters, cycles per hour (CPH) parameters, temperature set point stop limits, minimum off times, minimum on times, extended fan on times, display temperature offsets, and/or any other category as desired.

Back button **1222** permits the installer to revert to a previous screen while Help button **1224** may provide the installer with additional information or guidance pertaining to their options. Done button **1234**, if pressed, may cause HVAC controller **20** to exit the installer setup process and revert to a previous screen such as screen **1212** (FIG. **125**) while Next button **1236** may cause HVAC controller **20** to progress to a subsequent screen within the Create Setup menu.

In some cases, pressing Next button **1236** may cause HVAC controller **20** to display an illustrative screen **1280**, as shown in FIG. **132**. Screen **1280** may include banner **1228**,

which provides the installer with an indication of menu location and in this case informs the installer that they are to provide data pertaining to the number of cycles per hour while cooling. Screen **1280** may include one or more of a Stage **1** block **1282** and a Stage **2** block **1284**.

In the illustrative embodiment, Stage **1** block **1282** may display a number of cycles per hour for first stage cooling, which can be adjusted using up arrow **1250** and/or down arrow **1252**, as desired. Stage **2** block **1284** may display a number of cycles per hour for second stage cooling, which can be adjusted using up arrow **1250** and/or down arrow **1252**, as desired. In some cases, and as specified with respect to screen **1274** (FIG. **131**), there may be more than two cooling stages, or perhaps less than two cooling stages, and screen **1280** may accommodate this.

As noted above, HVAC controller **20** may be considered as displaying a first setup parameter in conjunction with a first descriptive text and a second, possibly related, setup parameter in conjunction with a second descriptive text. For example, and with respect to screen **1280**, a first setup parameter may be the number of cycles per hour for the first cooling stage, and the first descriptive text may be the text "Stage **1**" displayed immediately above Stage **1** block **1282**. A second setup parameter may be the number of cycles per hour for the second cooling stage, and the second descriptive text may be the text "Stage **2**" displayed immediately above Stage **2** block **1284**. These related parameters may be grouped into a common setup category and displayed on the same screen **1280**.

Back button **1222** permits the installer to revert to a previous screen while Help button **1224** may provide the installer with additional information or guidance pertaining to their options. Done button **1234**, if pressed, may cause HVAC controller **20** to exit the installer setup process and revert to a previous screen such as screen **1212** (FIG. **125**) while Next button **1236** may cause HVAC controller **20** to progress to a subsequent screen within the Create Setup menu.

In some cases, pressing Next button **1236** may cause HVAC controller **20** to display an illustrative screen **1286**, as shown in FIG. **133**. Screen **1286** may include banner **1228**, which provides the installer with an indication of menu location and in this case informs the installer that they are to provide data pertaining to the number of cycles per hour while heating. Screen **1286** may include one or more of a Stage **1** block **1288**, a Stage **2** block **1290** and a Stage **3** block **1292**.

In the illustrative embodiment, Stage **1** block **1288** may display a number of cycles per hour for first stage heating, which can be adjusted using up arrow **1250** and/or down arrow **1252**, as desired. Stage **2** block **1290** may display a number of cycles per hour for second stage heating, which can be adjusted using up arrow **1250** and/or down arrow **1252**, as desired. Stage **3** block **1292** may display a number of cycles per hour for third stage heating, which can be adjusted using up arrow **1250** and/or down arrow **1252**, as appropriate. In some cases, and as specified with respect to screen **1274** (FIG. **131**), there may be more than three heating stages, or perhaps less than three heating stages, and screen **1286** may accommodate this.

As noted above, HVAC controller **20** may be considered as displaying a first setup parameter in conjunction with a first descriptive text and a second, possibly related, setup parameter in conjunction with a second descriptive text. For example, and with respect to screen **1286**, a first setup parameter may be the number of cycles per hour for the first heating stage, and the first descriptive text may be the text "Stage **1**" displayed immediately above Stage **1** block **1288**. A second setup parameter may be the number of cycles per hour for the second heating stage, and the second descriptive text may be

the text "Stage 2" displayed immediately above Stage 2 block 1290. These related parameters may be organized into a common setup category and displayed on the same screen 1286.

Back button 1222 permits the installer to revert to a previous screen while Help button 1224 may provide the installer with additional information or guidance pertaining to their options. Done button 1234, if pressed, may cause HVAC controller 20 to exit the installer setup process and revert to a previous screen such as screen 1212 (FIG. 125) while Next button 1236 may cause HVAC controller 20 to progress to a subsequent screen within the Create Setup menu.

In some cases, pressing Next button 1236 may cause HVAC controller 20 to display an illustrative screen 1294, as shown in FIG. 134. Screen 1294 may include banner 1228, which provides the installer with an indication of menu location and in this case informs the installer that they are to provide data pertaining to fan settings. Screen 1294 may include, for example, one or more of a No Fan Operation button 1296, a Fan On With All Stages button 1298 and a Fan On With Stage 2 and 3 button 1300.

The installer may indicate their choice by pressing the appropriate fan setting button. While only three fan setting buttons are shown, it will be appreciated that in some instances there may be more fan setting buttons than can be displayed at one time. Screen 1294 may, therefore, include Up button 1270 and Down button 1272 that can be used to scroll up and/or down through the displayed fan setting buttons. Less fan setting buttons may also be displayed.

Back button 1222 permits the installer to revert to a previous screen while Help button 1224 may provide the installer with additional information or guidance pertaining to their options. Done button 1234, if pressed, may cause HVAC controller 20 to exit the installer setup process and revert to a previous screen such as screen 1212 (FIG. 125) while Next button 1236 may cause HVAC controller 20 to progress to a subsequent screen within the Create Setup menu.

In some cases, pressing Next button 1236 may cause HVAC controller 20 to display an illustrative screen 1302, as shown in FIG. 135. Screen 1302 may include banner 1228, which provides the installer with an indication of menu location and in this case informs the user that they are to provide data pertaining to a reversing valve. In some cases, screen 1302 may only be displayed if HVAC controller 20 was previously instructed that there was a heat pump, with respect to screen 1262 (FIG. 13). Screen 1302 may include an O button 1304 and a B button 1306. The installer may, for example, press O button 1304 if they want the reversing valve to reverse on cooling or they may press B button 1306 if they want the reversing valve to reverse on heating.

Back button 1222 permits the installer to revert to a previous screen while Help button 1224 may provide the installer with additional information or guidance pertaining to their options. Done button 1234, if pressed, may cause HVAC controller 20 to exit the installer setup process and revert to a previous screen such as screen 1212 (FIG. 125) while Next button 1236 may cause HVAC controller 20 to progress to a subsequent screen within the Create Setup menu.

In some cases, pressing Next button 1236 may cause HVAC controller 20 to display an illustrative screen 1308, as shown in FIG. 136. Screen 1308 may include banner 1228, which provides the installer with an indication of menu location and in this case informs the installer that they are to provide information pertaining to a back-up heat source, if there is one. If there is no back-up heat source, HVAC controller 20 may not display screen 1308. Illustrative screen 1308 may include an Electric button 1310 and a Fossil button

1312. The installer may press one of Electric button 1310 or Fossil button 1312 to instruct HVAC controller 20 appropriately.

Back button 1222 permits the installer to revert to a previous screen while Help button 1224 may provide the installer with additional information or guidance pertaining to their options. Done button 1234, if pressed, may cause HVAC controller 20 to exit the installer setup process and revert to a previous screen such as screen 1212 (FIG. 125) while Next button 1236 may cause HVAC controller 20 to progress to a subsequent screen within the Create Setup menu.

In some cases, pressing Next button 1236 may cause HVAC controller 20 to display an illustrative screen 1314, as shown in FIG. 137. Screen 1314 may, for example, only be displayed if the installer indicated with respect to screen 1308 (FIG. 136) that there was a fossil fuel back-up heat source. Screen 1314 may include banner 1228, which provides the installer with an indication of menu location and in this case informs the installer that they are to tell HVAC controller 20 whether or not there is an external fossil fuel kit. Screen 1314 may include a No button 1316 and a Yes button 1318. The installer may press No button 1316 if there is no external fossil fuel kit and may press Yes button 1318 if there is.

Back button 1222 permits the installer to revert to a previous screen while Help button 1224 may provide the installer with additional information or guidance pertaining to their options. Done button 1234, if pressed, may cause HVAC controller 20 to exit the installer setup process and revert to a previous screen such as screen 1212 (FIG. 125) while Next button 1236 may cause HVAC controller 20 to progress to a subsequent screen within the Create Setup menu.

In some cases, pressing Next button 1236 may cause HVAC controller 20 to display an illustrative screen 1320, as shown in FIG. 138. Screen 1320 may include banner 1228, which provides the installer with an indication of menu location and in this case informs the installer that they are to tell HVAC controller 20 whether or not there is an outdoor sensor. Screen 1320 may include a None button 1322 and a Remote button 1324. The installer may press None button 1320 if there is no outdoor sensor and may press Remote button 1324 if there is. In some cases, None button 1322 may instead be labeled "No" while Remote button 1324 may be labeled as "Yes".

Back button 1222 permits the installer to revert to a previous screen while Help button 1224 may provide the installer with additional information or guidance pertaining to their options. Done button 1234, if pressed, may cause HVAC controller 20 to exit the installer setup process and revert to a previous screen such as screen 1212 (FIG. 125) while Next button 1236 may cause HVAC controller 20 to progress to a subsequent screen within the Create Setup menu.

In some cases, pressing Next button 1236 may cause HVAC controller 20 to display an illustrative screen 1326, as shown in FIG. 139. Screen 1326 may, for example, only be displayed if the installer has previously indicated with respect to screen 1262 (FIG. 130) that there is a heat pump. Screen 1326 may include banner 1228, which provides the installer with an indication of menu location and in this case informs the installer that they are to provide information pertaining to dual fuel heat pump control. Screen 1326 may include, for example, one or more of a Balance Point Only button 1328, a Balance Point Plus 2° F. Droop button 1330 and a Balance Point and Aux Lockout Plus 2° F. Droop button 1332. The installer may press the appropriate button.

Back button 1222 permits the installer to revert to a previous screen while Help button 1224 may provide the installer with additional information or guidance pertaining to their

43

options. Done button 1234, if pressed, may cause HVAC controller 20 to exit the installer setup process and revert to a previous screen such as screen 1212 (FIG. 125) while Next button 1236 may cause HVAC controller 20 to progress to a subsequent screen within the Create Setup menu.

In some cases, pressing Next button 1236 may cause HVAC controller 20 to display an illustrative screen 1334, as shown in FIG. 140. Screen 1334 may include banner 1228, which provides the installer with an indication of menu location and in this case informs the installer that they are to provide information pertaining to the upstage to furnace timer. Screen 1334 may include an UpstageTime block 1336. Upstage Timer block 1336 may display a time and may also display the time units being used (minutes, in the illustrated example). Up arrow 1250 and/or Down arrow 1252 may be used to increase and/or decrease the upstage to furnace timer value.

Back button 1222 permits the installer to revert to a previous screen while Help button 1224 may provide the installer with additional information or guidance pertaining to their options. Done button 1234, if pressed, may cause HVAC controller 20 to exit the installer setup process and revert to a previous screen such as screen 1212 (FIG. 125) while Next button 1236 may cause HVAC controller 20 to progress to a subsequent screen within the Create Setup menu.

In some cases, pressing Next button 1236 may cause HVAC controller 20 to display an illustrative screen 1338, as shown in FIG. 141. Screen 1338 may, for example, only be displayed if the installer has previously indicated with respect to screen 1262 (FIG. 130) that there is a heat pump. Screen 1338 may include banner 1228, which provides the installer with an indication of menu location and in this case informs the installer that they are to provide information pertaining to heat pump lockouts.

Screen 1338 may include a Compressor Lockout block 1340 and an Aux Lockout block 1342. Compressor Lockout block 1340 may display a compressor lockout value such as a value given in degrees, which can be increased or decreased, as desired, using Up arrow 1250 and/or Down arrow 1252. Aux Lockout block 1342 may display an Aux lockout value such as a value given in degrees, which can be increased or decreased, as desired, using Up arrow 1250 and/or Down arrow 1252.

As noted above, HVAC controller 20 may be considered as displaying a first setup parameter in conjunction with a first descriptive text and a second, possibly related, setup parameter in conjunction with a second descriptive text. For example, and with respect to screen 1338, a first setup parameter may be the compressor lockout value, and the first descriptive text may be the text "Compressor Lockout" displayed immediately above Compressor Lockout block 1340. A second setup parameter may be the number of auxiliary lockout value, and the second descriptive text may be the text "Aux Lockout" displayed immediately above Aux Lockout block 1342. These related parameters may be organized into a common setup category and displayed on the same screen 1338.

Back button 1222 permits the installer to revert to a previous screen while Help button 1224 may provide the installer with additional information or guidance pertaining to their options. Done button 1234, if pressed, may cause HVAC controller 20 to exit the installer setup process and revert to a previous screen such as screen 1212 (FIG. 125) while Next button 1236 may cause HVAC controller 20 to progress to a subsequent screen within the Create Setup menu.

In some cases, pressing Next button 1236 may cause HVAC controller 20 to display an illustrative screen 1342, as

44

shown in FIG. 142. Screen 1342 may include banner 1228, which provides the installer with an indication of menu location and in this case informs the installer that they are to provide information pertaining to changeover settings. The installer may, for example, use screen 1342 to instruct HVAC controller 20 how changeovers between heating and cooling are to be handled, as well as a dead band setting. In some cases, if the installer selects manual changeover, there may not be a dead band setting to make or adjust.

Screen 1342 may include a Manual Changeover button 1344 and an Automatic Changeover button 1346. If the installer wants the user to have to manually switch HVAC controller 20 between heating mode and cooling mode as shown with respect to screen 134 (FIG. 15), the installer will press Manual Changeover button 1344. However, if the installer wants HVAC controller 20 to automatically switch between heating and cooling, the installer will press Automatic Changeover button 1346. This may be useful, for examples, in environments that may undergo large temperature swings on a daily basis.

Screen 1342 may include a Dead band block 1348, which displays a dead band value. In the illustrated example, this is displayed in degrees Fahrenheit. Up arrow 1250 and/or Down arrow 1252 may be used to increase or decrease the dead band value, as desired. The dead band value represents a minimum difference between a heating temperature set point and a cooling temperature set point and may be particularly relevant if HVAC controller 20 is operating in accordance with automatic changeover between heating and cooling and vice versa.

Back button 1222 permits the installer to revert to a previous screen while Help button 1224 may provide the installer with additional information or guidance pertaining to their options. Done button 1234, if pressed, may cause HVAC controller 20 to exit the installer setup process and revert to a previous screen such as screen 1212 (FIG. 125) while Next button 1236 may cause HVAC controller 20 to progress to a subsequent screen within the Create Setup menu.

In some cases, pressing Next button 1236 may cause HVAC controller 20 to display an illustrative screen 1350, as shown in FIG. 143. Screen 1350 may include banner 1228, which provides the installer with an indication of menu location and in this case informs the installer that they are to provide information pertaining to humidification equipment. Screen 1350 may include, for example, one or more of a None button 1352, an Internal Relay button 1354 and a Remote RF button 1356. None button 1352 may be pressed if there is no humidification equipment. Internal Relay button 1354 and/or Remote RF button 1356 may be used if there is humidification equipment, and may specify how HVAC controller 20 will be communicating with the humidification equipment.

Back button 1222 permits the installer to revert to a previous screen while Help button 1224 may provide the installer with additional information or guidance pertaining to their options. Done button 1234, if pressed, may cause HVAC controller 20 to exit the installer setup process and revert to a previous screen such as screen 1212 (FIG. 125) while Next button 1236 may cause HVAC controller 20 to progress to a subsequent screen within the Create Setup menu.

In some cases, pressing Next button 1236 may cause HVAC controller 20 to display an illustrative screen 1358, as shown in FIG. 144. Screen 1358 may include banner 1228, which provides the installer with an indication of menu location and in this case informs the installer that they are to provide information pertaining to humidification control. Screen 1358 may include, for example, a Disabled button 1360 and an Enabled button 1362 that can be used to specify

45

if humidification is disabled or enabled as well as a Disabled button **1364** and an Enabled button **1366** that can be used to specify if frost protection is disabled or enabled. These settings may, for example, affect whether or not HVAC controller **20** provides particular options to the user.

Back button **1222** permits the installer to revert to a previous screen while Help button **1224** may provide the installer with additional information or guidance pertaining to their options. Done button **1234**, if pressed, may cause HVAC controller **20** to exit the installer setup process and revert to a previous screen such as screen **1212** (FIG. **125**) while Next button **1236** may cause HVAC controller **20** to progress to a subsequent screen within the Create Setup menu.

In some cases, pressing Next button **1236** may cause HVAC controller **20** to display an illustrative screen **1368**, as shown in FIG. **145**. Screen **1368** may include banner **1228**, which provides the installer with an indication of menu location and in this case informs the installer that they are to provide information pertaining to humidification fan action. Screen **1368** may include, for example, one or more of a Humidification Force Fan button **1370**, an Only Humidify With Heat button **1372** and a Humidify Independent of Fan button **1374**. The installer may use screen **1368** to instruct HVAC controller **20** when and/or how to humidify by pressing the appropriate humidification button. While only three humidification buttons are shown, it will be appreciated that in some instances there may be more humidification buttons than can be displayed at one time. Screen **1368** may, therefore, include Up button **1270** and Down button **1272** that can be used to scroll up and/or down through the displayed humidification buttons.

Back button **1222** permits the installer to revert to a previous screen while Help button **1224** may provide the installer with additional information or guidance pertaining to their options. Done button **1234**, if pressed, may cause HVAC controller **20** to exit the installer setup process and revert to a previous screen such as screen **1212** (FIG. **125**) while Next button **1236** may cause HVAC controller **20** to progress to a subsequent screen within the Create Setup menu.

In some cases, pressing Next button **1236** may cause HVAC controller **20** to display an illustrative screen **1376**, as shown in FIG. **146**. Screen **1376** may include banner **1228**, which provides the installer with an indication of menu location and in this case informs the installer that they are to provide information pertaining to dehumidification equipment. Screen **1376** may include one or more of a None button **1378**, a Dehumidify With A/C button **1380** and a Whole House Dehumidifier button **1382**. If there is no equipment provided for dehumidification, the installer may press None button **1378**. If the only option is to use the air conditioning to dehumidify, the installer may press Dehumidify With A/C button **1380**. However, if there is a separate dehumidifier, the installer may press Whole House Dehumidifier button **1382**.

Back button **1222** permits the installer to revert to a previous screen while Help button **1224** may provide the installer with additional information or guidance pertaining to their options. Done button **1234**, if pressed, may cause HVAC controller **20** to exit the installer setup process and revert to a previous screen such as screen **1212** (FIG. **125**) while Next button **1236** may cause HVAC controller **20** to progress to a subsequent screen within the Create Setup menu.

In some cases, pressing Next button **1236** may cause HVAC controller **20** to display an illustrative screen **1384**, as shown in FIG. **147**. Screen **1384** may include banner **1228**, which provides the installer with an indication of menu location and in this case informs the installer that they are to provide information pertaining to the Over Cooling Limit.

46

Screen **1384** may include an Over Cooling Limit block **1386**, which may display a setting value for the Over Cooling Limit. Up arrow **1250** and/or down arrow **1252** may be used to increase and/or decrease the displayed value, as desired.

Back button **1222** permits the installer to revert to a previous screen while Help button **1224** may provide the installer with additional information or guidance pertaining to their options. Done button **1234**, if pressed, may cause HVAC controller **20** to exit the installer setup process and revert to a previous screen such as screen **1212** (FIG. **125**) while Next button **1236** may cause HVAC controller **20** to progress to a subsequent screen within the Create Setup menu.

In some cases, pressing Next button **1236** may cause HVAC controller **20** to display an illustrative screen **1388**, as shown in FIG. **148**. Screen **1388** may include banner **1228**, which provides the installer with an indication of menu location and in this case informs the installer that they are to provide information pertaining to dehumidification fan action. Screen **1388** may include one or more of a Dehumidification Forces Fan On button **1390** and a Dehumidify Independent of Fan button **1392**. The installer may press the appropriate button to instruct HVAC controller **20** accordingly.

Back button **1222** permits the installer to revert to a previous screen while Help button **1224** may provide the installer with additional information or guidance pertaining to their options. Done button **1234**, if pressed, may cause HVAC controller **20** to exit the installer setup process and revert to a previous screen such as screen **1212** (FIG. **125**) while Next button **1236** may cause HVAC controller **20** to progress to a subsequent screen within the Create Setup menu.

In some cases, pressing Next button **1236** may cause HVAC controller **20** to display an illustrative screen **1394**, as shown in FIG. **149**. Screen **1394** may include banner **1228**, which provides the installer with an indication of menu location and in this case informs the installer that they are to provide information pertaining to the dehumidification away mode. Screen **1394** may include a Disabled button **1396** and an Enabled button **1398**. The installer may press the appropriate button to specify whether the dehumidification away mode is enabled or disabled.

Back button **1222** permits the installer to revert to a previous screen while Help button **1224** may provide the installer with additional information or guidance pertaining to their options. Done button **1234**, if pressed, may cause HVAC controller **20** to exit the installer setup process and revert to a previous screen such as screen **1212** (FIG. **125**) while Next button **1236** may cause HVAC controller **20** to progress to a subsequent screen within the Create Setup menu.

In some cases, pressing Next button **1236** may cause HVAC controller **20** to display an illustrative screen **1400**, as shown in FIG. **150**. Screen **1400** may include banner **1228**, which provides the installer with an indication of menu location and in this case informs the installer that they are to provide information pertaining to dehumidification away fan action. Screen **1400** may include one or more of an Auto button **1402**, an On button **1404** and a Circulate button **1406**. The installer may press the appropriate button to specify how HVAC controller **20** should act during the dehumidification away mode.

Back button **1222** permits the installer to revert to a previous screen while Help button **1224** may provide the installer with additional information or guidance pertaining to their options. Done button **1234**, if pressed, may cause HVAC controller **20** to exit the installer setup process and revert to a previous screen such as screen **1212** (FIG. **125**) while Next

button **1236** may cause HVAC controller **20** to progress to a subsequent screen within the Create Setup menu.

In some cases, pressing Next button **1236** may cause HVAC controller **20** to display an illustrative screen **1408**, as shown in FIG. **151**. Screen **1408** may include banner **1228**, which provides the installer with an indication of menu location and in this case informs the installer that they are to provide information pertaining to heat pump lockouts. Screen **1408** may include one or more of a Temperature Low Limit block **1410**, a Temperature Setting block **1412** and a Dehumidification Setting block **1414**, each of which may include Up arrow **1250** and Down arrow **1252**. The installer may adjust one or more of a temperature low limit, a temperature setting and/or a dehumidification setting by adjusting the displayed values up and/or down using Up arrow **1250** and/or Down arrow **1252**.

Back button **1222** permits the installer to revert to a previous screen while Help button **1224** may provide the installer with additional information or guidance pertaining to their options. Done button **1234**, if pressed, may cause HVAC controller **20** to exit the installer setup process and revert to a previous screen such as screen **1212** (FIG. **125**) while Next button **1236** may cause HVAC controller **20** to progress to a subsequent screen within the Create Setup menu.

In some cases, pressing Next button **1236** may cause HVAC controller **20** to display an illustrative screen **1416**, as shown in FIG. **152**. Screen **1416** may include banner **1228**, which provides the installer with an indication of menu location and in this case informs the installer that they are to provide information pertaining to ventilation control. Screen **1416** may include one or more of an Off button **1418**, a Ventilation Always Allowed button **1420** and a Ventilation Disabled in Sleep button **1422**. The installer may set the desired ventilation control by pressing one Off button **1418**, Ventilation Always Allowed button **1420** and Ventilation Disabled in Sleep button **1422**, as appropriate.

Back button **1222** permits the installer to revert to a previous screen while Help button **1224** may provide the installer with additional information or guidance pertaining to their options. Done button **1234**, if pressed, may cause HVAC controller **20** to exit the installer setup process and revert to a previous screen such as screen **1212** (FIG. **125**) while Next button **1236** may cause HVAC controller **20** to progress to a subsequent screen within the Create Setup menu.

In some cases, pressing Next button **1236** may cause HVAC controller **20** to display an illustrative screen **1424**, as shown in FIG. **153**. Screen **1424** may include banner **1228**, which provides the installer with an indication of menu location and in this case informs the installer that they are to provide information pertaining to ventilation house size. In some cases, ventilation rates may be determined based at least partially upon the number of bedrooms within a house and/or the physical size of the house. Other physical parameters related to the house or other structure are also contemplated.

In the illustrative embodiment, screen **1424** may include one or more of a Bedroom Number block **1426** and a House Size block **1428**. Bedroom Number block **1426** may display a number of bedrooms that can be adjusted up and/or down, as desired, using Up arrow **1250** and/or Down arrow **1250**. House Size block **1428** may display a house size (in square feet) that can be adjusted up and/or down, as desired, using Up arrow **1250** and/or Down arrow **1250**.

As noted above, HVAC controller **20** may be considered as displaying a first setup parameter in conjunction with a first descriptive text and a second, possibly related, setup parameter in conjunction with a second descriptive text. For example, and with respect to screen **1424**, a first setup param-

eter may be the number of bedrooms, and the first descriptive text may be the text "Number of Bedrooms" displayed immediately above Bedroom Number block **1426**. A second setup parameter may be the house size, and the second descriptive text may be the text "Size of House" displayed immediately above House Size block **1428**. These related parameters may be organized into a common setup category and displayed on the same screen **1424**.

Back button **1222** permits the installer to revert to a previous screen while Help button **1224** may provide the installer with additional information or guidance pertaining to their options. Done button **1234**, if pressed, may cause HVAC controller **20** to exit the installer setup process and revert to a previous screen such as screen **1212** (FIG. **125**) while Next button **1236** may cause HVAC controller **20** to progress to a subsequent screen within the Create Setup menu.

In some cases, pressing Next button **1236** may cause HVAC controller **20** to display an illustrative screen **1430**, as shown in FIG. **154**. Screen **1430** may include banner **1228**, which provides the installer with an indication of menu location and in this case informs the installer that they are to provide information pertaining to ventilation levels. In some cases, ventilation rates may be determined based at least partially upon a ventilation level (in cubic feet per minute) and/or a percentage of a maximum ventilation rate. The ventilation rates may also, in some cases, depend on the parameters specified in FIG. **153** as well as other parameters, if desired.

In the illustrative embodiment, screen **1430** may include one or more of a Ventilation Level block **1432** and a Max Ventilation Limit block **1434**. Ventilation Level block **1432** may display a ventilation rate that can be adjusted up and/or down, as desired, using Up arrow **1250** and/or Down arrow **1250**. Max Ventilation Limit block **1434** displays a percentage value that can be adjusted up and/or down, as desired, using Up arrow **1250** and/or Down arrow **1250**. In some instances, HVAC controller **20** may display text **1436**, informing the installer that their settings satisfy (or do not satisfy) one or more standardized requirements or guidelines, such as the ASHRAE 62.2 standard.

As noted above, HVAC controller **20** may be considered as displaying a first setup parameter in conjunction with a first descriptive text and a second, possibly related, setup parameter in conjunction with a second descriptive text. For example, and with respect to screen **1430**, a first setup parameter may be a ventilation level, and the first descriptive text may be the text "Ventilation Level" displayed immediately above Ventilation Level block **1432**. A second setup parameter may be the ventilation rate, and the second descriptive text may be the text "Max Ventilation Limit" displayed immediately above Max Ventilation Limit block **1434**. These related parameters may be organized into a common setup category and displayed on the same screen **1430**.

Back button **1222** permits the installer to revert to a previous screen while Help button **1224** may provide the installer with additional information or guidance pertaining to their options. Done button **1234**, if pressed, may cause HVAC controller **20** to exit the installer setup process and revert to a previous screen such as screen **1212** (FIG. **125**) while Next button **1236** may cause HVAC controller **20** to progress to a subsequent screen within the Create Setup menu.

In some cases, pressing Next button **1236** may cause HVAC controller **20** to display an illustrative screen **1438**, as shown in FIG. **155**. Screen **1438** may include banner **1228**, which provides the installer with an indication of menu location and in this case informs the installer that they are to provide information pertaining to ventilation fan action.

Screen **1438** may include one or more of a Ventilation Forces Fan On button **1440** and a Ventilate Independent of Fan button **1442**. In some HVAC installations, for example, it may be beneficial for the furnace blower motor (fan) to run when the air exchanger operates. In some installations, the air exchanger may function properly without requiring the furnace blower motor to run. The installer may press the appropriate button.

Back button **1222** permits the installer to revert to a previous screen while Help button **1224** may provide the installer with additional information or guidance pertaining to their options. Done button **1234**, if pressed, may cause HVAC controller **20** to exit the installer setup process and revert to a previous screen such as screen **1212** (FIG. **125**) while Next button **1236** may cause HVAC controller **20** to progress to a subsequent screen within the Create Setup menu.

In some cases, pressing Next button **1236** may cause HVAC controller **20** to display an illustrative screen **1444**, as shown in FIG. **156**. Screen **1444** may include banner **1228**, which provides the installer with an indication of menu location and in this case informs the installer that they are to provide information pertaining to whether to ventilate upon high humidity. Screen **1444** may include one or more of an Enabled button **1446** and a Disabled button **1448**. The installer may press the appropriate button.

Back button **1222** permits the installer to revert to a previous screen while Help button **1224** may provide the installer with additional information or guidance pertaining to their options. Done button **1234**, if pressed, may cause HVAC controller **20** to exit the installer setup process and revert to a previous screen such as screen **1212** (FIG. **125**) while Next button **1236** may cause HVAC controller **20** to progress to a subsequent screen within the Create Setup menu.

In some cases, pressing Next button **1236** may cause HVAC controller **20** to display an illustrative screen **1450**, as shown in FIG. **157**. Screen **1450** may include banner **1228**, which provides the installer with an indication of menu location and in this case informs the installer that they are to provide information pertaining to replacement reminders. Screen **1450** may include one or more of a Furnace Filter block **1452**, a Humidifier Pad block **1454** and a UV lamp block **1456**. It will be recognized that these are merely illustrative, as more or fewer replacement reminders may be incorporated into HVAC controller **20**.

In the illustrative example shown, Furnace Filter block **1452** may display a time period such as a number of runtime days that should elapse before HVAC controller **20** provides the user with a reminder to replace the furnace filter screen as previously shown with respect to screen **92** (FIG. **10**). Up arrow **1250** and/or Down arrow **1252** may be used to increase or decrease the displayed value. Humidifier Pad block **1454** may display a time period such as a number of calendar days that should elapse before HVAC controller **20** provides the user with a reminder to replace the humidifier pad. UV lamp block **1456** may display a time period such as a number of years that should elapse before HVAC controller **20** provides the user with a reminder to replace the UV lamp.

As noted above, HVAC controller **20** may be considered as displaying a first setup parameter in conjunction with a first descriptive text and a second, possibly related, setup parameter in conjunction with a second descriptive text. For example, and with respect to screen **1450**, a first setup parameter may be a replacement period for a furnace filter, and the first descriptive text may be the text "Furnace Filter" displayed immediately above Furnace Filter block **1452**. A second setup parameter may be a replacement period for an humidifier pad, and the second descriptive text may be the

text "Humidifier Pad" displayed immediately above Humidifier Pad block **1454**. These related parameters may be organized into a common setup category and displayed on the same screen **1450**.

Back button **1222** permits the installer to revert to a previous screen while Help button **1224** may provide the installer with additional information or guidance pertaining to their options. Done button **1234**, if pressed, may cause HVAC controller **20** to exit the installer setup process and revert to a previous screen such as screen **1212** (FIG. **125**) while Next button **1236** may cause HVAC controller **20** to progress to a subsequent screen within the Create Setup menu.

In some cases, pressing Next button **1236** may cause HVAC controller **20** to display an illustrative screen **1458**, as shown in FIG. **158**. Screen **1458** may include banner **1228**, which provides the installer with an indication of menu location and in this case informs the installer that they are to provide information pertaining to furnace filter run time. Screen **1458** may include a Count Heat and Cool Run Time button **1460** and an Only Count Cool Run Time button **1462**. In some cases, the installer may want to count both heating time and cooling time towards furnace filter replacement timing, and thus may press Count Heat and Cool Run Time button **1460**. In some instances, the installer may only want to count cooling time, and thus may press Only Count Cool Run Time button **1462**.

Back button **1222** permits the installer to revert to a previous screen while Help button **1224** may provide the installer with additional information or guidance pertaining to their options. Done button **1234**, if pressed, may cause HVAC controller **20** to exit the installer setup process and revert to a previous screen such as screen **1212** (FIG. **125**) while Next button **1236** may cause HVAC controller **20** to progress to a subsequent screen within the Create Setup menu.

In some cases, pressing Next button **1236** may cause HVAC controller **20** to display an illustrative screen **1464**, as shown in FIG. **159**. Screen **1464** may include banner **1228**, which provides the installer with an indication of menu location and in this case informs the installer that they are to provide information pertaining to a number of schedule periods per day. In some cases, the installer may want HVAC controller **20** to operate in accordance with four time periods per day, sometimes known as the Wake period, the Leave period, the Return period and the Sleep period, and thus may press a Four Periods Per Day button **1468**. In some instances, such as if the space is occupied during the day every day, the installer may want HVAC controller **20** to only use the Wake period and the Sleep period, and thus may press a Two Periods Per Day button **1466**.

Back button **1222** permits the installer to revert to a previous screen while Help button **1224** may provide the installer with additional information or guidance pertaining to their options. Done button **1234**, if pressed, may cause HVAC controller **20** to exit the installer setup process and revert to a previous screen such as screen **1212** (FIG. **125**) while Next button **1236** may cause HVAC controller **20** to progress to a subsequent screen within the Create Setup menu.

In some cases, pressing Next button **1236** may cause HVAC controller **20** to display an illustrative screen **1470**, as shown in FIG. **160**. Screen **1470** may include banner **1228**, which provides the installer with an indication of menu location and in this case informs the installer that they are to provide information pertaining to temperature range stops. Screen **1470** may include one or more of a Maximum Heat Setpoint block **1472** and a Minimum Cool Setpoint block **1474**.

51

Maximum Heat Setpoint block **1472** may display a temperature value that limits how high a user may raise a heating temperature set point. Up arrow **1250** and/or Down arrow **1252** may be used to adjust this value, as desired. Minimum Cool Setpoint block **1474** may display a temperature value that limits how low a user may drop a cooling temperature set point. Up arrow **1250** and/or Down arrow **1252** may be used to adjust this value, as desired.

As noted above, HVAC controller **20** may be considered as displaying a first setup parameter in conjunction with a first descriptive text and a second, possibly related, setup parameter in conjunction with a second descriptive text. For example, and with respect to screen **1470**, a first setup parameter may be a maximum heat set point, and the first descriptive text may be the text “Maximum Heat Setpoint” displayed immediately above Maximum Heat Setpoint block **1472**. A second setup parameter may be a minimum cool set point, and the second descriptive text may be the text “Minimum Cool Setpoint” displayed immediately above Minimum Cool Setpoint block **1474**. These related parameters may be organized into a common setup category and displayed on the same screen **1470**.

Back button **1222** permits the installer to revert to a previous screen while Help button **1224** may provide the installer with additional information or guidance pertaining to their options. Done button **1234**, if pressed, may cause HVAC controller **20** to exit the installer setup process and revert to a previous screen such as screen **1212** (FIG. **125**) while Next button **1236** may cause HVAC controller **20** to progress to a subsequent screen within the Create Setup menu.

In some cases, pressing Next button **1236** may cause HVAC controller **20** to display an illustrative screen **1476**, as shown in FIG. **161**. Screen **1476** may include banner **1228**, which provides the installer with an indication of menu location and in this case informs the installer that they are to provide information pertaining to minimum off times. Screen **1476** may include one or more of a Non-Compressor Stages block **1478** and a Compressor Stages block **1480**. Each of Non-Compressor Stages block **1478** and Compressor Stages block **1480** may display a value that can be increased or decreased, as desired, using Up arrow **1250** and/or Down arrow **1252**.

As noted above, HVAC controller **20** may be considered as displaying a first setup parameter in conjunction with a first descriptive text and a second, possibly related, setup parameter in conjunction with a second descriptive text. For example, and with respect to screen **1476**, a first setup parameter may be a non-compressor minimum off time, and the first descriptive text may be the text “Non-Compressor Stages” displayed immediately above Non-Compressor Stages block **1478**. A second setup parameter may be a compressor minimum off time, and the second descriptive text may be the text “Compressor Stages” displayed immediately above Minimum Cool Setpoint block **1474**. These related parameters may be organized into a common setup category and displayed on the same screen **1476**.

Back button **1222** permits the installer to revert to a previous screen while Help button **1224** may provide the installer with additional information or guidance pertaining to their options. Done button **1234**, if pressed, may cause HVAC controller **20** to exit the installer setup process and revert to a previous screen such as screen **1212** (FIG. **125**) while Next button **1236** may cause HVAC controller **20** to progress to a subsequent screen within the Create Setup menu.

In some cases, pressing Next button **1236** may cause HVAC controller **20** to display an illustrative screen **1482**, as shown in FIG. **162**. Screen **1482** may include banner **1228**,

52

which provides the installer with an indication of menu location and in this case informs the installer that they are to provide information pertaining to minimum on times. Screen **1482** may include one or more of Non-Compressor Stages block **1478** and Compressor Stages block **1480**, each of which may display a value that can be increased or decreased, as desired, using Up arrow **1250** and/or Down arrow **1252**.

As noted above, HVAC controller **20** may be considered as displaying a first setup parameter in conjunction with a first descriptive text and a second, possibly related, setup parameter in conjunction with a second descriptive text. For example, and with respect to screen **1482**, a first setup parameter may be a non-compressor minimum on time, and the first descriptive text may be the text “Non-Compressor Stages” displayed immediately above Non-Compressor Stages block **1478**. A second setup parameter may be a compressor stages minimum on time, and the second descriptive text may be the text “Compressor Stages” displayed immediately above Compressor Stages block **1478**. These related parameters may be organized into a common setup category and displayed on the same screen **1482**.

Back button **1222** permits the installer to revert to a previous screen while Help button **1224** may provide the installer with additional information or guidance pertaining to their options. Done button **1234**, if pressed, may cause HVAC controller **20** to exit the installer setup process and revert to a previous screen such as screen **1212** (FIG. **125**) while Next button **1236** may cause HVAC controller **20** to progress to a subsequent screen within the Create Setup menu.

In some cases, pressing Next button **1236** may cause HVAC controller **20** to display an illustrative screen **1484**, as shown in FIG. **163**. Screen **1484** may include banner **1228**, which provides the installer with an indication of menu location and in this case informs the installer that they are to provide information pertaining to extended fan on times. Screen **1484** may include one or more of an Extended Heat Time block **1486** and an Extended Cool Time block **1488**. Each of Extended Heat Time block **1486** and Extended Cool Time block **1488** may display a value that can be increased or decreased, as desired, using Up arrow **1250** and/or Down arrow **1252**.

As noted above, HVAC controller **20** may be considered as displaying a first setup parameter in conjunction with a first descriptive text and a second, possibly related, setup parameter in conjunction with a second descriptive text. For example, and with respect to screen **1476**, a first setup parameter may be an extended heating fan time, and the first descriptive text may be the text “Extended Time in Heat” displayed immediately above Extended Heat Time block **1486**. A second setup parameter may be an extended cooling fan time, and the second descriptive text may be the text “Extended Time in Cool” displayed immediately above Extended Cool Time block **1488**. These related parameters may be organized into a common setup category and displayed on the same screen **1484**.

Back button **1222** permits the installer to revert to a previous screen while Help button **1224** may provide the installer with additional information or guidance pertaining to their options. Done button **1234**, if pressed, may cause HVAC controller **20** to exit the installer setup process and revert to a previous screen such as screen **1212** (FIG. **125**) while Next button **1236** may cause HVAC controller **20** to progress to a subsequent screen within the Create Setup menu.

In some cases, pressing Next button **1236** may cause HVAC controller **20** to display an illustrative screen **1490**, as shown in FIG. **164**. Screen **1490** may include banner **1228**, which provides the installer with an indication of menu loca-

tion and in this case informs the installer that they are to provide information pertaining to heating control settings. In some cases, these control settings may influence parameters used in a PID (Proportional-Integral-Derivative) and/or other control. Screen 1490 includes a Less Aggressive button 1492, a Standard button 1494 and a More Aggressive button 1496. The installer may influence the performance of HVAC controller 20 by pressing one of these buttons.

Back button 1222 permits the installer to revert to a previous screen while Help button 1224 may provide the installer with additional information or guidance pertaining to their options. Done button 1234, if pressed, may cause HVAC controller 20 to exit the installer setup process and revert to a previous screen such as screen 1212 (FIG. 125) while Next button 1236 may cause HVAC controller 20 to progress to a subsequent screen within the Create Setup menu.

In some cases, pressing Next button 1236 may cause HVAC controller 20 to display an illustrative screen 1498, as shown in FIG. 165. Screen 1498 may include banner 1228, which provides the installer with an indication of menu location and in this case informs the installer that they are to provide information pertaining to cooling control settings. In some cases, these control settings may influence parameters used in a PID (Proportional-Integral-Derivative) and/or other control. Screen 1498 includes Less Aggressive button 1492, Standard button 1494 and More Aggressive button 1496. The installer may influence the performance of HVAC controller 20 by pressing one of these buttons.

Back button 1222 permits the installer to revert to a previous screen while Help button 1224 may provide the installer with additional information or guidance pertaining to their options. Done button 1234, if pressed, may cause HVAC controller 20 to exit the installer setup process and revert to a previous screen such as screen 1212 (FIG. 125) while Next button 1236 may cause HVAC controller 20 to progress to a subsequent screen within the Create Setup menu.

In some cases, pressing Next button 1236 may cause HVAC controller 20 to display an illustrative screen 1500, as shown in FIG. 166. Screen 1500 may include banner 1228, which provides the installer with an indication of menu location and in this case informs the installer that they are to provide information pertaining to display offsets. In some cases, the installer may want to have HVAC controller 20 display or otherwise operate in accordance with temperature values that are adjusted, or offset, from the detected temperatures.

Screen 1500 may include one or more of an Indoor Temperature block 1502, an Outdoor Temperature block 1504 and an Indoor Humidity block 1506. Indoor Temperature block 1502 may display an offset value in degrees that can be adjusted using Up arrow 1250 and/or Down arrow 1252, as desired. Outdoor Temperature block 1504 may display an offset value in degrees that can be adjusted using Up arrow 1250 and/or Down arrow 1252, as desired. Indoor Humidity block 1506 may display an offset value in percentage that can be adjusted using Up arrow 1250 and/or Down arrow 1252, as desired.

As noted above, HVAC controller 20 may be considered as displaying a first setup parameter in conjunction with a first descriptive text and a second, possibly related, setup parameter in conjunction with a second descriptive text. For example, and with respect to screen 1500, a first setup parameter may be an indoor temperature offset, and the first descriptive text may be the text "Indoor Temperature" displayed immediately above Indoor Temperature block 1502. A second setup parameter may be an outdoor temperature offset, and the second descriptive text may be the text "Outdoor

Temperature" displayed immediately above Outdoor Temperature block 1504. A third setup parameter may be an indoor humidity offset, and a third descriptive text may be the text "Indoor Humidity" displayed immediately above Indoor Humidity block 1506. These related parameters may be organized into a common setup category and displayed on the same screen 1500.

Back button 1222 permits the installer to revert to a previous screen while Help button 1224 may provide the installer with additional information or guidance pertaining to their options. Done button 1234, if pressed, may cause HVAC controller 20 to exit the installer setup process and revert to a previous screen such as screen 1212 (FIG. 125) while Next button 1236 may cause HVAC controller 20 to progress to a subsequent screen within the Create Setup menu.

In some cases, pressing Next button 1236 may cause HVAC controller 20 to display an illustrative screen 1508, as shown in FIG. 167. Screen 1508 may include banner 1228, which provides the installer with an indication of menu location and in this case informs the installer that they are to provide dealer information. Screen 1508 may include a Dealer Name button 1510 and a Dealer Phone Number button 1512. Pressing Dealer Name button 1510, for example, may cause HVAC controller 20 to display an illustrative screen 1514, as shown in FIG. 168. Screen 1514 provides a touch-sensitive QWERTY keyboard that the user may use to enter the dealer name. Once the dealer name has been typed, pressing Done button 1516 may cause HVAC controller 20 to save the new name as well as to revert to screen 1508 (FIG. 167). A similar procedure may be used to enter the dealer's telephone number by touching Dealer Phone Number button 1512.

Referring briefly to FIG. 167, Back button 1222 permits the installer to revert to a previous screen while Help button 1224 may provide the installer with additional information or guidance pertaining to their options. Done button 1234, if pressed, may cause HVAC controller 20 to exit the installer setup process and revert to a previous screen such as screen 1212 (FIG. 125) while Next button 1236 may cause HVAC controller 20 to progress to a subsequent screen within the Create Setup menu.

In some cases, pressing Next button 1236 may cause HVAC controller 20 to display an illustrative screen 1518, as shown in FIG. 169. Screen 1518 may include banner 1228, which provides the installer with an indication of menu location and in this case informs the installer that they are to provide additional dealer information. Screen 1518 may include a Dealer E-Mail button 1520 and a Dealer Website button 1522. Pressing Dealer E-Mail button 1520, for example, may cause HVAC controller 20 to display an illustrative screen 1524, as shown in FIG. 170. Screen 1524 provides a touch-sensitive QWERTY keyboard that the user may use to enter the dealer's email address. Once the dealer email address has been typed, pressing Done button 1526 may cause HVAC controller 20 to save the email address as well as to revert to screen 1518 (169). A similar procedure may be used the dealer's website by pressing Dealer Website button 1522.

Referring briefly to FIG. 169, Back button 1222 permits the installer to revert to a previous screen while Help button 1224 may provide the installer with additional information or guidance pertaining to their options. Done button 1234, if pressed, may cause HVAC controller 20 to exit the installer setup process and revert to a previous screen such as screen 1212 (FIG. 125) while Next button 1236 may cause HVAC con-

troller 20 to progress to a subsequent screen within the Create Setup menu, or to revert to the first screen within the Create Setup menu.

Referring briefly to FIG. 125, pressing View/Edit Current Installer Setup button 1214 may cause HVAC controller 20 to display an illustrative screen 1528, as shown in FIG. 171. Screen 1528 may include navigational bar 1228, which provides the installer with an indication of menu location. Screen 1528 may provide information pertaining to a number of settings, which may include more information than can be displayed at one time, and thus may include Up button 1270 and Down button 1272 so that the installer can scroll up and/or down through the displayed settings and settings categories.

As illustrated, screen 1528 explicitly shows a System Type button 1530, a Humidification button 1532 and a Dehumidification button 1540. Humidification button 1532 has been pressed to expand the sub-headings under humidification, as evidenced by the down arrow displayed within Humidification button 1532. The sub-headings include a Humidity Sensor button 1534, an Equipment Type button 1536 and a Control Strategy button 1538. It can be seen that some of this information has not yet been entered into HVAC controller 20. A Done button 1542, if pressed, may cause HVAC controller 20 to revert to a previous screen such as screen 1212 (FIG. 125). In some cases, the installer may touch one of the buttons, such as Equipment Type button 1536, and HVAC controller 20 may open the appropriate menu or menus to enter the desired information. A Back button may then return the installer to screen 1528. This may provide an efficient way for the installer to enter and/or change settings for HVAC controller 20.

Returning briefly to FIG. 125, pressing Installer Test button 1218 may cause HVAC controller 20 to display an illustrative screen 1544, as shown in FIG. 172. Screen 1544 may include banner 1546, which reminds the user that they are at a screen in which they can test cooling stages. Screen 1544 may include one or more of an Off button 1548, a Cool Stage One button 1550 and a Cool Stages One and Two button 1552. The installer may press one or more of these buttons, and then ascertain if the HVAC equipment is responding properly.

Back button 1222 permits the installer to revert to a previous screen while Help button 1224 may provide the installer with additional information or guidance pertaining to their options. Done button 1234, if pressed, may cause HVAC controller 20 to exit the installer test process and revert to a previous screen such as screen 1212 (FIG. 125) while Next button 1236 may cause HVAC controller 20 to progress to a subsequent screen within the Installer Test menu.

In some cases, pressing Next button 1236 may cause HVAC controller 20 to display an illustrative screen 1554, as shown in FIG. 173. Screen 1544 may include banner 1546, which reminds the user that they are at a screen in which they can test fan operation. Screen 1554 may include an Off button 1556 and an On button 1558. The installer may press one or more of these buttons, and then ascertain if the blower motor is responding properly.

Back button 1222 permits the installer to revert to a previous screen while Help button 1224 may provide the installer with additional information or guidance pertaining to their options. Done button 1234, if pressed, may cause HVAC controller 20 to exit the installer test process and revert to a previous screen such as screen 1212 (FIG. 125) while Next button 1236 may cause HVAC controller 20 to progress to a subsequent screen within the Installer Test menu.

In some cases, pressing Next button 1236 may cause HVAC controller 20 to display an illustrative screen 1560, as

shown in FIG. 174. Screen 1560 may include banner 1546, which reminds the user that they are at a screen in which they can test heating stages. Screen 1560 may permit more testing options than can be displayed at one time, and when so provided, screen 1560 may include Up button 1270 and Down button 1272 so that the installer can scroll up and/or down through the displayed testing options. Screen 1560 may include, for example, one or more of a Heat Stages One and Two On button 1562, a Heat Stages One, Two and Three On button 1564 and a Heat Stages One, Two, Three and Four On button 1566. The installer may press one or more of these buttons, and then ascertain if the furnace is responding properly.

Back button 1222 permits the installer to revert to a previous screen while Help button 1224 may provide the installer with additional information or guidance pertaining to their options. Done button 1234, if pressed, may cause HVAC controller 20 to exit the installer test process and revert to a previous screen such as screen 1212 (FIG. 125) while Next button 1236 may cause HVAC controller 20 to progress to a subsequent screen within the Installer Test menu.

In some cases, pressing Next button 1236 may cause HVAC controller 20 to display an illustrative screen 1568, as shown in FIG. 175. Screen 1568 may include banner 1546, which reminds the user that they are at a screen in which they can test emergency heating stages. Screen 1568 may permit more testing options than can be displayed at one time, and thus may include Up button 1270 and Down button 1272 so that the installer can scroll up and/or down through the displayed buttons. Screen 1568 may include one or more of an EM Heat Stage One On button 1570, an EM Heat Stages One and Two On button 1572 and a Heat Stages One, Two and Three On button 1574. The installer may press one or more of these buttons, and then ascertain if the furnace is responding properly.

Back button 1222 permits the installer to revert to a previous screen while Help button 1224 may provide the installer with additional information or guidance pertaining to their options. Done button 1234, if pressed, may cause HVAC controller 20 to exit the installer test process and revert to a previous screen such as screen 1212 (FIG. 125) while Next button 1236 may cause HVAC controller 20 to progress to a subsequent screen within the Installer Test menu.

In some cases, pressing Next button 1236 may cause HVAC controller 20 to display an illustrative screen 1576, as shown in FIG. 176. Screen 1576 may include banner 1546, which reminds the user that they are at a screen in which they can test operation of the indoor air quality equipment. Screen 1576 may include one or more of a Humidifier Off button 1578, a Humidifier On button 1580, a Dehumidifier Off button 1582, a Dehumidifier On button 1584, a Ventilator On button 1586 and a Ventilator Off button 1588. The installer may press one or more of these buttons, and then ascertain if the indoor air quality equipment is responding properly.

Back button 1222 permits the installer to revert to a previous screen while Help button 1224 may provide the installer with additional information or guidance pertaining to their options. Done button 1234, if pressed, may cause HVAC controller 20 to exit the installer test process and revert to a previous screen such as screen 1212 (FIG. 125) while Next button 1236 may cause HVAC controller 20 to progress to a subsequent screen within the menu structure.

Returning briefly to FIG. 125, pressing Advanced Options button 1218 may cause HVAC controller 20 to display an illustrative screen 1590, as shown in FIG. 177. Screen 1590 may include Navigational bar 1228, which provides the installer with an indication of where they are within the hier-

57

archical menu. Screen **1590** may include one or more of a Configure Using USB button **1592** and a Restore Factory Defaults button **1594**. Back button **1222** permits the installer to revert to a previous screen while Help button **1224** may provide the installer with additional information or guidance pertaining to their options.

Pressing Restore Factory Defaults button **1594** may cause HVAC controller **20** to display an illustrative screen **1596**, as shown in FIG. **178**. Navigational bar **1228** provides the installer of an indication of where they are within the hierarchical menu structure. Screen **1596** may include an inquiry **1598**, asking the installer if they wish to delete any and all parameter settings in favor of their factory default settings. A Yes button **1600** and a No button **1602** permit the installer to provide their answer. A Cancel button **1604**, if pressed, may cause HVAC controller **20** to revert to a previous screen such as screen **1212** (FIG. **125**) or screen **1590** (FIG. **177**).

Returning briefly to FIG. **177**, in some instances HVAC controller **20** may be configured to permit an installer to download a configuration file onto a USB device or other portable storage device so that the configuration file may be uploaded into another HVAC controller. This may make programming an HVAC controller much quicker, rather than having to go through the setup screens as discussed herein. In some cases, pressing Configure Using USB button **1592** may cause HVAC controller **20** display an illustrative screen **1606**, as shown in FIG. **179**.

Screen **1606** includes text **1608**, instructing the installer to insert the USB memory stick or related storage device. The memory stick or related storage device may be inserted into, for example, a compatible data port such as data port **18** (FIG. **1**). A Cancel button **1610**, if pressed, may cause HVAC controller **20** to revert to a previous screen such as screen **1590** (FIG. **177**). If the installer inserts the USB device in response to screen **1606**, HVAC controller **20** may display an illustrative screen **1612**, as shown in FIG. **180**. In some cases, with respect to FIG. **177**, controller **20** may display screen **1612** upon insertion of a USB device even if the installer does not press Configure Using USB button **1592**.

Screen **1612** may include a navigation bar **1614** that provides the installer with a reminder of where they are within the USB setup menu. A Previous Menu button **1616**, if pressed, may cause HVAC controller **20** to revert to a previous screen. In some cases, HVAC controller **20** may display a screen (not illustrated) reminding the installer to remove the USB device when appropriate, although this is not required.

In some cases, screen **1612** may provide more option buttons than can be displayed at one time. An Up button **1618** and a Down button **1620** may be used, as desired, to scroll up and/or down through the displayed option buttons. Screen **1612** may include, for example, one or more of a Load Configuration to Thermostat button **1622**, a Save Configuration From Thermostat button **1624**, a Dealer Information button **1626** and a Safely Remove USB Device button **1628**.

In some instances, pressing Load Configuration to Thermostat button **1622** may cause HVAC controller **20** to display an illustrative screen **1630**, shown in FIG. **181**. Navigation bar **1614** provides the installer with a reminder of where they are within the USB setup menu. Screen **1630** may provide a number of configuration buttons including a First Configuration button **1632**, a Second Configuration button **1634**, a Third Configuration button **1636** and a Fourth Configuration button **1638**. As the USB device may include more configurations than can be displayed at one time, screen **1630** may include Up button **1618** and Down button **1620** so that the installer may scroll up and down, as desired.

58

In some instances, the USB device (not illustrated) may include a number of different configurations. In some cases, these configurations may be for different residential and/or light commercial environments but may be for a particular type of thermostat. In some cases, these configurations may also be for different types or models of thermostats. HVAC controller **20** may in some instances only display configurations that are appropriate for the HVAC controller being configured.

The installer may select one of the configurations by pressing the appropriate configuration button such as one of First Configuration button **1632**, Second Configuration button **1634**, Third Configuration button **1636** and Fourth Configuration button **1638**. A View Configuration button **1640** may be pressed in order to obtain more information regarding a particular configuration including, for example, being able to preview a number of the operating parameters included in the selected configuration. These operating parameters may be organized in a hierarchical manner, and may be previewed through a hierarchical menu structure. If the configuration does not fit on the display, HVAC controller **20** may display scroll bars that may be used to scroll through the displayed information. As illustrated, First Configuration button **1632** (labeled ABC.XML) has been selected. Upon pressing View Configuration button **1638**, HVAC controller **20** may display an illustrative screen **1646**, as shown in FIG. **183**.

Screen **1646** includes Navigation bar **1614**, which provides the installer with a reminder of where they are within the USB setup menu. A particular configuration file may include more setup topics than can be displayed at one time, and thus screen **1646** may include Up button **1618** and Down button **1620** so that the installer may scroll up and down, as desired. Screen **1646** may include one or more of a System Setup button **1648**, a System Control Options button **1650**, a Scheduling Options button **1652**, and a Zoning Options **1654**, but are not limited to these. Other possible buttons (not displayed) may include one or more of Display Settings, Calendar Settings, Humidification Settings, Dehumidification Settings, Ventilation Settings, and Service Reminders; as well as things such as various wallpapers for home screens, screen savers, skins, etc., that might be used to customize the look and feel of the display, if desired.

A Show All Values button **1656**, if pressed, may cause HVAC controller **20** to expand each of the options buttons such as System Setup button **1648**, System Control Options button **1650**, Scheduling Options button **1652**, and Zoning Options **1654** and to display each of the parameters and parameter values pertaining to each of the options buttons. A Help button **1658** may provide the installer with additional information, guidance, options and the like. A Done button **1660**, if pressed, may cause HVAC controller **20** to revert to a previous screen such as screen **1630** (FIG. **181**).

Returning briefly to FIG. **180**, if the installer presses Load Configuration to Thermostat button **1622** and there are no compatible configuration files on the USB device, HVAC controller **20** may display an illustrative screen **1662**, as shown in FIG. **182**. Screen **1662** may include Navigation bar **1614**, which provides the installer with a reminder of where they are within the USB setup menu. Screen **1662** may include text **1664** informing the installer that there are no compatible configuration files on the USB device. The installer may have to try a different USB device, or perform the setup process manually. An OK button **1666** may cause HVAC controller **20** to revert to a previous screen.

Returning briefly to FIG. **181**, pressing Load button **1644** may cause HVAC controller **20** to upload the selected configuration from the USB device. If the upload is not success-

ful, HVAC controller 20 may display a screen (not illustrated) providing an appropriate error message and/or a suggested way to correct the error. If the upload is successful, HVAC controller 20 may display an illustrative screen 1668, as shown in FIG. 184. Screen 1668 may include text 1670 informing the installer that the configuration was successfully loaded. An OK button 1672, if pressed, may cause HVAC controller 20 to revert to a previous screen such as screen 1612 (FIG. 180).

Returning briefly to FIG. 180, pressing Save Configuration From Thermostat button 1624 may cause HVAC controller 20 to display an illustrative screen 1674, as shown in FIG. 185. Screen 1674 provides a touch-sensitive QWERTY keyboard that the installer may use to enter a name for the configuration that will be downloaded from HVAC controller 20 to the USB device (not illustrated). A Done button 1676, if pressed, may cause HVAC controller 20 to attempt to upload the newly named configuration to the USB device. If the configuration is successfully uploaded, HVAC controller 20 may display an illustrative screen 1678, as shown in FIG. 186. Screen 1678 may include text 1680, informing the installer that the configuration was successfully saved to the USB device. OK button 1672, if pressed, may cause HVAC controller 20 to revert to a previous screen such as screen 1612 (FIG. 180).

In some instances, a current configuration may be saved as a file on the USB or other external memory device. The name of the current configuration may be used as the file name. It will be appreciated that if there are two or more configurations saved on the USB or other external memory device, each will have a unique configuration name and a corresponding unique file name.

Returning briefly to FIG. 180, pressing Dealer Information button 1626 may cause HVAC controller 20 to display an illustrative screen 1682, as shown in FIG. 187. Screen 1626 may include Navigation bar 1614, which provides the installer with a reminder of where they are within the USB setup menu. Previous Menu button 1616, if pressed, may cause HVAC controller 20 to revert to a previous screen such as screen 1612 (FIG. 180). As there may include more options than can be displayed at one time, screen 1682 may include Up button 1618 and Down button 1620 so that the installer may scroll up and down, as desired. Screen 1682 may include, for example, one or more of a Load Dealer Info Into Thermostat button 1684, a Save Dealer Info From Thermostat button 1686, a Load Dealer Logo into Thermostat button 1688 and a Safely Remove USB Device button 1690.

Pressing Load Dealer Info Into Thermostat button 1684 may cause HVAC controller 20 to display an illustrative screen 1692, as shown in FIG. 188. Screen 1692 may include Navigation bar 1614, which provides the installer with a reminder of where they are within the USB setup menu. As there may include more dealer information files than can be displayed at one time, screen 1692 may include Up button 1618 and Down button 1620 so that the installer may scroll up and down, as desired.

Screen 1692 may provide a number of dealer information buttons including a First Dealer File button 1694, a Second Dealer File button 1696, a Third Dealer File button 1698 and a Fourth Dealer File button 1700. The installer may select one of the dealer information files by pressing the appropriate button such as one of First Dealer File button 1694, Second Dealer File button 1696, Third Dealer File button 1698 and Fourth Dealer File button 1700.

A Preview Dealer Info button 1702 may be pressed in order to obtain more information regarding a particular configuration. A Cancel button 1704 may be pressed to return to a previous screen such as screen 1682 (FIG. 187). Pressing a

Load button 1706 may cause HVAC controller 20 to attempt to upload the selected dealer information file from the USB device. In some cases, the file may be corrupted or may otherwise not be useable.

If the file is corrupt or otherwise not compatible with HVAC controller 20, and the installer presses either of Preview Dealer Info button 1702 or Load button 1706, HVAC controller 20 may display an illustrative screen 1708, as shown in FIG. 189. Screen 1708 may include text 1710, informing the installer that the selected dealer information file is corrupted or otherwise not compatible with HVAC controller 20. It should be noted that HVAC controller 20 may display a similar screen if, with respect to screen 1630 (FIG. 181), the selected configuration file is corrupted or otherwise not compatible with HVAC controller 20. Pressing OK button 1672 may cause HVAC controller 20 to revert to a previous screen such as screen 1692 (FIG. 188).

Returning briefly to FIG. 188, and if the selected dealer information file is intact, HVAC controller 20 may display an illustrative screen 1712, as shown in FIG. 190. Navigation bar 1614 may provide the installer with a reminder of where they are within the USB setup menu. Screen 1708 may include text 1714, providing contact information corresponding to the selected dealer information file. A Return button 1716, if pressed, may cause HVAC controller 20 to revert to a previous screen such as screen 1692 (FIG. 188).

Pressing Load button 1706 (FIG. 188), assuming the selected dealer information file is correct and the selected file is successfully uploaded from the USB device, HVAC controller 20 may display an illustrative screen 1718, shown in FIG. 191. Navigation bar 1614 may provide the installer with a reminder of where they are within the USB setup menu. Screen 1718 may display the successfully uploaded dealer information, including one or more of text 1714 and/or a dealer logo 1720. A Done button 1722, if pressed, may cause HVAC controller 20 to revert to a previous screen such as screen 1682 (FIG. 187).

Returning briefly to FIG. 187, pressing Save Dealer Info From Thermostat button 1686 may cause HVAC controller 20 to display an illustrative screen 1724 as shown in FIG. 192, which provides a touch-sensitive QWERTY keyboard that the installer may use to enter a name for the dealer information file to be downloaded from HVAC controller 20 to the USB device (not illustrated).

A Done button 1726, if pressed, may cause HVAC controller 20 to attempt to upload the newly named dealer information file to the USB device. If the configuration is successfully uploaded, HVAC controller 20 may display an illustrative screen 1728, as shown in FIG. 193. Navigation bar 1614 may provide the installer with a reminder of where they are within the USB setup menu. Screen 1728 may include text 1730, informing the installer that the dealer information file was successfully saved to the USB device. OK button 1672, if pressed, may cause HVAC controller 20 to revert to a previous screen such as screen 1682 (FIG. 187).

Returning briefly to FIG. 187, pressing Load Dealer Logo Into Thermostat button 1688 may cause HVAC controller 20 to display an illustrative screen 1732, as shown in FIG. 194. Because there may be more dealer logo files than can be displayed at one time, screen 1732 may include Up button 1618 and Down arrow 1620, so that the installer may scroll up and/or down through the listed dealer logo files, if desired. Screen 1732 may, as illustrated, include a First Dealer Logo file button 1734, a Second Dealer Logo file button 1736 and a Third Dealer Logo button 1738.

After selecting a dealer logo file by pressing the appropriate button, the installer may preview the logo by pressing a

61

View Dealer Logo button 1740. Cancel button 1704 may be pressed to return to a previous screen such as screen 1682 (FIG. 187). Load button 1706 may be pressed to attempt to upload the selected dealer logo file from the USB device to HVAC controller 20. If the attempt is successful, HVAC controller 20 may display a screen (not illustrated) similar to screen 1668 (FIG. 184). If the dealer logo file is corrupted, as may be discovered when the installer attempts to preview the logo and/or tries to upload the dealer logo file, HVAC controller 20 may display a screen (not illustrated) similar to screen 1708 (FIG. 189).

Returning briefly to FIG. 187, pressing Safely Remove USB Device button 1690 may cause HVAC controller 20 to display an illustrative screen 1742, as shown in FIG. 195. Navigation bar 1614 may provide the installer with a reminder of where they are within the USB setup menu. Screen 1742 may include text 1744 informing the installer that it is safe to remove the USB device. Cancel button 1704, if pressed, may cause HVAC controller 20 to revert to a previous screen such as screen 1612 (FIG. 180).

The disclosure should not be considered limited to the particular examples described above, but rather should be understood to cover all aspects of the invention as set out in the attached claims. Various modifications, equivalent processes, as well as numerous structures to which the invention can be applicable will be readily apparent to those of skill in the art upon review of the instant specification.

What is claimed is:

1. An HVAC controller comprising:

a controller configured to operate an algorithm that at least partially controls one or more components of an HVAC system; and

a touch screen dot matrix display coupled to the controller, the controller configured to display on the touch screen dot matrix display a first menu that includes a plurality of selection options that are each independently selectable by a user on the touch screen dot matrix display such that multiple selection options may be selected at the same time, wherein selection of an additional selection option does not cancel selection of a first selection option, the controller further simultaneously displaying one or more quick select touch buttons on the first menu that permit a user to quickly select two or more of the plurality of selection options by simply pressing one of the one or more quick select touch buttons displayed on the touch screen dot matrix display.

2. The HVAC controller of claim 1, wherein each of the selection options has an associated algorithm parameter, and wherein the controller is configured to permit the user to simultaneously change the associated algorithm parameters for each of the two or more of the plurality of selection options that are selected by pressing one of the one or more quick select touch buttons.

3. The HVAC controller of claim 2, wherein the controller displays a second menu that permits the user to simultaneously change the associated algorithm parameters for each of the two or more of the plurality of selection options that are selected by pressing one of the one or more quick select touch buttons.

4. The HVAC controller of claim 1, wherein the first menu comprises a schedule menu, and each of the plurality of selection options of the schedule menu correspond to a corresponding day of a week.

5. The HVAC controller of claim 4, wherein one of the quick select touch buttons comprises a WEEKDAY button that, when pressed, selects Monday, Tuesday, Wednesday, Thursday and Friday for scheduling.

62

6. The HVAC controller of claim 5, wherein one of the quick select touch buttons comprises a WEEKEND button that, when pressed, selects Saturday and Sunday for scheduling.

7. The HVAC controller of claim 6, wherein one of the quick select touch buttons comprises an ALL button that, when pressed, selects all days of the week for scheduling.

8. The HVAC controller of claim 4, wherein one of the quick select touch buttons comprises a WEEKEND button that, when pressed, selects Saturday and Sunday for scheduling.

9. The HVAC controller of claim 4, wherein one of the quick select touch buttons comprises an ALL button that, when pressed, selects all days of the week for scheduling.

10. The HVAC controller of claim 1, wherein the first menu comprises a schedule menu, and each of the plurality of selection options of the schedule menu correspond to a PERIOD of a day of a week.

11. The HVAC controller of claim 10, wherein one of the quick select touch buttons comprises a wake button that, when pressed, selects the wake period for all or selected days of the week.

12. The HVAC controller of claim 10, wherein one of the quick select touch buttons comprises a leave button that, when pressed, selects the leave period for all or selected days of the week.

13. The HVAC controller of claim 10, wherein one of the quick select touch buttons comprises a return button that, when pressed, selects the return period for all or selected days of the week.

14. The HVAC controller of claim 10, wherein one of the quick select touch buttons comprises a sleep button that, when pressed, selects the sleep period for all or selected days of the week.

15. The HVAC controller of claim 1, wherein when one of the plurality of selection options is independently selected by a user, a display indicator is displayed indicating that the selection option has been selected.

16. The HVAC controller of claim 1, wherein the plurality of selection options and the one or more quick select touch buttons are simultaneously displayed on a single screen of the touch screen dot matrix display.

17. An HVAC controller comprising:

a controller configured to operate an algorithm that at least partially controls one or more components of an HVAC system;

a touch screen dot matrix display coupled to the controller, the controller configured to display on the touch screen dot matrix display a plurality of available selection options that are each independently selectable by a user, the controller further simultaneously displaying one or more quick select touch buttons on the touch screen dot matrix display that permit a user to select two or more of the plurality of selection options by pressing one of the one or more quick select touch buttons, wherein each of the plurality of selection options correspond to a corresponding day of a week and wherein upon selection of one of the quick select touch buttons by a user, two or more of the plurality of selection options that correspond to the selected quick select touch button include a display indication designating selection on the touch screen dot matrix display; and

wherein each of the selection options has an associated algorithm parameter, and wherein the controller is configured to permit the user to simultaneously change the associated algorithm parameters for each of the two or

63

more of the plurality of selection options that are selected by pressing one of the one or more quick select touch buttons.

18. The HVAC controller of claim 17, wherein one of the quick select touch buttons comprises a WEEKDAY button that, when pressed, selects Monday, Tuesday, Wednesday, Thursday and Friday for scheduling. 5

19. The HVAC controller of claim 18, wherein one of the quick select touch buttons comprises a WEEKEND button that, when pressed, selects Saturday and Sunday for scheduling. 10

20. The HVAC controller of claim 19, wherein one of the quick select touch buttons comprises an ALL button that, when pressed, selects all days of the week for scheduling. 15

21. The HVAC controller of claim 17, wherein one of the quick select touch buttons comprises a WEEKEND button that, when pressed, selects Saturday and Sunday for scheduling.

22. The HVAC controller of claim 17, wherein one of the quick select touch buttons comprises an ALL button that, when pressed, selects all days of the week for scheduling. 20

23. A method for selecting two or more of a plurality of selection options of an HVAC controller, comprising:

displaying on a touch screen dot matrix display a first menu that includes a plurality of selection options that are each independently selectable by a user on the touch screen dot matrix display such that multiple selection options may be selected at the same time, wherein selection of an additional selection option does not cancel selection of a first selection option; 25 30

64

displaying one or more quick select touch buttons on the first menu simultaneously with the plurality of selection options that permit a user to quickly select two or more corresponding ones of the plurality of selection options by simply pressing one of the one or more quick select touch buttons; and

wherein upon selection of one of the one or more quick select touch buttons by a user, displaying on the touch screen dot matrix display selection indicators that indicate that the two or more selection options that correspond to the selected quick select touch button have been selected.

24. The method of claim 23, wherein each of the selection options has an associated algorithm parameter, comprising: permitting the user to simultaneously change the associated algorithm parameters for each of the two or more of the plurality of selection options that are selected by pressing one of the one or more quick select touch buttons.

25. The method of claim 24 wherein one of the quick select touch buttons comprises a WEEKDAY button that, when pressed, selects selection options Monday, Tuesday, Wednesday, Thursday and Friday for scheduling.

26. The method of claim 25, wherein one of the quick select touch buttons comprises a WEEKEND button that, when pressed, selects selection options Saturday and Sunday for scheduling.

27. The method of claim 26, wherein one of the quick select touch buttons comprises an ALL button that, when pressed, selects all days of a week for scheduling.

* * * * *